

Delivers the ultimate in outdoor bulk DEF dispensing, at the island, for the island fleet customer.

- Fiberglass manufactured unit
- Side access door with lockable latch for security.
- Island pad bolt through bottom skirt bracket for affixing to concrete pad or sump.
- Nozzle boot switch relay to operate pump.
- Incidentals include stainless steel auto nozzle with breakaway, 25' hose reel and 25' hose.

Construction

Dimensions 24" W x 69" H x 41" D





ISLAND Dispensers

Delivers the ultimate in outdoor bulk DEF dispensing, at the island, for the island fleet customer.

Dimensions and System Options

DEF Flow Meter

DESCRIPTION

Face-Mounted Display Meter

In-Line Pulse Meter

Options

DESCRIPTION

Thermostatically Controlled Heater

Insulated Nozzle Door and Hardware

Insulation Package

Benecor DEF Flow Meter

Strobe Light Warning for Low Temperature Inside Enclosure



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

Delivers the ultimate in outdoor bulk DEF dispensing, at the island, for the island fleet customer.

- Fiberglass manufactured unit
- Side access door with lockable latch for security.
- Island pad bolt through bottom skirt bracket for affixing to concrete pad or sump.
- Nozzle boot switch relay to operate pump.
- Incidentals include stainless steel auto nozzle with breakaway, 25' hose reel and 25' hose.

Construction

Dimensions 24" W x 69" H x 41" D



ISLAND Dispensers

Delivers the ultimate in outdoor bulk DEF dispensing, at the island, for the island fleet customer.

Dimensions and System Options

DEF Flow Meter

DESCRIPTION

Face-Mounted Display Meter

In-Line Pulse Meter

Options

DESCRIPTION

Thermostatically Controlled Heater

Insulated Nozzle Door and Hardware

Insulation Package

Benecor DEF Flow Meter

Strobe Light Warning for Low Temperature Inside Enclosure



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

Ideal for limited in-shop or island fueling space in a warm weather environment.

- Can be tied with on-site or off-site bulk tanks.
- Choice of submersible or centrifugal pump.
- Integrated nozzle boot switch.
- Stainless steel dispensing enclosure.
- Built-in bracket to mount directly to concrete.
- UL cUL enclosed electrical panel.
- Standard 20' hose (other lengths available).
- Automatic stainless steel nozzle with breakaway swivel.

Construction

Dimensions	12" W x 53" H x 12" D
------------	-----------------------





BULK Compact Dispensers

Delivers the ultimate in outdoor bulk DEF dispensing, at the island, for the island fleet customer.

Dimensions and System Options

Options

DESCRIPTION

Face Mount Digital Display Flow

In-Line Pulse Meter

Hose Reel with 25' Hose



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

Delivers the ultimate in flexibility.

- All stainless steel construction.
- Stand base mounts directly to concrete end tabs for added stability/bracket security.
- Incorporate any of Benecor's pumps (excluding submersible) for use as a pumping system
- Standard 20' hose (other sizes available).
- Optional Flow Meter available.

Construction

Dimensions	17" W x 49" H x 17" D
------------	-----------------------





Delivers the ultimate in flexibility.

Dimensions and System Options

DEF Flow Meter

DESCRIPTION	
Maximum Flow Rate	31.7 G/Min
Precision	±1% within the Flow Range
Working Temperature	14° F to 122° F (=10° C to 50° C)
Repetitiveness	0.2%
Loss of Pressure	<0.15 bar



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.

Delivers the ultimate in outdoor storage and dispensing of DEF for the fleet customer.

- 1/2 HP DEF centrifugal pump.
- Integrated nozzle boot switch.
- Fiberglass island mounted enclosure.
- UL, cUL enclosed electrical panel 25' hose reel with DEF hose.
- Automatic stainless steel nozzle with breakaway swivel, 25' hose reel and hose.
- Lockable front tank access door.
- Lockable rear tank access door for service.

Construction

Dimensions 84" W x 48" H x 47" D





Delivers the ultimate in outdoor storage and dispensing of DEF for the fleet customer.

Dimensions and System Options

DEF Flow Meter

DESCRIPTION

Maximum Flow Rate	31.7 G/Min
Precision	±1% within the Flow Range
Working Temperature	14° F to 122° F (=10° C to 50° C)
Repetitiveness	0.2%
Loss of Pressure	<0.15 bar



2325 Husky Way • Pacific, MO 63069
 (800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 

For use in commercial and retail locations where durability, ruggedness and affordability is required.

- Simple electronic computer.
- Stand-alone or interfaced to control device.
- RS485 interface or current loop or dual pulse output.
- Exclusive eCal™ (electronic calibration).
- Magnet activated totals display.
- Programmable unit of measure for US gallons, liters or imperial gallons.
- Self-contained (suction) models feature a 4-piston diaphragm pump.
- Back lit LCD displays.
- Self-contained (suction) models: single, 1-product, single hose.
- Remote models: single, 1-product, single hose.
- Lockable front tank access door, lockable rear tank access door for service.
- Expandable tank sizes available.

Construction

Operates	From 116V or 230V 60/50Hz
Electronics Operating Temperature	-22° F to +122° F (-30° C to +50° C)
Humidity	0-95% Condensing
Dimensions	96" W x 84" H x 47" D



**BENECOR**

DEF DISPENSING AND STORAGE

TOTE Retail Enclosures

For use in commercial and retail locations where durability, ruggedness and affordability is required.

Dimensions and System Options

Cold Weather Package

DESCRIPTION

Insulated Nozzle Door

Thermostatically Controlled Heater

Insulated Enclosure



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A. 



Smart solution built to deliver both durability and superiority to suit your unique situation.

- All truck tank dispensing systems come equipped with a DEF 12-volt pump (self-priming), 7 GPM, 12' power cord, in-line fuse and battery clips
- All stainless steel frame construction - will not be attacked by DEF or weather.
- Tank pan constructed to bolt to truck bed with vertical and horizontal slotted holes for optimal placement.
- Custom designed to mount behind truck bed diesel tank between the wheel wells.
- Available sizes: 32 gallon and 71 gallon polyethylene tank meets ISO standards for proper storage of DEF.
- Optional available 25' hose reel and integrated nozzle holder.
- All components of the BENECOR Truck Tank system are also available for individual sale.

Construction

Tank	32 Gallon DEF Tank (Customizable Item)
Hose	40' Delivery Hose (Customizable Item)
Pump and Mount	DEF 12-Volt
Base	Stainless Steel
Straps	Stainless Steel
Hardware	Necessary hardware included.



**BENECOR**

DEF DISPENSING AND STORAGE

TRUCK Tank Dispensers

Smart solution built to deliver both durability and superiority to suit your unique situation.

Dimensions and System Options



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.



Commercialized for Caterpillar and Cummins stationary power.

- Our insulated prime power solutions are built for reliability and durability in challenging warm and cold weather applications.
- Houses 500 gallon tank, 275 gallon tote, or 330 gallon tote.
- Power coated for durability.
- Transports easily and safely. Industrial fork lift pockets for easy lifting with full 500 gallon tank, 275 gallon tote or 330 gallon tote. Tote secured to structure for safe transport.
- Lockable insulated roller shutter door.
- Rear access door for convenient service entry.
- 25'-100' hose reel options.
- Optional unlimited feed stocking controls interface for generator or compressor farms.

Construction

Tank	500 Gallon, 275 Gallon Tote, or 330 Gallon Tote
Hose	25'-100' Hose Reel Options





Commercialized for Caterpillar and Cummins stationary power.

Dimensions and System Options

Extreme Col Weather Application Options

110V Electric Heater

Diesel Fired Heater with 2.5 Gallon Tank or Supply with Bulk Fuel Tanks

Power Supply Options

12V / 24V

110V

208-230V



2325 Husky Way • Pacific, MO 63069
(800) 325-3558 • Fax (636) 825-7300
www.husky.com • sales@husky.com

MADE IN THE U.S.A.

