

Service Station Equipment



EMCO[®]
WHEATON RETAIL

Table of Contents

Service Station Equipment

Underground Storage Tank Equipment

A0030/A0089 Fill Adapters	5-6
A0097 Fill Caps	7
A0076 Vapor Adapters	8
A0099 Vapor Caps	9
A0060 Emergency Shear Valves	10
A0063 Vapor Shear Valve	11
A1100 Overfill Prevention Valves/Assemblies	12-15
A0020 Drop Tubes	16
A0088/A0070 Coaxial Drop Tubes	17
A0079 Extractor Fittings	18-19
A0075/A0078 Ball Floats	20
A0066 Check Valve	21
A0750 Ball Valve	21
A0732 Underpump Union Check Valve	21
A0084 Pressure Vacuum Vents	22
A4103/A0785 Tank Vents	23
A0998 In-ground ID Markers	24
A0997 ID Tags	24
Z0838 Sealants	25

Spill Containment

Selection Chart	28-29
Replaceable	30-33
A1004 Single Wall Poly	30
A1005 Single Wall Stainless Steel	31
A1005 Below Grade	31
A1004 Double Wall Poly	32
A1005 Double Wall Stainless Steel	33
Non-Replaceable	34
A1004 Single Wall Poly	34
A1005 Single Wall Stainless Steel	34
Special Applications	35-37
A1004 Multi-Purpose Access Manhole	35
A1005 For Tank Monitor	35
A1005 Remote Fill	36-37
Retrofit	38-46
Franklin Fueling	39
OPW	40-41
OPW 500/700 Series Retrofit	42
Universal	43
Pomeco	44
Fairfield	44
Pemco	44
Emco	45-46
Accessories	47-48
Spill Containment Accessories	48-55
A0031 Riser Extensions	48
A7901 Pipe Nipples	49

Spill Containment Accessories, cont.

A0028 Riser Lock	50
A0333 Hand Pump	50
Tools and Test Equipment	50-51
Spill Containment Replacement Parts	52-55

Manholes

A0716 Composite Manholes	58-59
A0717 Standard Round Manholes	60-61
A0717 Square Manholes and Vaults	62-63
A0721 Monitoring Well Manholes	64-65
A0727/A0728 Well Protectors	66

Phase I EVR

Caps and Adapters	68
A1004EVR Spill Containment	69-70
Installation and Maintenance Tools	70
A1100EVR Overfill Prevention	71
A0020EVR Drop Tubes	72

Phase II EVR

A4005EVR Balance Vapor Recovery Nozzle	74
A4119EVR Coaxial SafeBreak®	75
Repair and Replacement Kits/Service Tools	76

Nozzles

A4005/A4015 Balance Vapor Recovery	77
A6000 Truck Stop	79
A2500 Nozzle Replacement Parts	80

Dispenser Accessories


A2119/A2219 Standard SafeBreaks®	81
A3019/A3219 Standard SafeBreaks®	82
A4119EVR Coaxial SafeBreak®	83
A0360 Hose Swivels	84
A4110EVR Coaxial Hose Swivel	84
A4043/A4041 Coaxial Splitters	85
563639 Adapters	86
A0010 Flow Regulators	86
A0021 Standard Hose Assemblies	87
A0069 Dispenser Frames	88
A0718-729 Dispenser Conversion Frames	89
A0729-048 E-Stop Switch Pedestal	90

Competitor Cross Reference

Numerical Index

Warranty Policy


Service Station Layout



Product	Page	Product	Page
1 A4015 Balanced Nozzle	77	15 A1004 Double Wall Manhole	32
2 A4119 Coaxial SafeBreak®	83	16 A0097 Tight Fill Cap	7
3 A3219 1" Standard SafeBreak®	82	17 A0030 Fill Adapter, Fixed or Swivel	5
4 A2219 3/4" Standard SafeBreak®	81	18 A1100 Overfill Prevention Valve	12
5 A0021 Standard Hose	87	19 A0028 Riser Lock	50
6 A0360 Swivel	84	20 A0031 Riser Extension	48
7 A6000 Truck Stop Nozzle	79	21 A0099 Vapor Adapter Cap	9
8 A0063 Vapor Shear Valve	11	22 A0076 Vapor Adapter, Fixed or Swivel	8
9 A0060 Emergency Valve	10	23 A1004 Double Wall Manhole	32
10 A0066 Multi-Purpose Check Valve	21	24 A0717 Standard Manhole	61
11 A0750 Ball Valve	21	25 A0585 Extractor Pipe Cap	19
12 A0717 Standard Manhole, Steel or Composite (A0716)	61 59	26 A0079 Extractor Assembly	18
13 A0717 Standard Manhole or Composite (A0716)	61 59	27 A0075 Ball Float	20
14 A0097-010 Fill Cap for Tank Probe	7	28 A0720 Monitoring Well Cap	64
		29 A0721 Monitoring Well Manhole	65
		30 A0084 Pressure Vacuum Vent	22

EMCO®

WHEATON RETAIL



NOT TO SCALE


Fill Adapters

A0030-I24S Fill Swivel Adapter

Material

Body: Brass
O-rings: Viton®
Gasket: Buna-N

Viton® is a registered trademark of DuPont Dow Elastomers.



The Emco Wheaton A0030-I24S Swivel Adapter prevents accidental loosening of the adapter from the fill pipe. The adapter incorporates two set screws that are tightened after torquing the adapter. These screws prevent the adapter from becoming loose. The A0030-I24S is **field serviceable** with o-ring kit p/n 494301 and gasket kit p/n 569924. Use with the A0097 Fill Cap. Use the Emco Wheaton A0081 Adapter Wrench for installation.

■ Approved under Phase I EVR
Executive Order VR-105
Complies with EPA 40 CFR Part 63




Model No.	Material	Thread Size	Cam & Groove	Weight
A0030-I24S	Brass	4" Female NPSM	4"	8.1 lbs.
A0030-I24SE	Nickle Plated Brass For E85 Applications	4" Female NPSM	4"	8.1 lbs.

569924 Gasket Replacement Kit
494301 O-ring Replacement Kit

A0030 Fill Adapter

Material

Body: See table below
Gasket: Buna-N



The Emco Wheaton A0030 Adapter is designed for use with conventional dual point fill systems. Features recessed threads for easy installation and positive seating on riser pipes. Use with the A0097 Fill Cap.

■ CARB E.O. G-70-97-A
ULC Listed MH27242

The A0030-024 series are notched for use with the A0032-001 Adapter Clamp to comply with EPA 40 CFR Part 63 requirements.

Model No.	Material	Thread Size	Lugs	Cam & Groove	Weight	A	B	C
**A0030-014	Aluminum	4" Female NPSM	No	4"	1.8 lbs.	5.5"	4.0"	2.0"
***A0030-014F	Aluminum	4" Female NPSM	No	4"	1.9 lbs.	5.5"	4.0"	2.0"
A0030-024	Brass	4" Female NPSM	Yes	4"	2.6 lbs.	4.9"	2.5"	1.7"
*A0030-024A	Aluminum	4" Female NPSM	No	4"	1.0 lbs.	4.9"	2.5"	1.7"
A0030-024BA	Aluminum	4" Female BSPP	Yes	4"	1.0 lbs.	4.9"	2.5"	1.7"

* Most common variant

** Phase I EVR E.O.VR-105

*** For Franklin INCON Tank Probe


409628 Gasket Replacement Kit

Fill Adapters

A0089, A0096 Coaxial Fill Adapters

Material

Body: Aluminum



Emco Wheaton Coaxial Vapor Recovery Adapters are designed for standard coaxial fill systems and coaxial systems with self-sealing vapor lines. Features recessed threads for easy installation and positive seating on riser pipes. Use with the A0097 Fill Cap. Use Emco Wheaton A0081 Adapter Wrench for installation.

The A0089 and A0096 are notched for use with the A0032-001 Adapter Clamp to comply with EPA 40 CFR Part 63 requirements.

Model No.	Use With	Size	A	Weight
A0089-001	A0088 Self-sealing Coaxial Drop Tube	4" Female NPSC	3.0"	1.6 lb
A0096-001	A0070 Coaxial Drop Tube	4" Female NPSC	2.5"	1.8 lbs

A0032 Adapter Clamp

Material

Body: Aluminum



The Emco Wheaton A0032-001 Adapter Clamp installs on the riser pipe or pipe nipple. The A0032 is used with the following non-swivel adapters: A0089, A0096, A0030-024, A0030-024A, A0076-005 and A0076-010. The tabs are aligned with the notches on the adapter, and the three set screws are tightened to prevent the adapter from loosening in use, in compliance with EPA 40 CFR Part 63 requirements.



Installed on pipe nipple with A0030-024A Adapter

Model No.	Material	Size	Weight
A0032-001	Aluminum	4"	0.7 lbs.


A0033 Debris Collector

The Emco Wheaton A0033-004 Debris Collector attaches to the bottom of any fill adapter to prevent large debris from entering the underground storage tank. There are no restrictions during a fuel drop, and the center hole allows for fuel sampling.

Material

Rag Stopper: Stainless Steel
Gasket: Nitrile

Model No.	Weight
A0033-004	0.25 lbs.




Installed in A0030-124S Swivel Fill Adapter

Fill Caps

A0097 Fill Cap

Material

Body: Aluminum
Cams: Brass
Links: Steel
Seal: Buna-N



The Emco Wheaton A0097-005 series Top Seal Fill Cap is designed for use on conventional A0030 or coaxial A0089 and A0096 Adapters. The cap is lockable and features a self-aligning, toggle-action design with center collar to prevent breakage; made of corrosion resistant aluminum.

Model No.	Cam & Groove	Weight
A0097-005	4"	1.6 lbs.
563939	Replacement Gasket	




■ CARB E.O. G-70-97-A
Approved under Phase I EVR
Executive Order VR-105
Complies with EPA 40 CFR Part 63

A0097-004LP Low Profile Fill Cap

Material

Body: Aluminum
Lever: Ductile Iron
Gasket: Buna-N




The A0097-004LP Low Profile Fill Cap is designed for use when there is limited space between the top of the adapter and the spill containment lid. The cap is painted gray.

Model No.	Cam & Groove	Weight
A0097-004LP	4"	3.5 lbs.
563939	Replacement Gasket	

A0097-010 Fill Cap

Material

Body: Aluminum
Cams: Brass
Links: Steel
Seal: Buna-N



The A0097-010 Fill Cap has the same features of the A0097-005 Fill Cap and is designed with a grommet to allow a cable to pass through the cap. The A0097-010 comes with two sizes of leak tight connector nut fittings: .125"-.375" and .190"-.250".

Model No.	Cam & Groove	Weight
A0097-010	4" For Tank Probe	1.7 lbs.
563939	Replacement Gasket	



■ Approved under Phase I EVR
Executive Order VR-105


Vapor Adapters

A0076-I24S Vapor Swivel Adapter

Material

Body: Brass
O-rings: Viton®
Gasket: Buna-N

Viton® is a registered trademark of DuPont Dow Elastomers.



- Approved under Phase I EVR Executive Order VR-105
Complies with EPA 40 CFR Part 63



The Emco Wheaton A0076-I24S Vapor Swivel Adapter prevents accidental loosening of the adapter from the vapor pipe. The adapter incorporates two set screws that are tightened after torquing the adapter. These screws prevent the adapter from becoming loose. The A0076-I24S is **field serviceable** with o-ring kit p/n 494301 and gasket kit p/n 569924. Use with the A0099-002 Vapor Cap. Use the Emco Wheaton A0081 Adapter Wrench for installation.

Model No.		Thread Size	Cam & Groove	Weight
A0076-I24S	Brass	4" Female	4"	9.1 lbs.
A0076-I24SE	Nickle Plated Brass for E85 Applications	4" Female	4"	9.1 lbs.


569924 Gasket Replacement Kit

494301 O-ring Replacement Kit

A0076 Vapor Adapter

Material

Body: Aluminum
Gasket: Buna-N



The Emco Wheaton A0076 Vapor Adapter is used in dual point fill systems on the vapor return line. It features a poppet design which seals off the vapor path and external lugs on the adapter body for easy installation. Use with the A0099-002 Vapor Cap.

- CARB E.O. G-70-97-A
ULC Listed MH27242

The A0076-005 is notched for use with the A0032-001 Adapter Clamp to comply with EPA 40 CFR Part 63 requirements.

Model No.	Thread Size	Cam & Groove	Weight	A	B	C
A0076-002	3" Female NPSM	4"	2.9 lbs.	4.0"	5.6"	5.00"
*A0076-005	4" Female NPSM	4"	3.1 lbs.	4.9"	5.6"	4.88"
A0076-009	3" Female BSPP	4"	2.1 lbs.	4.0"	5.6"	5.00"

562803 Gasket for A0076-005


*Most common variant

Vapor Caps

A0099 Vapor Adapter Cap

Material

Body: Aluminum
Cams: Brass
Links: Steel
Seal: Buna-N



The Emco Wheaton A0099-002/003 Vapor Adapter Cap features a cam system designed for Stage I vapor recovery dual point systems. The cap is lockable and features a self-aligning, toggle-action design with center collar to prevent breakage. The A0099 is made of corrosion resistant aluminum, powdered coated orange for vapor line identification.

■ CARB E.O. G-70-97-A
Approved under Phase I EVR
Executive Order VR-105
Complies with EPA 40 CFR Part 63

Model No.	Cam & Groove	Weight
A0099-002	4"	1.4 lbs.
A0099-003	4" w/chain	1.8 lbs.

563939 Replacement Gasket



A0099-001TEST Vapor Test Cap


The A0099-001TEST Vapor Test Cap is used when performing a pressure decay test. The cap incorporates the same features as the A0099-002 Vapor Cap. The extended tube underneath the cap opens the poppet on the vapor adapter. Pressure is injected through the Schrader valve, and a gauge can be connected to the barbed fitting.



A0099-004LP Low Profile Vapor Adapter Cap

Material

Body: Aluminum
Lever: Ductile Iron
Gasket: Buna-N




The A0099-004LP Low Profile Cap is designed for use when there is limited space between the top of the adapter and the spill containment lid. The cap is painted orange for vapor line identification.

Model No.	Cam & Groove	Weight
A0099-004LP	4"	3.5 lbs.

563939 Replacement Gasket

Emergency Shear Valves

A0060 Underpump Emergency Valve



■ UL Listed MH6518
ATEX FTZUI4ATEX0204

Available with Stainless Steel Body and Top for E85/DEF/Ultra Low Sulfur Diesel

The Emco Wheaton A0060 Emergency Shear Valve incorporates a replaceable shear section and a heat sensitive fusible link assembly. The valve can be manually operated to facilitate dispenser maintenance and incorporates a $\frac{3}{8}$ " test port. The closing poppet assembly is positioned out of the fuel flow path to minimize pressure drop. The A0060 utilizes a standard three boss mounting arrangement. Available in single or double poppet variants.

UL Listed
for up to 85%
Ethanol

Material

Body: Cast Iron
Spring: Stainless Steel
Seal: Viton®

Viton® is a registered trademark of DuPont Dow Elastomers.

Model No.	Stainless Steel	Description	Inlet	Outlet	Weight	A	B
* A0060-002	A0060-002S	1 1/2" Single Poppet	Female	Male	5.7 lbs.	6.9"	2.2"
A0060-003	A0060-003S	1 1/2" Single Poppet	Female	Female	5.6 lbs.	6.7"	1.7"
A0060-015	A0060-015S	1 1/2" Single Poppet	Female BSPT	Male BSPT	5.7 lbs.	7.9"	3.2"
A0060-016	A0060-016S	1 1/2" Single Poppet	Female BSPT	Female BSPT	5.6 lbs.	6.9"	2.2"
A0060-022	A0060-022S	1 1/2" Double Poppet	Female	Male	5.8 lbs.	7.9"	3.2"
A0060-023	A0060-023S	1 1/2" Double Poppet	Female	Female	5.7 lbs.	6.9"	2.2"
A0060-025	A0060-025S	1 1/2" Double Poppet	Female BSPT	Male BSPT	5.8 lbs.	7.9"	3.2"
A0060-026	A0060-026S	1 1/2" Double Poppet	Female BSPT	Female BSPT	5.7 lbs.	6.9"	2.2"

*Most common variant

Replacement Parts

Part No.	Description	Outlet	Weight
492938	1 1/2" Replacement Top; 1 Poppet	Male	2.2 lbs.
492939	1 1/2" Replacement Top; 1 Poppet	Female	2.3 lbs.
493885	1 1/2" Replacement Top; 1 Poppet	Female BSPT	1.4 lbs.
493886	1 1/2" Replacement Top; 1 Poppet	Male BSPT	1.6 lbs.
493887	1 1/2" Replacement Top; 2 Poppets	Male	2.7 lbs.
493888	1 1/2" Replacement Top; 2 Poppets	Female	2.7 lbs.
493889	1 1/2" Replacement Top; 2 Poppets	Male BSPT	1.6 lbs.
493890	1 1/2" Replacement Top; 2 Poppets	Female BSPT	1.6 lbs.
492963K	Fusible Link Kit		0.2 lbs.
564036	Control Arm		

Note: To order the A0060 Shear Valve with the A0065 Mounting Kit (see following page), replace the first digit of the variant number with a 1. Example: A0060-102, single poppet male with mounting kit.

Emergency Shear Valves


A0063EVR Vapor Shear Valve




Material

Body: Cast Iron
Spring: Stainless Steel
Seal: Viton®

Viton® is a registered trademark of DuPont Dow Elastomers.



■ UL Listed MH10206



The Emco Wheaton A0063EVR Vapor Shear Valve installs on vapor recovery lines under the dispenser to eliminate the escape of vapors in the event of a collision to the dispenser. The double poppet valve incorporates a 1.5" female NPT connection to the underground piping and a 1" female NPT connection to dispenser piping. The valve incorporates a 3/8" test port. The A0063EVR is approved for use with all CARB certified pre-EVR and EVR Phase II vapor recovery systems. Includes 3 boss mounting hardware.

Model No.	Description	Inlet	Outlet	Weight
A0063EVR-024	1 1/2" Double Poppet	Female	Female	5.2 lbs.

A0065 Mounting Kit

The Emco Wheaton A0065-001 Mounting Kit is used to mount the A0060 and A0063 to the dispenser pan stabilizer bar. The kit includes 2 U-bolts, 4 lock washers, 4 hex nuts, 3 socket head counter-sunk screws and mounting plate. Weighs 3.8 lbs.

To order the A0065 Mounting Kit with the A0060 Shear Valve, replace the first digit of the variant number with a 1.


Example: A0060-102, single poppet male with mounting kit.



Overfill Prevention Valve

A1100 Guardian Overfill Prevention Valve

- **Drain Bleed Valve** for hose drainage, reduces unnecessary delays. Spring loaded and includes soft seat for positive seal
- **Protective Retainer** over floats for protection during installation, shipping and operation
- **Cast-in Dip Stick Diverters** permit stick gauging at any tank level without damage to internal parts
- **Vertical Slide Float Design** for protection during installation
- **Auto Relatch** prevents premature shut-off
- **Integrated Body Design** suitable for both dual point and coaxial drop tubes - one valve for all applications
- **Shock Relief Valve** incorporated to reduce line shock
- **Viton® O-Rings** at base of valve seals drop tube to valve to protect against leakage



The Emco Wheaton A1100 is a two stage overfill prevention valve for use in both dual point and coaxial drop tubes, gravity feed systems. Easily installs in a new or existing drop tube assembly for economical compliance with EPA regulations. Internal float design to eliminate any chance of the floats getting caught on tank walls or the riser pipe as well as to prevent float damage during installation. Stick diverter and automatic spring loaded poppet retract from the flow path when the valve is not in operation, allowing for stick gauging at any tank level. Compatible with all standard fuels. Special variants are available for most bulk chemical applications.

Material

Body: Aluminum
Floats: HDPE
Seals: Viton®

Viton® is a registered trademark of Dupont Dow Elastomers.

Specifications





Weight: 5.2 lbs.
Diameter: 3.76"
Length: 18.0"

Approvals

CARB Approval	99-8
ULC	MH21164
ATEX	FTZU98EX0733
Florida DEP	EQ-414

Overfill Prevention Valve

AI100 Guardian Overfill Prevention Systems



A7900-004H
4" NPSM Male Pipe Plug without o-ring



A0379-001
Remote Fill Cage Adjustable NPSM



A0079-444
Tee 4"x4"x4"



A0479-001
Dip Stick Port



A0081-006JP
Remote Fill Piping Test Assembly

Overfill Prevention Valve

AI100 Guardian Dual Point Overfill Prevention Systems

All assemblies are factory welded; bottom tube screws to top tube/valve assembly. No Epoxy

Assemblies are vapor tight and meet the EPA 40 CFR Part 63 requirements.

All standard AI100 variants are acceptable for use with up to E25 ethanol blend gasoline and B20 Biodiesel blends. Higher percentage ethanol or biodiesel require use of the “E” variant.

Model No.	Description
493192	Kit, Assembly Valve to Tube
493436	Remote Fill Kit
493734S	Support Collar
566675	Drill Fixture
571814	Drill Fixture, Remote Fill Assemblies
A0379-001	Remote Fill Cage Adjustable NPSM
A0379-101	Remote Fill Cage Adjustable BSPP




566675 Drill Fixture
Aligns holes for drilling to ensure vapor-tight seal



571814 Drill Fixture
For remote fill applications



493734S
Support
Collar



Model No.	Description	Upper Length A	Lower Length B	Overall Length C	Max. Burial Depth	Nominal Tank Dia.	Weight
AI100-010	Valve Only	N/A	N/A	N/A	N/A	N/A	5.2 lbs.
AI100-010E	Valve Only E85	N/A	N/A	N/A	N/A	N/A	5.7 lbs.
AI100-011	Valve Only Remote Fill Export	N/A	N/A	N/A	N/A	N/A	5.0 lbs.
AI100-054S	Remote Fill Export	50"	100"	162"	N/A	N/A	28.5 lbs.
AI100-054SC	Remote Fill w/Cage BSPT Export	50"	100"	158"	N/A	N/A	27.9 lbs.
AI100-054SCN	Remote Fill w/Cage NPT	50"	100"	162"	N/A	N/A	25.0 lbs.
AI100-055SRF	Remote Fill Assembly and Kit	73"	83"	168"	4.0'*	8'	64.3 lbs.
AI100-056SRF	Remote Fill Assembly and Kit	85"	95"	192"	4.0'*	10'	66.5 lbs.
AI100-053S	Dual Pt Screw Together	60"	50"	122"	5.0'	6'	22.1 lbs.
AI100-055S	Dual Pt Screw Together	73"	83"	168"	6.0'	8'	25.2 lbs.
AI100EVR-055	Dual Pt Screw Together Phase I EVR	73"	83"	168"	6.0'	8'	25.2 lbs.
AI100-056SE	Dual Pt Screw Together E85	85"	95"	192"	7.0'	10'	27.4 lbs.
AI100-056S	Dual Pt Screw Together	85"	95"	192"	7.0'	10'	27.2 lbs.
AI100EVR-056	Dual Pt Screw Together Phase I EVR	85"	95"	192"	7.0'	10'	27.2 lbs.
AI100-057S	Dual Pt Screw Together	85"	121"	218"	6.8'	12'	30.3 lbs.
AI100EVR-057	Dual Pt Screw Together Phase I EVR	85"	121"	218"	6.8'	12'	30.3 lbs.
AI100EVR-057E	Dual Pt Screw Tgthr Phase I EVR, E85	85"	121"	218"	6.8'	12'	30.5 lbs.
AI100-058S	Dual Pt Screw Together	123"	121"	256"	10.0'	12'	31.0 lbs.
AI100EVR-058	Dual Pt Screw Together Phase I EVR	123"	121"	256"	10.0'	12'	31.0 lbs.

The AI100 Overfill Prevention Valve is not recommended for tanks under 6' in diameter.

Lengths A and B are measured from the shut-off point. Maximum burial depth assumes 95% shut-off and 6" clearance between top of drop tube and inside bottom of containment manhole lid.

***SRF variants are designed for precise burial depth of 46"-54"; tank top access required.** For additional applications and installation instructions, call Customer Service at 800-234-4394.

Custom lengths available. OPV systems can be ordered as a package with a fill cap and fill adapter. Contact Customer Service for ordering information.

Overfill Prevention Valve

AI100 Guardian Coaxial Overfill Prevention Systems


The Emco AI100-08X assemblies are factory welded; bottom tube screws to top tube/valve assembly. No Epoxy. These assemblies are vapor tight and meet the EPA 40 CFR Part 63 requirements.

The Emco AI100-08X series is the only Coaxial Overfill Prevention Valve that will pass the Pressure Decay Test (CARB TP201). Note: must be used with the Emco A0089-001 Fill Adapter.

All standard AI100 variants are acceptable for use with up to E25 ethanol blend gasoline and B20 Biodiesel blends. Higher percentage ethanol or biodiesel require use of the “E” variant.

Accessories:

Model No.	Description
493785S	Spring-loaded Self-sealing Vapor Collar
A0089-001	Fill Adapter for AI100-08X series
A0096-001	Fill Adapter for AI100-06X series



Model No.	Coaxial Screw Together	Upper Length A	Lower Length B	Overall Length C	Max. Burial Depth	Nominal Tank Dia.	Weight
AI100-065S*	Coaxial Screw Together	67.5"	95"	163"	5.6'	8'	21.9 lbs.
AI100-066S*	Coaxial Screw Together	67.5"	107"	175"	5.5'	10'	24.7 lbs.
AI100-067S*	Coaxial Screw Together	67.5"	133"	201"	5.3'	12'	22.5 lbs.
AI100-067E*	Coaxial Screw Together E85	67.5"	133"	201"	5.3'	12'	22.5 lbs.
AI100-085S	Coaxial Self-Sealing Screw Together	67.5"	95"	163"	5.4'	8'	23.0 lbs.
AI100-086S	Coaxial Self-Sealing Screw Together	67.5"	107"	175"	5.3'	10'	26.3 lbs.
AI100-087S	Coaxial Self-Sealing Screw Together	67.5"	133"	201"	5.1'	12'	28.0 lbs.
AI100-087E	Coaxial Self-Sealing Screw Together E85	67.5"	133"	201"	5.1'	12'	28.0 lbs.

OPV systems can be ordered as a package with a fill cap and fill adapter. Contact Customer Service at 800-234-4394 for ordering information.

The AI100 Overfill Prevention Valve is not recommended for tanks under 6' in diameter.

Custom lengths available: Please contact our Customer Service Department.

Lengths A and B are measured from the shut-off point. Maximum burial depth assumes 95% shut-off and 6" clearance between top of drop tube and inside bottom of containment manhole lid.

*The AI100-06x series are non-poppeted and will not pass the pressure decay test. The -06X series must be used with the Emco A0096-001 Fill Adapter.


Drop Tubes

A0020 Drop Tube


Material

Tube: Aluminum

O-ring: Buna



Standard Rolled Edge



Heavy Duty Collar Kit
(p/n 493391) Application

■ CARB Executive Order G-70-97-A

The Emco Wheaton A0020 Drop Tube is designed for use in both conventional non-vapor recovery and dual point vapor recovery systems. Emco drop tubes are a full .05" thick for added strength and to reduce shipping damage. Tube I.D. is 3.815"; O.D. is 3.915". Custom lengths are available upon request.

Phase I EVR

Model No.	Size	Length	Weight
A0020-004	4"	12'	13.0 lbs.
** A0020-004E	4"	12'	13.0 lbs.
* A0020-005	4"	15'	16.1 lbs.
** A0020-005E	4"	15'	16.1 lbs.
A0020-007	4"	17'	18.2 lbs.
**A0020-007E	4"	17'	18.2 lbs.
A0020-008	4"	14'	14.0 lbs.
A0020-021	4"	21'	22.3 lbs.
*** A0020-133	4"	10'	11.0 lbs.
*** A0020-144	4"	12'	13.0 lbs.

* Most common variant

** E85

*** Includes handle

Model No.	Size	Length	Weight
Rolled Edge Collar			
A0020EVR-004	4"	12'	13.0 lbs.
A0020EVR-005	4"	15'	16.1 lbs.
A0020EVR-007	4"	17'	18.2 lbs.
A0020EVR-008	4"	14'	14.0 lbs.
Heavy Duty Collar			
A0020EVR-004	4"	12'	13.7 lbs.
A0020EVR-005	4"	15'	16.8 lbs.
A0020EVR-007	4"	17'	18.9 lbs.
A0020EVR-008	4"	14'	14.7 lbs.

Model No.	Description	Weight
493391	Riser Collar Kit	2.0 lbs.
561683	Collar Gasket	0.5 oz.



493391
Riser Collar Kit

Drop Tubes

A0088 Coaxial Drop Tube (Self-Sealing)

Emco Wheaton's exclusive A0088 Drop Tube is used in coaxial fill systems to provide a self-sealing vapor line. The spring-loaded assembly secures the tube against the adapter during normal storage. When the coaxial elbow is connected, the elbow pushes the tube down from the adapter to create a path for vapor return. Vapor recovery efficiency is rated in excess of 95%. Custom lengths are available upon request.

Model No.	Size	I.D.	O.D.	Length	Weight
A0088-101	4"	3.815"	3.915"	12'	12.4 lbs.
A0088-101A*	4"	3.815"	3.915"	12'	14.0 lbs.
A0088-116	4"	3.815"	3.915"	16'	16.0 lbs.

*Includes A0089-001 Fill Adapter

Model No.	Description	Weight
493197	Self-Sealing Coax Collar Kit	1.6 lbs.

Adapter: A0089-001

Cap: A0097-005

Material
Tube: Aluminum

■ CARB Executive Order G-70-97-A



A0070 Coaxial Drop Tube

The Emco Wheaton A0070 Drop Tube is used for coaxial vapor recovery tight fill systems and has a vapor recovery efficiency rate in excess of 95%. The A0070 tube design is narrow at the top but flares out to a standard tube size in the middle. This "vaselike" design helps to decrease flow restriction by creating a pull through effect in the system. Custom lengths are available upon request.

Model No.	Size	I.D.	O.D.	Length	Weight
A0070-101	4"	3.815"	3.915"	12'	12.3 lbs.
A0070-116	4"	3.815"	3.915"	16'	15.9 lbs.

Model No.	Description	Weight
493195	Coax Collar Kit	0.8 lbs.

Adapter: A0096-001

Cap: A0097-005

Material
Tube: Aluminum



Extractor Fittings

A0079 Float Valve Extractor


The Emco Wheaton A0079 Extractor Assembly consists of a cast iron extractor body and an internal “bar style” cage. This cage holds any length of A0075 Ball Float (sold separately). The A0079 may be ordered with a variety of port combinations to accommodate tank venting and Stage II vapor recovery piping. The A0079 is also available without an extractor cage for applications that do not require the use of a ball float and is an economical alternative for direct manifold systems.

The A0079 Extractor Assemblies are available with electroless nickel coating for compatibility with E85 fuels. To order, add an E suffix to the part number.

Material

Extractor Body: Cast Iron

The A0079 may be installed as part of the Emco Phase I EVR System without violating the Executive Order (VR-105)



Cross Style

Model No.	Top/Bottom Thread	Outlet Threads A & B	Cage Size	Weight
Extractor with Cage				
A0079-019	4"	3" x 2"	2"	11.9 lbs.
A0079-020	4"	2" x 2"	2"	10.7 lbs.
A0079-025	4"	3" x 3"	2"	12.0 lbs.
A0079-028	4" BSPT	2" x 2" BSPT	2"	9.6 lbs.
Extractor Body only				
A0079-043	4" BSPT	2" x 2" BSPT	N/A	8.5 lbs.
A0079-050	4"	2" x 2"	N/A	8.5 lbs.
* A0079-051	4"	3" x 2"	N/A	10.8 lbs.
A0079-052	4"	3" x 3"	N/A	11.8 lbs.

* Most common variant



Tee Style

Model No.	Top/Bottom Thread	Outlet Threads B	Cage Size	Weight
Extractor with Cage				
A0079-119	4"	3"	2"	14.6 lbs.
A0079-120	4"	2"	2"	10.7 lbs.
A0079-122	4" BSPT	2" BSPT	2"	8.5 lbs.
Extractor Body only				
A0079-150	4"	2"	N/A	7.1 lbs.
A0079-152	4"	3"	N/A	8.7 lbs.
A0079-444	4"	4"	N/A	8.7 lbs.
A0079-444M (male base)	4"	4"	N/A	10.1 lbs.



Extractor Fittings

Accessories

A0179 Extractor Cage

The Emco Wheaton A0179 Extractor Cage is designed with a 3" male thread and a 2" female thread for use with the Emco Wheaton A0079 Extractor Valve and A0075 Ball Float. Use with A0560-003 Bar Style Extractor Wrench.

Material

Body: Aluminum
Handle: Steel
O-ring: Buna-N

Model No.	Description	Weight
A0179-002	2" Extractor Cage	1.2 lbs.



A0279 Extractor Cage Test Plug

The Emco Wheaton A0279 Extractor Cage Test Plug is designed for performing pressure decay tests on your underground piping and storage tank systems. Use with A0560-003 Bar Style Extractor Wrench.

Material

Body: Aluminum
Handle: Steel
O-ring: Buna-N
Plug: Cast Iron

Model No.	Description	Weight
A0279-001	Test Plug	1.9 lbs.



A0560 Extractor Wrench

Emco Wheaton Extractor Wrenches are required to install and remove the A0584 and A0585 pipe caps and appropriate angle check, foot, and float valve extractor cages. Two head styles are available - the historic Emco Wheaton Buckeye style wrench and the A0560-003, industry standard "bar style" wrench.

Model No.	Size	Weight	Extractor Pipe Cap	Extractor Fitting
A0560-001 Buckeye	1 1/2"	8.0 lbs.		A0677-003
A0560-002 Buckeye	2"	10.0 lbs.	A0584-003	A0563-002, -004
A0560-003 Bar Style	2"	9.3 lbs.	A0585-003	A0079,A0179,A0279



A0585-003 Extractor Pipe Cap


The Emco Wheaton A0585-003 Bar Style Extractor Pipe Cap is designed to thread directly on the extractor access pipes. Requires the A0560-003 Bar Style Extractor Wrench.

Material

Body: Aluminum
Handle: Steel
O-ring: Buna-N

Model No.	Size	Weight
A0585-003	4" Female	0.8 lbs.

569924 Gasket Replacement Kit



Ball Floats

A0075 Ball Float

The Emco Wheaton A0075 Ball Float Valves are designed to restrict product flow in the event of a UST overfill. The A0075 meets EPA requirements for a slow down device.

The A0075 Ball Float Valves are available with electroless nickel coating for compatibility with E85 fuels. The ball and spring are stainless steel. To order, add an E suffix to the part number.

Material

Tube: Aluminum
Ball: Stainless Steel

The A0075 may be installed as part of the Emco Phase I EVR System without violating the Executive Order (VR-105)

Model No.	Tube Diameter	Tube Length	Overall Length	Bleed Hole	Weight
*A0075-001	2"	4.75"	9.52"	.125"	1.2 lbs.
A0075-002	2"	9.62"	14.39"	.125"	1.8 lbs.
A0075-004	2"	8.00"	12.77"	.125"	1.6 lbs.
A0075-006	2"	6.87"	11.64"	.062"	1.5 lbs.
A0075-010	2"	18.00"	22.77"	.125"	2.8 lbs.
A0075-013	2"	13.75"	18.52"	.125"	2.4 lbs.
A0075-015	2"	15.75"	20.75"	.125"	2.6 lbs.
A0075-017	2"	17.75"	22.52"	.125"	2.8 lbs.



■ CARB Executive Order
G-70-97-A

*Most common variant. Custom lengths are available upon request.

A0078 Ball Float with Extractor Cage


The Emco Wheaton A0078 combination Ball Float and Extractor Valve Cage meet the EPA requirements for a 30 minute warning device.

The A0078 Ball Floats with cages are available with electroless nickel coating for compatibility with E85 fuels. The ball and spring are stainless steel. To order, add an E suffix to the part number.

Material

Tube: Aluminum
Ball: Stainless Steel

Model No.	Tube Diameter	Tube Length	Overall Length	Bleed Hole	Weight	Replaces OPW
A0078-006A	2"	6.75"	11.52"	.0625"	2.8 lbs.	53VML-0060
A0078-008	2"	8.75"	13.52"	.0625"	3.2 lbs.	
A0078-008A	2"	8.75"	13.52"	.0625"	3.6 lbs.	
A0078-009A	2"	9.75"	14.52"	.0625"	4.0 lbs.	53VML-2090
A0078-012A	2"	12.75"	17.52"	.0625"	5.3 lbs.	53VML-0120
A0078-015	2"	15.75"	20.52"	.0625"	6.0 lbs.	
A0078-018A	2"	18.75"	23.52"	.0625"	7.6 lbs.	53VML-0180
*A0078-020	2"	20.50"	25.27"	.0625"	7.9 lbs.	
A0078-021A	2"	21.75"	26.52"	.0625"	8.8 lbs.	53VML-0210
A0078-308	3"	8.00"	12.77"	.0625"	3.2 lbs.	
A0078-312	3"	12.13"	16.27"	.0625"	4.5 lbs.	
A0078-318	3"	18.13"	22.27"	.0625"	6.9 lbs.	




*Most common variant. Custom lengths are available upon request.

A0066 Multi-Purpose Check Valve

Material

Body: Cast Iron
Poppet: Brass
Springs: Stainless Steel
Seal: Viton®

Viton® is a registered trademark of DuPont Dow Elastomers



Pressure relief valve incorporates o-ring seal

Pressure relief setting
15 psi - 35 psi


The Emco Wheaton A0066 Multi-Purpose Check Valve is designed to maintain prime and prevent unnecessary tripping of mechanical leak detectors. The A0066 is mounted at the submersible pump to relieve thermal expansion between the pump and dispenser. Vent poppet is designed to provide positive sealing and more accurate pressure relief settings. Heavy wall cast iron body construction.

Model No.	Size	Weight
A0066-020	2"	2.1 lbs.

A0750 Ball Valve

Material

Body: Brass
Seal: Teflon PTFE




The Emco Wheaton A0750 Ball Valve is a full port 2" valve. Thread depth is .865"; inside diameter is 2". 150 psi working pressure.

Model No.	Size	Weight
A0750-200	2"	4.1 lbs.

A0732 Underpump Union Check Valve

Material

Body: Plastic
Internal Components: Brass



Shown as installed
in union coupling

The Emco Wheaton A0732 Union Check Valve is inserted into a standard 1 1/2" union to stop the loss of prime. Body is plastic; all other components are brass. The A0732-002 includes a screen.

Model No.	Size	Weight
A0732-001	1 1/2"	0.4 lbs.
A0732-002	1 1/2"	0.3 lbs.

Vents


A0084 Pressure Vacuum Vent

The Emco Wheaton A0084 is an internal pressure vacuum valve that restricts vapor escape during product drops. Typically installs on the top of the vent pipes from the underground or aboveground fuel storage tanks. The vent valve is equipped with a wire mesh screen designed to protect the storage tank vents against intrusion and blockage from rain water and debris. A normally closed poppet within the valve opens to allow the tank to vent (see chart below). The body and cap are anodized aluminum for corrosion-free service. UL Listed.

Material

Body: Aluminum
Seal: Viton®
Cap: Aluminum
Screen: 40 Mesh Stainless Steel

Viton® is a registered trademark of DuPont Dow Elastomers.



■ UL Listed MH46838

Model No.	Inlet	Pressure Setting	Vacuum Setting	Weight	Replaces
A0084-014	2" BSPT	13.86" H ₂ O (8.00oz.)	0.8" H ₂ O (0.50oz.)	2.6 lbs.	A0084-100 A0084-101 A0084-004 A0084-009
A0084-105	2" Slip On	2.00" H ₂ O (1.14oz.)	0.8" H ₂ O (0.50oz.)	2.0 lbs.	
A0084-200	2" Thread-on	2.00" H ₂ O (1.14oz.)	3.0" H ₂ O (1.88oz.)	2.0 lbs.	
A0084-201	2" Slip On	2.00" H ₂ O (1.14oz.)	3.0" H ₂ O (1.88oz.)	2.6 lbs.	
A0084-204	2" Thread-on	13.86" H ₂ O (8.00oz.)	0.8" H ₂ O (0.50oz.)	2.9 lbs.	
A0084-209	2" Slip On	13.86" H ₂ O (8.00oz.)	0.8" H ₂ O (0.50oz.)	2.9 lbs.	
Meets EPA 40 CFR Part 63 Requirements					
* A0084-038	2" Thread-on	2.5"-6.0" WC	6.0"-10.0" WC	2.9 lbs.	
A0084-103	2" Slip-on	2.5"-6.0" WC	6.0"-10.0" WC	2.6 lbs.	
A0084-338	3" Thread-on	2.5"-6.0" WC	6.0"-10.0" WC	3.5 lbs.	
A0084-303	3" Slip-on	2.5"-6.0" WC	6.0"-10.0" WC	3.2 lbs.	

*Most common variant

A0085 Vent Adapters

Material

Body: Aluminum
Seal: Buna

Slip-on versions incorporate 3 set screws




The Emco A0085 is used with A0084 2" vents to connect to 3" riser pipes. Available in thread-on and slip-on versions. Aluminum construction.

Model No.	Description	Weight
A0085-302	3" Thread-on	0.6 lbs.
A0085-302S	3" Slip-on	0.6 lbs.

A4103 Upward “V” Vent

Material

Body: Polyethylene
Cap: Polyethylene
Screws: Steel
Screen: 40 Mesh Stainless Steel



■ UL Listed MH10206


The Emco Wheaton A4103 Upward “V” Vent utilizes a straight-up “V” design to rapidly disperse vapors. Slip-on style vent attaches to the pipe with three screws for easy installation. Screen can be easily removed for cleaning. Designed in accordance with NFPA 30.

Model No.	Inlet	Material	Weight
A4103-002	2"	Polyethylene	0.7 lbs.

A0785 Downward Mushroom Vent

Material

Body: Aluminum
Screen: Brass



The Emco Wheaton A0785 Downward Mushroom Vent is designed for downward venting of storage tanks. The 30 mesh stainless steel screen can be easily removed for cleaning. The A0785 threads onto either 1.5 or 2.0 inch vent lines. Clear coated aluminum for corrosion-free service.

Model No.	Inlet	Material	Weight
A0785-001	1.5" & 2" Female	Aluminum	1.0 lbs.
A0785-101	1.5" & 2" Female BSPT	Aluminum	1.0 lbs.

Product Identification

A0998 In-Ground ID Marker

The Emco Wheaton A0998 In-Ground ID Marker is used to identify the product grade in the underground tanks. The A0998 is constructed of die cast aluminum for a smooth appearance. The lower profile with beveled edge minimizes tripping hazard. Weighs .35 lbs.



Emco design easy to retrofit for flush mount on hard concrete



Competitor's bar profile does not accommodate retrofit application



<u>Model No.</u>	<u>Description</u>	<u>Model No.</u>	<u>Description</u>
A0998-001	ID Marker #1	A0998-017	ID Marker Kerosene
A0998-002	ID Marker #2	A0998-018	ID Marker Low-Sulfur Diesel
A0998-003	ID Marker #3	A0998-019	ID Marker High-Sulfur Diesel
A0998-004	ID Marker #4	A0998-020	ID Marker Mid-Grade
A0998-005	ID Marker #5	A0998-021	ID Marker Regular
A0998-006	ID Marker #6	A0998-027	ID Marker Diesel
A0998-007	ID Marker #7	A0998-030	ID Marker E-10
A0998-008	ID Marker Chevron Supreme	A0998-032	ID Marker Chevron #2 Diesel
A0998-011	ID Marker Chevron Regular	A0998-034	ID Marker E-85
A0998-012	ID Marker Chevron Diesel	A0998-042	ID Marker Tank 1/20000/Reg
A0998-013	ID Marker Chevron Plus	A0998-060	ID Marker Super
A0998-014	ID Marker Unleaded	A0998-116	ID Marker Gas/1500 Gal/Additive
A0998-015	ID Marker Plus	A0998-117	ID Marker Gas/2000 Gal/Additive
A0998-016	ID Marker Premium	A0998-118	ID Marker Diesel/1500 Gal/Additive

A0997 Tank ID Tag

The Emco Wheaton A0997 Tank ID Tag clamps onto the storage tank fill pipe to identify the product grade, tank number and tank size. Tag is black anodized for improved readability. Customized etching is available. Weighs .15 lbs.

<u>Model No.</u>	<u>Description</u>	<u>Model No.</u>	<u>Description</u>
A0997-030	Super	A0997-095	76 Premium Gasoline
A0997-032	Regular	A0997-201	w/Gal Tags - Unleaded
A0997-033	Diesel		Regular w/Extender
A0997-050	Tank #1	A0997-203	w/Gal Tags - Ultra
A0997-051	Tank #2	A0997-204	w/Gal Tags - Unleaded
A0997-059	Vapor Recovery		Low Sulfur Diesel
A0997-093	76 Regular Gasoline		



Z0838 Anti-Seize Joint Seal



Emco Wheaton Anti-Seize Joint Seal is recognized as one of the most versatile compounds available for its excellent sealing properties. Resistant to heat, cold and vibration.

Model No.	Size	Weight
Z0838-001	1/8 oz.	0.1 lbs.
Z0838-005	1/2 pint	1.3 lbs.

Z0839 Super Duty Sealant

The Z0839 Urethane Super Duty Sealant is a general purpose sealant for fuel and water. Net contents 10.3 oz.






Model No.	Weight
Z0839-001	1.2 lbs.








**SPILL
CONTAINMENT**

Spill Containment Selection Chart





Replaceable

Single Wall		5 Gallon				15 Gallon
Poly		Stainless Steel				Poly
<u>Thread On</u>		<u>Thread On</u>	<u>Slip On</u>	<u>Glass On</u>		<u>Thread On</u>
						
Phase I EVR		Below Grade		Remote Fill		Phase I EVR
Drain: AI004-316A	AI004EVR-316A	AI005-518ADR	AI005-905D	AI005-517ADR		AI004EVR-215A
No Drain: AI004-317A	AI004EVR-317A	AI005-518A	AI005-905	AI005-517A	AI005-517AF	AI004EVR-216A
Page #: 30	69	31	31	31	36-37	30, 69




Double Wall		5 Gallon				15 Gallon
Poly		Stainless Steel				Poly
<u>Thread On</u>		<u>Thread On</u>	<u>Slip On</u>	<u>Glass On</u>		<u>Thread On</u>
						
Phase I EVR				Remote Fill		Phase I EVR
Drain: AI004-316G	AI004EVR-316S	AI005-518GPDR		AI005-517SFDR		AI004EVR-215S
No Drain: AI004-317G	AI004EVR-317S	AI005-518G	AI005-518GP	AI005-517GS	AI005-517SF	AI004EVR-216S
Page #: 32	69	33	33	33	36-37	32, 69

Spill Containment Selection Chart

Non-Replaceable

5 Gallon		15 Gallon	
Poly		Stainless Steel	
Thread On	Thread On	Slip On	Slip On
			
Slimline	Fatboy		For Tank Monitor
Drain: A1004-010	A1004-003	N/A	N/A
No Drain: A1004-011	A1004-004	A1005-501	A1005-015TM
Page #: 34	34	34	35


Retrofit

OPW 500/700		Competitor Buckets	
Poly Double Wall	Stainless Steel Primary Poly Secondary	Stainless Steel	
Thread On	Thread On		
			Replaces Franklin Fueling 39 OPW 40-41 Universal 43 Fairfield 44 Pemco 44 Pomeco 44 Emco 45-46
Drain: A1004-316R	A1005-518RD	A1005-505C	
No Drain: A1004-317R	A1005-518R		
Page #: 42	42		

Spill Containment

Replaceable Single Wall

Poly (HDPE)



Adjustment screws allow change in elevation $\pm 1 \frac{1}{2}$ " (5 gallon models)




5 Gallon Thread-On



A1004EVR-316A
A1004EVR-317A

■ ULC Listed MH21149
Florida DEP #EQ-524



Replaces all A1004-210 variants
Installs on 16" centers

Never Break Concrete - Easily repair or replace primary unit from grade without breaking concrete

Heavy duty, snow plow resistant ductile iron, powder coated plow rim

Water-resistant cast iron lid with built-in handle, exclusive triple wiper seal and vent valve. Meets AASHTO H20 wheel loading


HDPE Liner

4 inch NPT or BSPT thread

15 Gallon Thread-On



■ ULC Listed MH21149
Florida DEP #EQ-695



Phase I EVR Certified
Executive Order VR-105

Model No.	Description	Application	Lid Dia.	Lid Wt.	Total Wt.
A1004-316A	Single wall poly, 16" center; drain, 5 gal	Fill/Vapor	13.2"	15.9 lbs.	65.3 lbs.
A1004-317A	Single wall poly, 16" center; no drain, 5 gal	Vapor	13.2"	15.9 lbs.	64.8 lbs.
A1004EVR-316A	Single wall poly, 16" center; drain, 5 gal, Phase I EVR	Fill/Vapor	13.2"	15.9 lbs.	66.0 lbs.
A1004EVR-317A	Single wall poly, 16" center; no drain, 5 gal, Phase I EVR	Vapor	13.2"	15.9 lbs.	63.0 lbs.
A1004EVR-215A	Single wall poly, drain, 15 gal, Phase I EVR	Fill/Vapor	17.3"	30.0 lbs.	126.0 lbs.
A1004EVR-216A	Single wall poly, no drain, 15 gal, Phase I EVR	Fill/Vapor	17.3"	30.0 lbs.	126.1 lbs.

Add a "V" to the end of the variant number to include an A0076-124S Vapor Swivel Adapter and A0099-002 Vapor Cap; add an "X" to include an A0030-124S Fill Swivel Adapter and A0097-005 Fill Cap. Refer to pages 52-55 for repair kits and replacement parts.

Spill Containment

Replaceable Single Wall

Stainless Steel

Never Break Concrete - Easily repair or replace primary unit from grade without breaking concrete

Installs on 16" centers

Heavy duty, snow plow resistant ductile iron, powder coated plow rim


Water-resistant cast iron lid with built-in handle, exclusive triple wiper seal and vent valve. Meets AASHTO H20 wheel loading

16 gauge stainless steel liner

HDPE skirt


5 Gallon Slip-on

■ ULC Listed MH21149
Florida DEP #EQ-753




5 Gallon Thread-on

■ ULC Listed MH21149
Florida DEP #EQ-753



5 Gallon Below-Grade

■ ULC Listed MH21149




Below Grade - One-piece, Rust-free Stainless Steel Construction

Grade level lid is composite; also available in cast iron or diamond plate with finger hole

Below grade lid is water-resistant cast iron lid with built-in handle, vent valve and exclusive triple wiper seal

Available with drain or drain plug; models with drain include a Phase I EVR approved pull/push drain design

Optional locking mechanism for below grade lid




Model No.	Description	Application	Lid Dia.	Lid Wt.	Total Wt.
Slip-on					
A1005-517A	Single wall stainless steel, no drain, 5 gal	Fill/Vapor	13.2"	15.9 lbs.	59.0 lbs.
A1005-517ADEF	Single wall stainless steel, no drain, composite lid, 5 gal	DEF	13.2"	6.6 lbs.	49.7 lbs.
A1005-517ADR	Single wall stainless steel, drain, 5 gal	Fill/Vapor	13.2"	15.9 lbs.	59.5 lbs.
Thread-on					
A1005-518A	Single wall stainless steel, no drain, 5 gal	Fill/Vapor	13.2"	15.9 lbs.	80.7 lbs.
A1005-518ADR	Single wall stainless steel, drain, 5 gal	Fill/Vapor	13.2"	15.9 lbs.	81.2 lbs.
A1005-518ADRDEF	Single wall stainless steel, drain, composite lid, 5 gal	DEF	13.2"	6.6 lbs.	
A1005-905	Below grade, stainless steel, 18" manhole, drain plug, 5 gal	Fill/Vapor	17.0"	13.5 lbs.	78.8 lbs.
A1005-905D	Below grade, stainless steel, 18" manhole, drain, 5 gal	Fill/Vapor	17.0"	13.5 lbs.	79.0 lbs.
A1005-915	Below grade, stainless steel, 18" manhole, drain plug, 15 gal	Fill/Vapor	17.0"	13.5 lbs.	97.8 lbs.
A1005-915D	Below grade, stainless steel, 18" manhole, drain, 15 gal	Fill/Vapor	17.0"	13.5 lbs.	98.0 lbs.

Add a "V" to the end of the variant number to include an A0076-124S Vapor Swivel Adapter and A0099-002 Vapor Cap; add an "X" to include an A0030-124S Fill Swivel Adapter and A0097-005 Fill Cap. Refer to pages 52-55 for repair kits and replacement parts.

Spill Containment

Replaceable Double Wall

Poly (HDPE)



Adjustment screws allow change in elevation $\pm 1 \frac{1}{2}$ " (5 gallon models)




5 Gallon Thread-On



A1004EVR-316G
A1004EVR-317G

■ ULC Listed MH21149
Florida DEP #EQ-741



Replaces all A1004-210 variants
Installs on 16\"

Never Break Concrete - Easily repair or replace primary unit from grade without breaking concrete

Heavy duty, snow plow resistant ductile iron, powder coated plow rim

Water-resistant cast iron lid with built-in handle, exclusive triple wiper seal and vent valve. Meets AASHTO H20 wheel loading

HDPE liner


Galvanized skirt

4 inch NPT or BSPT thread

15 Gallon Thread-On



■ ULC Listed MH21149
Florida DEP #EQ-695



Phase I EVR Certified
Executive Order VR-105

Model No.	Description	Application	Lid Dia.	Lid Wt.	Total Wt.
A1004-316G	Double wall poly, 16" center, drain, gauge, 5 gal	Fill/Vapor	13.2"	15.9 lbs.	83.4 lbs.
A1004-316S-CM	Double wall poly, 16" center, drain, sensor, 5 gal	Fill/Vapor	13.2"	15.9 lbs.	78.0 lbs.
A1004EVR-316S	Double wall poly, 16" center, drain, 5 gal, Phase I EVR	Fill/Vapor	13.2"	15.9 lbs.	84.0 lbs.
A1004-316S-CMX	Double wall poly, 16" center, drain, sensor ready, 5 gal	Fill	13.2"	15.9 lbs.	77.5 lbs.
A1004-317G	Double wall poly, 16" center, no drain, gauge, 5 gal	Fill/Vapor	13.2"	15.9 lbs.	79.9 lbs.
A1004EVR-317S	Double wall poly, 16" center, no drain, 5 gal, Phase I EVR	Fill/Vapor	13.2"	15.9 lbs.	79.9 lbs.
A1004-317S-CM	Double wall poly, 16" center, no drain, sensor, 5 gal	Fill/Vapor	13.2"	15.9 lbs.	77.5 lbs.
A1004EVR-215S	Double wall poly, drain, 15 gal, Phase I EVR	Fill/Vapor	17.3"	30.0 lbs.	151.0 lbs.
A1004EVR-216S	Double wall poly, no drain, 15 gal, Phase I EVR	Fill/Vapor	17.3"	30.0 lbs.	151.1 lbs.
A1004EVR-215SF4	Glass-on remote fill, double wall poly, drain, 15 gal	Remote Fill	17.3"	30.0 lbs.	
A1004EVR-216SF4	Glass-on remote fill, double wall poly, no drain, 15 gal	Remote Fill	17.3"	30.0 lbs.	

Add a "V" to the end of the variant number to include an A0076-124S Vapor Swivel Adapter and A0099-002 Vapor Cap; add an "X" to include an A0030-124S Fill Swivel Adapter and A0097-005 Fill Cap. Refer to pages 52-55 for repair kits and replacement parts.


Spill Containment

Replaceable Double Wall

Stainless Steel



5 Gallon Slip-on



■ ULC Listed MH21149
Florida DEP #EQ-764R

Never Break Concrete - Easily repair or replace primary unit from grade without breaking concrete

Installs on 16\" centers


Heavy duty, snow plow resistant ductile iron, powder coated plow rim

Water-resistant cast iron lid with built-in handle, exclusive triple wiper seal and vent valve. Meets AASHTO H20 wheel loading

16 gauge stainless steel liners

HDPE skirt

5 Gallon Thread-on



■ ULC Listed MH21149
Florida DEP #EQ-764R

A1005-518GP

Model No.	Description	Application	Lid Dia.	Lid Wt.	Total Wt.
Slip-on					
A1005-517G	Double wall stainless steel, no drain, gauge, 5 gal	Fill/Vapor	13.2"	15.9 lbs.	84.5 lbs.
A1005-517GDEF	DW stainless steel, no drain, gauge, composite lid, 5 gal	DEF	13.2"	6.6 lbs.	75.8 lbs.
A1005-517S-CM	Double wall stainless steel, no drain, sensor, 5 gal	Fill/Vapor	13.2"	15.9 lbs.	68.3 lbs.
A1005-517GS	DW stainless steel, no drain, gauge, 5 gal, Allegheny seal Viton®	Fill/Vapor	13.2"	15.9 lbs.	78.5 lbs.
A1005-517GSN	DW stainless steel, no drain, gauge, 5 gal, Allegheny seal Nitrile	Fill/Vapor	13.2"	15.9 lbs.	78.5 lbs.
Thread-on					
A1005-518G	Double wall stainless steel, no drain, gauge, 5 gal	Fill/Vapor	13.2"	15.9 lbs.	85.3 lbs.
A1005-518GP	Stainless steel primary, poly secondary, no drain, gauge, 5 gal	Fill/Vapor	13.2"	15.9 lbs.	91.0 lbs.
A1005-518GPDR	Stainless steel primary, poly secondary, drain, gauge, 5 gal	Fill/Vapor	13.2"	15.9 lbs.	91.5 lbs.

Add a "V" to the end of the variant number to include an A0076-124S Vapor Swivel Adapter and A0099-002 Vapor Cap; add an "X" to include an A0030-124S Fill Swivel Adapter and A0097-005 Fill Cap. Refer to pages 52-55 for repair kits and replacement parts.

Viton® is a registered trademark of DuPont Dow Elastomers.

Spill Containment

Non-Replaceable Single Wall

Poly (HDPE)

Heavy duty, snow plow resistant ductile iron, powder coated plow rim

HDPE liner and skirt

4 inch NPT or BSPT thread


Cast iron lid with built-in handle, meets AASHTO H20 wheel loading

Slimline: Water-resistant lid with exclusive triple wiper seal


5 Gallon Thread-on



A1004EVR-010
A1004EVR-011



Slimline



Fatboy

■ ULC Listed MH21149
Florida DEP #EQ-524

Model No.	Description	Lid Dia.	Lid Wt.	Total Wt.
* A1004-010	Slimline, cast iron lid, drain, 5 gal	15.3"	20.0 lbs.	49.7 lbs.
A1004-011	Slimline, cast iron lid, no drain, 5 gal	15.3"	20.0 lbs.	49.8 lbs.
A1004-012	Slimline, cast iron lid, drain, BSPT, 5 gal	15.3"	20.0 lbs.	49.7 lbs.
A1004-003	Fatboy, cast iron lid, drain, 5 gal	16.3"	22.0 lbs.	62.5 lbs.
A1004-004	Fatboy, cast iron lid, no drain, 5 gal	16.3"	22.0 lbs.	62.2 lbs.
* A1004-005	Fatboy, cast iron lid, drain, BSPT, 5 gal	16.3"	22.0 lbs.	62.5 lbs.

Refer to pages 52-55 for repair kits and replacement parts.

*Most common variant

Stainless Steel


Stainless steel spill containment with Nitrile seals

Heavy duty, snow plow resistant ductile iron, powder coated plow rim

Water-resistant cast iron lid with built-in handle and exclusive triple wiper seal, meets AASHTO H20 wheel loading

5 Gallon Slip-on

■ ULC Listed MH21149
Florida DEP #EQ-524



Model No.	Description	Application	Lid Dia.	Lid Weight	Total Weight
A1005-501	Cast iron lid, 5 gal	4" riser pipe	15.3"	20 lbs.	43.0 lbs.
A1005-502	Cast iron lid, 5 gal	3" riser pipe	15.3"	20 lbs.	43.1 lbs.

Can be ordered with an A0333-004 Hand Pump (refer to page 50); add a "P" to the end of the variant number. Refer to page 52 for replacement lids.

Special Applications

Tank Monitor

15 Gallon Slip-on


5" Offset Pipe Entry for Tank Monitor

Available for use with 2" or 4" riser pipe


16 gauge stainless steel containment will not rust

Stainless steel bolts and Nitrile seals on bottom flange



Water-resistant ductile iron lid with built-in handle and exclusive triple wiper seal, meets AASHTO H20 load rating



A1005-010TMA



A1005-015TME



Model No.	Description	Application	Lid Dia.	Lid Weight	Total Weight
A1005-010TM	Cast iron lid, 15 gal	2" riser pipe	17.3"	30 lbs.	90.0 lbs.
A1005-010TMA	Cast iron lid, 15 gal	2" & 4" riser pipe, 3/4" coupling	17.3"	30 lbs.	
A1005-015TM	Cast iron lid, 15 gal	4" riser pipe	17.3"	30 lbs.	110.0 lbs.
A1005-015TME	Cast iron lid, 15 gal	4" riser pipe, 3/4" coupling	17.3"	30 lbs.	

Refer to page 52 for replacement lids.



Multi-Purpose Access Manhole

Includes lid, rim and skirt assembly

Heavy duty, snow plow resistant ductile iron, powder coated rim

Water-resistant cast iron lid with built-in handle and exclusive triple wiper seal, meets AASHTO H20 wheel loading

HDPE skirt



Model No.	Description	Lid Dia.	Lid Weight	Total Weight
A1004-014	Slimline - Lid, rim and skirt assembly	15.3"	20.0 lbs.	39.6 lbs.

Refer to pages 52 for replacement lids.



Spill Containment

Special Applications

Remote Fill



5 Gallon Glass-On



Creates true double wall containment from spill bucket to the piping run

Assembly comes complete with 4" Dualoy® 3000/LCX or Red Thread® 4" single wall stub, ready for installation into the elbow and clamshell



Primary and secondary containment vessels are rust-proof stainless steel

Water-resistant cast iron lid with built-in handle and exclusive triple wiper seal, meets H20 load rating

Includes EZ-Gage for instant monitoring of interstitial space

15 Gallon Glass-On

■ ULC Listed MH21149



Special Applications

Remote Fill

Model No.	Description	Lid Dia.	Lid Wt.	Total Wt.
A1005-517AF	Single wall, stainless steel, no drain, LCX, 5 gal	13.2"	15.9 lbs.	72.8 lbs.
A1005-517SF	Double wall, stainless steel, no drain, gauge, LCX, 5 gal	13.2"	15.9 lbs.	96.2 lbs.
A1005-517SF-CM	Double wall, stainless steel no drain, gauge, w/sensor, LCX, 5 gal	13.2"	15.9 lbs.	94.8 lbs.
A1005-517SF64	Double wall, stainless steel, no drain, gauge, Red Thread®, 5 gal	13.2"	15.9 lbs.	
A1005-517SFD	Double wall, stainless steel, drain plug, gauge, LCX, 5 gal	13.2"	15.9 lbs.	96.4 lbs.
A1005-517SFD64	Double wall, stainless steel, drain plug, gauge, Red Thread®, 5 gal	13.2"	15.9 lbs.	
A1005-517SFD R	Double wall, stainless steel, drain, gauge, LCX, 5 gal	13.2"	15.9 lbs.	96.7 lbs.
A1005-517SFD R64	Double wall, stainless steel, drain, gauge, Red Thread®, 5 gal	13.2"	15.9 lbs.	
A1005-517SF3T	Double wall, stainless steel, no drain, gauge, 3" LCX, 5 gal	13.2"	15.9 lbs.	
A1004EVR-215SF4	Double wall poly, drain, gauge, LCX, 15 gal	17.3"	30.0 lbs.	
A1004EVR-216SF4	Double wall poly, no drain, gauge, LCX, 15 gal	17.3"	30.0 lbs.	
A1005EVR-616SF4	DW SST primary, poly secondary, no drain, LCX, 15 gal	17.3"	30.0 lbs.	145.0 lbs.

Refer to pages 52-54 for replacement parts.

Overfill Prevention Components



A7900-004H

4" NPSM Male Pipe
Plug without o-ring



A0379-001

Remote Fill Cage
Adjustable NPSM



A0079-444

Tee 4"x4"x4" NPT




A0479-001

Dip Stick Port



A0081-006JP

Remote Fill Piping
Test Assembly



Remote Fill
Buried

Spill Containment

Retrofit

Stainless Steel

**Convert your obsolete poly bucket to state-of-the-art stainless steel
- no excavation required**



Before



After

- The containment vessel completely isolates the existing manhole; the lid seals inside the stainless steel vessel
- Water-resistant cast iron lid with built-in handle and exclusive triple wiper seal, meets AASHTO H20 wheel loading
- Models available for virtually all common competitors' buckets - Emco will provide custom designs for rare or unique applications. Models can be customized to accommodate specific height requirements. Contact our Customer Service Department (800-234-4394) for ordering information. Data sheets available on our website (www.emcoretail.com).
- US Patent 8,425,145 B2; other patents pending

■ ULC Listed MH21149
Florida DEP EQ-753
EQ-764R (Double Wall)
North Carolina DENR
PEMEX PXR-SC-GVES-
SAFP-SPTF-80-2013



Cast Iron Cover with
Triple Wiper Seal

Stainless Steel
Containment Vessel

Stainless Steel Bolts
Flange
O-ring Seal



Double wall variants
include EZ-Gage


For drain options,
contact our Customer
Service Department
(800-234-4394)

Spill Containment

Retrofit


Franklin Fueling Stainless Steel

EBW 702, 703, 705



Rim 17.25"; Lid 14"


EBW 715, 725



EBW 715, 725 Below Grade




Rim 19.75"; Lid 19"



Phil-Tite 400



Rim 16"; Lid 14"



Model No.	Repairs	A	Min. Ht. B	Weight
A1005-505CE	EBW 702,703,705	9.75"	11.13"	26.0 lbs.
A1005-505CES	EBW 702,703,705 Short	7.70"	9.25"	24.9 lbs.
A1005-505CEI5	EBW 715,725 15 Gallon	16.00"	17.50"	30.0 lbs.
A1005-505CEBG	EBW 702,705, 715 Below Grade	10.31"	13.50"	25.6 lbs.
A1005-505CFI	Phil-Tite 400	8.88"	16.38"	30.0 lbs.
A1005-505DPEB	Drain Plug Kit for EBW 705,715			00.1 lbs.

Inserts without drains will require purchase of the proper drain plug kit for the existing spill container.

Refer to pages 47-53 for installation and replacement items.


Spill Containment

Retrofit

OPW Stainless Steel




Rim 16.0"
Lid 13.75"




Rim 15.75"
Lid 12.5"

OPW I-2100



OPW I-2105


Offset



The I-2100 and I-2105 series are identified with "I-2100 Series" or "IC Series" printed on the lid. You must determine if the spill containment has a 1" offset and a rubber boot (right photo). This indicates that it is a I-2105 (slip-on) series, and will require a different retrofit kit than the I-2100 series. Refer to table below.




OPW ISC-2100



OPW ISC-2105

Offset



Model No.	Repairs OPW	A	Min. Ht. B	Weight
A1005-505C	I-2100 Series	10.0"	12.00"	31.0 lbs.
A1005-505CDR	I-2100; Includes Drain	10.0"	12.00"	30.5 lbs.
A1005-505CS	I-2100 Short	8.7"	10.75"	27.0 lbs.
A1005-505CD	I-2100 Double Wall	10.0"	12.00"	34.0 lbs.
A1005-505CZ	I-2100 Crooked Riser	10.0"	12.00"	30.0 lbs.
A1005-505CZDR	" "; Includes Drain	10.0"	12.00"	30.0 lbs.
A1005-505CZS	" "; Short	8.7"	10.75"	30.0 lbs.
A1005-505C5	I-2105 Offset	10.0"	12.00"	26.0 lbs.
A1005-505CC	ISC-2100 Series	10.0"	12.00"	24.0 lbs.
A1005-505CC5	ISC-2105 Offset	10.0"	12.00"	23.0 lbs.

Drain Plug Kit	Description
A1005-505DP	Drain Plug Kit, I-2100/I-2105
A1005-505DPE	Drain Plug Kit w/Epoxy

Inserts without drains will require purchase of the proper drain plug kit for the existing spill container.

Refer to pages 47-53 for installation and replacement items.


Spill Containment

Retrofit OPW Stainless Steel

OPW 4000




Rim 16.375"; Lid 13.13"




OPW 84D




Rim 16.0"; Lid 13.75"



OPW 101BG Below Grade



Rim 20.5"; Lid 20.0"



Model No.	Repairs OPW	Weight
A1005-505C4*	4000	24.0 lbs.
A1005-505CA	84D	41.0 lbs.
A1005-505CBG	101BG	39.0 lbs.
A1005-505DP	Drain Plug Kit, I-2100/I-2105	0.3 lbs.
A1005-505DPE	Drain Plug Kit w/Epoxy	0.7 lbs.

*Not available with a drain option.

Inserts without drains will require purchase of the proper drain plug kit for the existing spill container.

Refer to pages 47-53 for installation and replacement items.

Spill Containment

Retrofit

OPW 500/700

No excavation required - use existing riser pipe

Eliminates all OPW primary and secondary containers

Diamond plate steel lid bolts to existing OPW rim

Spill containment unit includes cast iron, water-resistant lid with exclusive triple wiper seal; meets H20 load rating


Includes EZ-Gage for instant monitoring of interstitial space

Full Emco Wheaton warranty on complete single wall and double wall buckets




The **A0081-001R Retrofit Lid Wrench** is required for installation of the A1005 stainless steel versions. The A0081-001R can also be used on the A1004 poly versions.

Polyethylene (HDPE) Double Wall



A1004-316R ■ Florida DEP #EQ-741

Stainless Steel Primary Polyethylene Secondary



A1005-518R ■ Florida DEP #EQ-764R

<u>Single Wall</u>	Primary Liner		Secondary Liner		Drain	Sensor	Cap & Swivel Adapter	Weight
A1004-316RA	Polyethylene	Thread-on	N/A		Yes	No	No	118 lbs.
A1005-516RA	Stainless Steel	Slip-on	N/A		No	No	No	99 lbs.
A1005-516RAD	Stainless Steel	Slip-on	N/A		Yes	No	No	100 lbs.
<u>Double Wall</u>								
A1004-316R	Polyethylene	Thread-on	Polyethylene	Thread-on	Yes	No	No	133 lbs.
A1005-518R	Stainless Steel	Slip-on	Polyethylene	Thread-on	No	No	No	116 lbs.
A1005-518RD	Stainless Steel	Slip-on	Polyethylene	Thread-on	Yes	No	No	117 lbs.
A1005-518RDX	Stainless Steel	Slip-on	Polyethylene	Thread-on	Yes	No	Yes	127 lbs.
A1005-518R-CM	Stainless Steel	Slip-on	Polyethylene	Thread-on	No	Yes	No	118 lbs.

Spill Containment

Retrofit

Universal Stainless Steel



69RT, 71CD
Rim 15"; Lid 12.75"




69RT, 71CD; 70C-DW
Rim 15.5"; 12.5" Lid




70C; 71CD
Rim 15.75"; Lid 15"

Universal 69RT, 71CD



Universal 70C



Model No.	Repairs	Min. Ht. A	Weight
A1005-505CU	Universal 69RT, 71CD; Thread-on	9.25"	26.0 lbs.
A1005-505CU70	Universal 70C; Slip-on	N/A	29.0 lbs.
A1005-505DPU	Drain Plug Kit, 69RT, 71CD		0.4 lbs.

Inserts without drains will require purchase of the proper drain plug kit for the existing spill container.


Refer to pages 47-53 for installation and replacement items.

Spill Containment


Retrofit

Pomeco Stainless Steel

Pomeco 111KP, 111KB



Pomeco 211




Model No.	Repairs	Min. Ht. A	Weight
A1005-505CPI	Pomeco 111KP, 111KB	N/A	25.0 lbs.
A1005-505CP	Pomeco 211	12.38"	42.3 lbs.

Refer to pages 47-53 for installation and replacement items.


Retrofit

Fairfield, Pemco Stainless Steel

Fairfield SCM-5



Pemco 112



Model No.	Repairs	Weight
A1005-505CF5	Fairfield SCM-5	29.9 lbs.

Model No.	Repairs	A	Weight
A1005-505CPem	Pemco 112	9.50"	24.0 lbs.
A1005-505CPED	Pemco 112 Double Wall	9.75"	31.0 lbs.

Refer to pages 47-53 for installation and replacement items.


Spill Containment

Retrofit Emco Stainless Steel

Emco A1004-010 (Slimline)



Rim 17.6"; Lid 15.3"



Model No.	Repairs	Min. Ht. A	Weight
A1005-505CEW3	Emco A1004-010 Series	10.50"	26.0 lbs.
A1005-505CEW3DR	Emco A1004-010 Series, Includes Drain	11.50"	26.0 lbs.


*Minimum height is measured from the inside lip of the rim to the bottom of the bucket.

Refer to pages 47-53 for installation and replacement items.

Emco A1003



Rim 15.75"; Lid 15.75"



Model No.	Repairs	Min. Ht.	Weight
A1005-505CEW4	Emco A1003 Series	8.00"	28.0 lbs.
A1005-505CEW4DR	Emco A1003 Series, Includes Drain	9.00"	28.3 lbs.

*Minimum height is measured from the inside lip of the rim to the bottom of the bucket.

Refer to pages 47-53 for installation and replacement items.

Spill Containment


Retrofit

Emco Stainless Steel


Emco A1004-210 Series




Rim 17.6"; Lid 15.3"



Kit for Single Wall



Kit for Double Wall



There are two styles of the A1004-210. Double wall versions require either an NPT or NPSM adapter; both adapters are included with each kit. You may return the unused adapter to Emco for credit. Single wall versions include an A0031-725 (A0031-725P for drain versions).

For stretched or compressed bellows applications, additional adapter lengths are available. Refer to the list on the following page.

Model No.	Repairs	*Min. Ht.	Weight
A1005-505CEW1	A1004-211A Single Wall	10.00"	47.0 lbs.
A1005-505CEW1DR	A1004-210A Single Wall, Includes Drain	11.00"	48.9 lbs.
A1005-505CEW1G	A1004-211S Double Wall, Includes Gage	10.75"	48.2 lbs.
A1005-505CEW1GDR	A1004-210S Double Wall, Includes Drain & Gage	11.50"	50.1 lbs.


*Minimum height is measured from the inside lip of the rim to the bottom of the bucket.

Refer to pages 47-53 for installation and replacement items.


Emco A1004-316 Series




Rim 16"; Lid 13.2"



Kit for Single Wall



Kit for Double Wall



An A7901-305K Adapter Kit is included with the A1005-505CEW2 models. For buckets that have been installed with the bellows in a stretched position, *a taller adapter may be required*. Refer to the following page for a list of adapter kits.

Model No.	Repairs	*Min. Ht.	Weight
A1005-505CEW2	A1004-317A Single Wall	10.25"	36.3 lbs.
A1005-505CEW2DR	A1004-316A Single Wall, Includes Drain	11.25"	39.4 lbs.
A1005-505CEW2GDW	A1004-317S Double Wall, Includes Gage	10.13"	37.5 lbs.
A1005-505CEW2GDR	A1004-316S Double Wall, Includes Drain & Gage	11.00"	39.4 lbs.

*Minimum height is measured from the inside lip of the rim to the bottom of the bucket.


Refer to pages 47-53 for installation and replacement items.

Spill Containment

Retrofit

Accessories

A790I Adapter Kit



An A790I-305K Adapter Kit is included with the A1005-505CEW1 and A1005-505CEW2 models. For buckets that have been installed with the bellows in a stretched position, a taller adapter may be required.

Part No.	Installed Height	Description	Weight
A790I-302K		Adapter, 4" NPSM/NPT	2.0 lbs.
A790I-304K	4.00"	A1005-505CEW1, CEW2	4.0 lbs.
A790I-304KP	4.00"	A1005-505CEW1, CEW2	4.1 lbs.
* A790I-305K	5.00"	A1005-505CEW1, CEW2	6.0 lbs.
** A790I-305KP	5.00"	A1005-505CEW1, CEW2	6.1 lbs.
A790I-306K	6.00"	A1005-505CEW1, CEW2	7.5 lbs.
A790I-306KP	6.00"	A1005-505CEW1, CEW2	7.6 lbs.

*Included in A1005-505CEW1 & A1005-505CEW2

**Included in A1005-505CEW1DR & A1005-505CEW2DR

Retrofit

Testing Equipment

Part No.	Description	Weight
A1004-210TEST	Test Unit	6.5 lbs.
494833	Test Cover	4.5 lbs.
494854	Test Cover (-505CP)	5.0 lbs.

A1004-210TEST



494833




The A1004-210TEST is used with the 494833 Test Cover to perform vacuum testing on the A1005-505C Series Retrofit Spill Containment.

Spill Containment

Riser Extensions - One-Piece

The Emco Wheaton A003I Riser Extension is designed to compensate for riser pipe variations and to accommodate spill containment retrofits. The threads are 4" NPT.



Part No.	Installed Height	Application	Weight
A003I-175	1.75"	Riser pipe extension	2.7 lbs.
A003I-250	2.50"	Riser pipe extension	3.7 lbs.
A003I-450	4.50"	Riser pipe extension	4.1 lbs.
A003I-625	6.25"	Riser pipe extension	4.4 lbs.
A003I-625P	6.25"	Riser pipe extension	4.5 lbs.
A003I-725	7.25"	Riser pipe extension	6.4 lbs.
A003I-725P	7.25"	Riser pipe extension	6.5 lbs.
A003I-825	8.25"	Riser pipe extension	7.9 lbs.
A003I-825P	8.25"	Riser pipe extension	8.0 lbs.
A003I-900	9.00"	Riser pipe extension	9.0 lbs.

Variants with a "P" include a drain port

Spill Containment


Riser Extensions - Two-Piece

Pipe Nipples

The Emco Wheaton A7901 Pipe Nipple is used in spill containment buckets to extend the fill pipe. The A7901 is available in schedule 40 pipe or stainless steel. The top and bottom threads are NPT.

The Schedule 40 nipples are made from flame controlled pipe with no internal weld bead and have a nominal ID of 4.026". The stainless steel nipples have a nominal ID of 4.173".


Schedule 40 Model No.	Stainless Steel Model No.	Weight	Length A
A7901-004C	A7901-004CSS	1.6 lbs.	3" (close)
A7901-004	A7901-004SS	2.5 lbs.	4"
A7901-005	A7901-005SS	3.4 lbs.	5"
A7901-006	A7901-006SS	4.2 lbs.	6"
A7901-008	A7901-008SS	5.9 lbs.	8"
A7901-010	A7901-010SS	7.7 lbs.	10"
A7901-012	A7901-012SS	9.4 lbs.	12"
A7901-014	A7901-014SS	11.1 lbs.	14"
A7901-015	A7901-015SS	12.0 lbs.	15"
A7901-016	A7901-016SS	12.8 lbs.	16"
A7901-018	A7901-017SS	14.5 lbs.	18"
A7901-019	A7901-019SS	15.4 lbs.	19"
A7901-020	A7901-020SS	16.3 lbs.	20"
A7901-022	A7901-022SS	18.0 lbs.	22"
A7901-024	A7901-024SS	19.7 lbs.	24"
A7901-026	A7901-026SS	21.4 lbs.	26"
A7901-028	A7901-028SS	23.1 lbs.	28"
A7901-030	A7901-030SS	24.9 lbs.	30"
A7901-032	A7901-032SS	26.6 lbs.	32"
A7901-034	A7901-034SS	28.3 lbs.	34"
A7901-036	A7901-036SS	30.0 lbs.	36"




Pipe Couplings

The Emco Wheaton A7904-500 and A7904-004 Pipe Couplings convert a male riser pipe to a female, allowing for an extension nipple. The A7904-500 adds only 1/4" to the original riser.

Model No.	Length A	Weight
A7904-500	2.38"	2.9 lbs.
A7904-004	3.50"	4.5 lbs.



A7904-500
Short Pipe
Coupling



A7904-004
Merchant Steel
Coupling

Spill Containment

Spill Containment Accessories


A0028 Riser Lock

The Emco Wheaton A0028-001 Riser Lock is designed to lock the riser pipe in place when removing manholes or adapters. Can be used on 3" and 4" pipe.

Model No.	Weight
A0028-001	5.4 lbs.



Prevents riser pipe from backing out of tank fitting



A0333 Hand Pump

The Emco Wheaton A0333 Hand Pump is a thermoplastic self-venting pump. The A0333-002 is acceptable for use with A1003, A1004 and A1005 Spill Containment.

Model No.	Description	Weight
A0333-002	Hand Pump	1.3 lbs.
A0333-003	Hand Pump w/ Mounting Bracket for A1005-001	3.0 lbs.
A0333-004	Hand Pump w/ Mounting Bracket for A1005-501	3.0 lbs.



Tools and Test Equipment

A0099-001 TEST

The A0099-001 TEST Vapor Test Cap is used when performing a pressure decay test. The cap incorporates the same features as the A0099-002 Vapor Cap. The extended tube underneath the cap opens the poppet on the vapor adapter. Pressure is injected through the Schrader valve, and a gauge can be connected to the barbed fitting.



A1004-210TEST Vacuum Apparatus w/Test Adapter

The A1004-210TEST is designed to perform vacuum testing on interstitial space in double wall spill containment.

Model No.	Description
A1004-210TEST	Vacuum Test Apparatus
494343	Test Adapter
569143	Test Cap Assembly
569194	Air Switch 1/8"
569195	Air Regulator 1/8"



494343
Test Adapter



569143
Test Cap
Assembly



A1004-210TEST
Test Apparatus

Tools and Test Equipment

A0081 Wrench

The A0081-001 Adapter Wrench is a specially designed tool for installing Emco Wheaton fill and vapor adapters. Octagonal bottom and tee handles assure tight positive seating of the fitting.

The A0081-001C Adapter Wrench is designed with a 3/4" hex in place of the tee handle, for socket/torque wrench tightening. Fits in a standard toolbox. Both the A0081-001 and -001C are for use on the A0030-014, A0030-124S, A0076-124S, A0089 and A0096 Adapters.

The A0081-001H Wrench is used when installing the A1004 series primary repair kit. This wrench has 24" steel tube handles for easy removal of stubborn spill buckets. A hex bolt is welded to the top of the wrench, allowing use with a torque wrench.

Model No.	Material	Weight
A0081-001	Steel	10.4 lbs.
A0081-001C	Steel	7.8 lbs.
A0081-001H	Steel	11.3 lbs.
A0081-001R	Steel	



A0081-001
Swivel Adapter
Wrench



A0081-001C
Swivel Adapter
Wrench, Compact



A0081-001H
Wrench, Primary
Repair Kit

A0081-003 Pipe Nipple Extractor

The Emco Wheaton A0081-003 Pipe Nipple Extractor is used to remove 4" pipe nipples; steel construction.

Model No.	Weight
A0081-003	10.3 lbs.



Spill Containment

Replacement Parts

Lids

Lid Model No.	Description	Material	Lid Dia.	Weight
<u>AI004-210 Series</u>				
AI004-210LID	Black	Cast Iron	15.3"	20.0 lbs.
AI004-210LID-C	Black	Composite	15.3"	8.3 lbs.
AI004-210LID-R	White, Regular	Cast Iron	15.3"	20.0 lbs.
AI004-210LID-U	Red, Ultra	Cast Iron	15.3"	20.0 lbs.
AI004-210LID-V	Orange, Vapor	Cast Iron	15.3"	20.0 lbs.
AI004-210LID-CR	White, Regular	Composite	15.3"	8.3 lbs.
AI004-210LID-CU	Red, Ultra	Composite	15.3"	8.3 lbs.
AI004-210LID-CV	Orange, Vapor	Composite	15.3"	8.3 lbs.
<u>AI004-316, AI005-517 & -518 Series</u>				
AI004-316LID	Black	Composite	13.2"	6.6 lbs.
AI004-316CLID	Black	Cast Iron	13.2"	15.9 lbs.
AI004-316CLID-D	Yellow, ULSD	Cast Iron	13.2"	15.9 lbs.
AI004-316CLID-R	White, Regular	Cast Iron	13.2"	15.9 lbs.
AI004-316CLID-U	Red, Ultra	Cast Iron	13.2"	15.9 lbs.
AI004-316CLID-V	Orange, Vapor	Cast Iron	13.2"	15.9 lbs.
<u>AI005-505 Retrofit</u>				
AI005-505CAL	AI005-505CA, CAZ	Cast Iron	13.8"	16.6 lbs.
AI005-505CL	AI005-505C, CDR, C5, CBG, -505CD, CS, CZ	Cast Iron	13.7"	16.6 lbs.
AI005-505CCL	AI005-505CC, CC5	Cast Iron	12.4"	16.6 lbs.
AI005-505CEL	AI005-505CE, CE15, CES	Cast Iron	13.7"	16.6 lbs.
AI005-505CEW3L	AI005-505CEW3	Cast Iron	15.4"	14.9 lbs.
AI005-505CFLI	AI005-505CFI	Cast Iron	13.9"	16.5 lbs.
AI005-505CF5L	AI005-505CF5	Cast Iron	13.5"	15.2 lbs.
AI005-505CL4	AI005-505C4	Cast Iron	12.8"	12.3 lbs.
AI005-505CPEML	AI005-505CPEM, CPED	Cast Iron	12.8"	13.3 lbs.
AI005-505CPL	AI005-505CP	Cast Iron	17.6"	24.5 lbs.
AI005-505CUL	AI005-505CU	Cast Iron	12.8"	13.4 lbs.
AI005-505CUL70	AI005-505CU70, CEW4	Cast Iron	15.0"	16.9 lbs.
AI004-210LID	AI005-505CEW1, CEW1DR	Cast Iron	15.3"	20.0 lbs.
AI004-316CLID	AI005-505CEW2, CEW2DR	Cast Iron	13.2"	15.9 lbs.
493123	AI003	Cast Iron	15.8"	19.1 lbs.
493806	AI004 Slimline, AI005-001, -501	Cast Iron	15.3"	20.0 lbs.
494554	AI004-215, AI005-010TM	Cast Iron	17.3"	29.5 lbs.
566332	AI004 Fatboy	Cast Iron	16.3"	24.1 lbs.




AI004-210LID



AI004-316LID



AI004-316CLID



AI005-505CL



493123



493806



494554



566332

Replacement Parts

Lids

Lid Replacement Seals

Model No.	Description
571126	O-ring Seal, 493123
567166K	Triple Wiper Seal A1004-210LID, 493806
568961	Triple Wiper Seal A1005-505C Series*
569227	Triple Wiper Seal 494554
570012	Triple Wiper Seal A1004-316LID, A1005-505CPL*, CEW3L

*Refer to photo and chart at right



A1005-505 Series Lid Seals:

Measure inside diameter as shown

10 ³/₈" - 10 ¹/₂" 568961 Seal
 12 ³/₄" - 13" 570012 Seal

494335 Lid for OPW I-2100 Series

Incorporates the features of Emco Wheaton A1004 lids: exclusive triple wiper seal, built-in side handle, cast iron construction, and meets AASHTO H20 wheel loading.

Model No.	Description	Weight
494335	Lid for OPW I-2100 Series	21.3 lbs.
568961	Replacement Seal	0.3 lbs.



Spill Containment

Replacement Parts

Drains



493508K
Pull/Push
Drain Assembly
A1003, A1004
Slimline, Fatboy



494118
Drain Assembly
A1004EVR



494551
Drain Assembly
A1004 Poly
494551S
Drain Assembly
A1005 Stainless Steel



494875
Adapter Kit
494551 Drain
2.26" top dia.



494952
Adapter Kit
494118 Drain
4.0" top dia.

Drain Assembly	Adapter Kit	Drain Plug
493508K	N/A	495202
494118	494952	495202
494551	494875	494697
494551S	N/A	494697S

493820 Drain Wrench



494697
Drain Plug
Replaces 494551 Drain
Kit includes 3 plugs



495202
Drain Plug
Replaces 493508K
& 494118 Drains
Kit includes 1 plug



493820
Drain Wrench
For use on 494118
& 493508K Drains

494697S
Replaces 494551S Drain
Kit includes 1 plug

Dip Sticks



494641
For use on A1004-210S
and A1004-316S Spill
Containment



494367
For use on A1004EVR
Spill Containment

Model No.	Description	Weight
494641	Dipstick	.7 lbs.
494367	Dipstick, EVR Spill Containment	1.2 lbs.
A1004-001GAGE	EZ-Gage, Emco Spill Containment	1.1 lbs.

EZ-Gage

A1004-001GAGE

For use on 5 gallon double wall spill containment in place of a dipstick. The EZ-Gage allows for hands-free, visual inspection of interstitial space, displaying green (OK) or red (TEST) to indicate if liquid removal is required.



Electronic Sensor

Easy push-button sensor test mechanism eliminates bucket removal for annual sensor testing. Provides an access to remove liquid, and for interstitial vacuum testing from the secondary containment. Includes factory-installed liquid electronic sensor with 30' cable.

Accommodates the Veeder Root system. Contact Customer Service for information on ordering sensors for other systems.

Model No.	Description	Weight
A1004-001SEN	Sensor Kit	1.2 lbs.
494890	Sensor Test Port Cap	1.0 lbs.



Normal Position




Test Position

Spill Containment

Replacement Parts

Replacement Kits and Parts AI004, AI005 Replaceable



Lid Included
With all Primary
Replacement Kits

	Model No.	Description	Weight
<u>AI004-210</u>	494360	Primary Replacement Kit (-210A)	64.0 lbs.
	494360EVR	Primary Replacement Kit (EVR-210A)	64.0 lbs.
	494466EVR	Primary Replacement Kit (EVR-211A)	68.5 lbs.
	494350	Primary Replacement Kit (-210S)	71.4 lbs.
	494350EVR	Primary Replacement Kit (EVR-210S)	71.4 lbs.
	494350-CM	Primary Replacement Kit (-210S-CM)	65.7 lbs.
	494467EVR	Primary Replacement Kit (EVR-211S)	67.7 lbs.
	494467G	Primary Replacement Kit (-211G)	67.7 lbs.
<u>AI004-215</u>	494550EVR	Primary and Secondary Replacement Kit (-215S)	119.7 lbs.
	494660EVR	Primary and Secondary Replacement Kit (-216S)	117.5 lbs.
<u>AI004-316</u>	494797	Primary Replacement Kit (-316A)	
	494797EVR	Primary Replacement Kit (EVR-316A)	
	494798	Primary Replacement Kit (-317A)	
	494798EVR	Primary Replacement Kit (EVR-317A)	
	494794	Primary Replacement Kit (-316S)	53.5 lbs.
	494794EVR	Primary Replacement Kit (EVR-316S)	53.5 lbs.
	494794-CM	Primary Replacement Kit (-316S-CM)	
	494795	Primary Replacement Kit (-317S)	36.5 lbs.
	494795EVR	Primary Replacement Kit (EVR-317S)	36.5 lbs.
	494795-CM	Primary Replacement Kit (-317S-CM)	20.9 lbs.
	494888	Handle Kit (Lid)	.5 lbs.
	494836	Primary Rim Kit	
	569989	Rim Gasket	
	570587	Rim Screw	
<u>AI005-517</u>	494845	Flange Seal, AI005-517	
	494897	Flange Seal, AI005-517GS	
	494836	Primary Rim Kit	16.0 lbs.
	569989	Rim Gasket	

Repair Parts AI004/AI005 Non-Replaceable

	Model No.	Description	Weight
<u>AI004 Slimline</u>	494247	Internal Repair Kit, Slimline	17.0 lbs.
	566949	Rim, Ductile, Slimline	18.3 lbs.
<u>AI004 Fatboy</u>	494329	Internal Repair Kit, Fatboy	
	565271	Rim, Ductile, Fatboy	31.0 lbs.
<u>AI005-001</u>	493855	Bellows Assembly 4"	1.4 lbs.

MANHOLES

Composite Manholes

A0716 Composite Manholes

The Emco Wheaton A0716 Composite Manhole is designed with lightweight, slip-resistant composite manhole covers, using the latest manufacturing technology to ensure porosity-free molding, and compact, homogeneous distribution of reinforcing fiber. The covers also utilize a UV resistant treatment to protect against sun and weather damage.

- Reduced weight
- Meets AASHTO H20 Wheel Loading
- Stainless steel fittings
- Slip resistant tread pattern
- Galvanized steel skirt (12" & 18")

39", 42" & 44" Models

- Domed top construction to shed water
- Dual handle - spring-loaded and key-lift
- Powder coated cast iron cam with o-ring
- Pry bar cleat
- Hot rolled steel skirt
- Concrete anchors
- Cam lock fittings etched to show open and close directional arrows



3.64" diameter spot face recessed 0.07" for fuel grade ID markers



569427
Euro Lift Handle

All composite manholes are available with stainless steel rim, skirt, and fittings


Model Number	Style	Lid Dia. A	Overall Dia. B	Clear Hole C	Skirt ID D	Overall Ht. E	Weight
A0716-018SS	18" Lay-in	17.0"	17.9"	15.9"	16.1"	12.9"	32 lbs.
A0716-039SS	39" Lay-in	39.5"	40.9"	37.8"	38.3"	12.9"	190 lbs.
A0716-042SS	42" Lay-in	43.8"	45.2"	42.0"	42.5"	12.9"	221 lbs.
A0716-044SS	44" Lay-in	44.3"	45.7"	42.5"	43.1"	12.9"	228 lbs.

Painted Lids - API Product Codes

Add to the end of the variant number:

- D Yellow ULSD
- R White Regular
- U Red Premium

Contact Customer Service at 800-234-4394, for additional colors



Composite Manholes

A0716 Composite Manholes

	Model Number	Style	Lid Dia. A	Overall Dia. B	Clear Hole ID C	Skirt ID D	Overall Height E	Weight
18"	A0716-018	Lay-in	17.0"	17.8"	16.0"	17.0"	11.0"	37.3 lbs.
	A0716-018C	Cam Lock	17.0"	17.7"	15.1"	17.0"	11.0"	38.9 lbs.
	A0716-018CW	Cam Lock White Lid	17.0"	17.7"	15.1"	17.0"	11.0"	38.9 lbs.
	A0716-018L	Lid Only Lay-in	17.0"	--	--	--	--	12.9 lbs.
	A0716-018CL	Lid Only Cam Lock	17.0"	--	--	--	--	14.6 lbs.
	A0716-018CWL	Lid Only, White, Cam Lock	17.0"	--	--	--	--	14.6 lbs.
39"	* A0716-039	Lay-in	39.5"	40.9"	37.8"	38.3"	10.0"	159.0 lbs.
	A0716-039A	Lay-in	39.5"	40.9"	37.8"	38.3"	18.0"	174.0 lbs.
	A0716-039B	Bolt-down	39.5"	40.9"	35.5"	38.3"	10.0"	170.9 lbs.
	A0716-039C	Cam Lock	39.5"	40.9"	36.8"	38.3"	10.0"	173.0 lbs.
	A0716-039CL	Lid Only Cam Lock	39.5"	--	--	--	--	112.7 lbs.
	A0716-039LID	Lid Only Lay-in	39.5"	--	--	--	--	109.2 lbs.
42"	495157	Replacement Gasket, -039B, -039C						
	* A0716-042	Lay-in	43.8"	45.2"	42.0"	42.5"	10.0"	182.2 lbs.
	A0716-042B	Bolt-down	43.8"	45.2"	38.5"	42.5"	10.0"	174.3 lbs.
	A0716-042C	Cam Lock	43.8"	45.2"	41.0"	42.5"	10.0"	211.1 lbs.
	A0716-042CL	Lid Only Cam Lock	43.8"	--	--	--	--	163.0 lbs.
	A0716-042LID	Lid Only Lay-in	43.8"	--	--	--	--	143.0 lbs.
44"	494988	Replacement Gasket, -042B, -042C						
	A0716-044	Lay-in	44.3"	45.7"	42.5"	43.1"	10.0"	188.0 lbs.
	A0716-044B	Bolt-down	44.3"	45.7"	40.3"	43.1"	10.0"	199.5 lbs.
	* A0716-044C	Cam Lock	44.3"	45.7"	41.5"	43.1"	10.0"	208.6 lbs.
	A0716-044CL	Lid Only Cam Lock	44.3"	--	--	--	--	161.2 lbs.
	A0716-044LID	Lid Only Lay-in	44.3"	--	--	--	--	137.2 lbs.
	494988	Replacement Gasket, -044B, -044C						

*Most common variant

Custom skirt heights available upon request

Drop-In Replacement Lids for Competitors' Manholes:

Emco manufactures replacement lids in both composite and steel construction

Composite	3/8" Steel	OPW	Franklin	Flexing	Morrison	Environ
A0716-039LID	A0717-039LID	E00618	781-448-06			
A0716-039M	A0717-039M				318L-3800/3900	
A0716-042LID	A0717-042LID			14U-4210C		
A0716-044LID	A0717-044LID	E00626	781-445-06			
A0716-044E						WTM-4511, WTM-4521
A0716-044M	A0717-044M				318L-4400/4500	

Standard Manholes

A0717 Round Manholes

The Emco Wheaton A0717 multi-purpose manhole provides access to all types of underground storage or containment vessels and meets AASHTO H20 wheel loading.



- Open throat design for easy access
- Optional galvanized steel or polyethylene skirt (8" & 12")
- Bolt-down units have water-resistant lids
- Built-in handle (18")
- Custom skirt heights available on all models




A0717-036B

24" - 48" Models


- Diamond plate steel lid
- Hot rolled steel skirt
- Concrete anchors
- T-bar frame
- Recessed handle
- Available in lay-in, bolt-down and cam-lock versions




Lay-in



Bolt-down



Cam-lock



Standard Manholes

A0717 Round Manholes

	Model Number	Style	Skirt	Lid	Lid Dia. A	Max. Dia. B	Clear Hole Dia. C	Skirt I.D. D	Overall Ht. E	Weight
8"	A0717-188	Lay-in	Steel	3/8" Steel	9.0"	9.9"	8.0"	8.4"	9.0"	14.0 lbs.
	A0717-008	Lay-in	Poly	3/8" Steel	9.0"	9.9"	8.0"	8.1"	12.0"	16.0 lbs.
	A0717-108	Lay-in	Steel	3/8" Steel	9.0"	9.9"	8.0"	8.4"	12.0"	15.4 lbs.
12"	* A0717-128	Lay-in	Steel	Cast Iron	12.4"	13.8"	11.3"	12.0"	8.0"	21.8 lbs.
	* A0717-022	Lay-in	Poly	Cast Iron	12.4"	13.8"	11.3"	12.0"	12.0"	18.0 lbs.
	* A0717-122	Lay-in	Steel	Cast Iron	12.4"	13.8"	11.3"	12.0"	12.0"	25.3 lbs.
	A0717-122FG	Lay-in, w/finger hole	Steel	Cast Iron	12.4"	13.8"	11.3"	12.0"	12.0"	26.0 lbs.
	567177	Lid Only		Cast Iron	12.4"					10.0 lbs.
18"	* A0717-018	Lay-in	Steel	Cast Iron	17.0"	17.8"	16.0"	16.6"	12.0"	51.0 lbs.
	A0717-018A	Lay-in	Steel	Cast Iron	17.0"	17.8"	16.0"	16.6"	18.0"	58.1 lbs.
	A0717-018B	Bolt-down WR	Steel	Cast Iron	17.0"	17.2"	14.1"	16.9"	12.0"	56.3 lbs.
	567715X	Lid Only Lay-in (Old style)		Cast Iron	17.3"					26.5 lbs.
	570893L	Lid Only Lay-in (> 05/14)		Cast Iron	17.0"					22.9 lbs.
24"	A0717-024	Lay-in	Steel	3/8" Steel	23.6"	24.5"	21.6"	23.1"	13.0"	68.0 lbs.
	A0717-024A	Lay-in	Steel	3/8" Steel	23.6"	24.5"	21.6"	23.0"	18.0"	73.0 lbs.
	A0717-124	Bolt-down WR	Steel	3/8" Steel	23.6"	24.5"	21.6"	23.0"	13.0"	69.0 lbs.
	A0717-124B	Bolt-down WR	Steel	3/8" Steel	23.6"	24.5"	21.6"	23.0"	18.0"	74.0 lbs.
	A0717-124CL	Cam-Lock WR	Steel	3/8" Steel	23.6"	24.5"	21.6"	23.0"	13.0"	67.0 lbs.
30"	A0717-030	Lay-in	Steel	3/8" Steel	29.6"	30.5"	27.6"	29.0"	13.0"	105.0 lbs.
	A0717-030B	Bolt-down WR	Steel	3/8" Steel	29.6"	30.5"	27.6"	29.0"	13.0"	107.8 lbs.
	A0717-030CL	Cam-Lock WR	Steel	3/8" Steel	29.6"	30.5"	27.6"	29.0"	13.0"	107.8 lbs.
36"	A0717-036	Lay-in	Steel	1/2" Steel	35.6"	36.5"	33.6"	35.0"	13.0"	189.2 lbs.
	A0717-036B	Bolt-down WR	Steel	1/2" Steel	35.6"	36.5"	33.6"	35.0"	13.0"	175.0 lbs.
	A0717-036CL	Cam-Lock WR	Steel	1/2" Steel	35.6"	36.5"	33.6"	35.0"	13.0"	175.0 lbs.
	* A0717-136	Lay-in	Steel	3/8" Steel	35.6"	36.5"	33.6"	35.0"	13.0"	173.3 lbs.
	A0717-136B	Bolt-down WR	Steel	3/8" Steel	35.6"	36.5"	33.6"	35.0"	13.0"	173.8 lbs.
	A0717-136CL	Cam-Lock WR	Steel	3/8" Steel	35.6"	36.5"	33.6"	35.0"	13.0"	173.8 lbs.
38"	A0717-038	Lay-in	Steel	1/2" Steel	39.6"	40.5"	37.6"	39.0"	13.0"	257.0 lbs.
	A0717-038A	Lay-in	Steel	1/2" Steel	39.6"	40.5"	37.6"	39.0"	18.0"	240.0 lbs.
	A0717-038B	Bolt-down WR	Steel	1/2" Steel	39.6"	40.5"	37.6"	39.0"	13.0"	238.2 lbs.
	A0717-038CL	Cam-Lock WR	Steel	1/2" Steel	39.6"	40.5"	37.6"	39.0"	13.0"	238.2 lbs.
	* A0717-038C	Lay-in	Steel	3/8" Steel	39.6"	40.5"	37.6"	39.0"	13.0"	203.0 lbs.
	A0717-038CB	Bolt-down WR	Steel	3/8" Steel	39.6"	40.5"	37.6"	39.0"	13.0"	205.0 lbs.
	A0717-038CCL	Cam-Lock WR	Steel	3/8" Steel	39.6"	40.5"	37.6"	39.0"	13.0"	205.0 lbs.
42"	A0717-042A	Lay-in	Steel	1/2" Steel	44.1"	45.0"	42.1"	43.5"	13.0"	299.7 lbs.
	A0717-042AB	Lay-in	Steel	1/2" Steel	44.1"	45.0"	42.1"	43.5"	18.0"	390.0 lbs.
	A0717-042B	Bolt-down WR	Steel	1/2" Steel	44.1"	45.0"	42.1"	43.5"	13.0"	342.0 lbs.
	A0717-042D	Lay-in	Steel	3/8" Steel	44.1"	45.0"	42.1"	43.5"	13.0"	247.0 lbs.
48"	A0717-048	Lay-in	Steel	1/2" Steel	47.1"	48.0"	45.1"	46.5"	13.0"	321.0 lbs.
	A0717-148	Lay-in	Steel	3/8" Steel	47.1"	48.0"	45.1"	46.5"	13.0"	280.0 lbs.

*Most common variant

Standard Manholes

A0717 Square Manholes and Vaults



A0717-724VW




A0717-736VWL

The Emco Wheaton A0717 square manhole provides ease of access to a variety of tank hardware and monitoring equipment.

All Square Manholes

- $\frac{3}{8}$ " heavy duty diamond plate lid
- 16 gauge steel skirt
- Meets AASHTO H20 wheel loading




The 24" and 30" vaults are reinforced with 2"x2"x $\frac{1}{4}$ " steel angle

The 36" and 48" vaults are reinforced with cross bracing of 3" structural steel channel

Locking Vault Manholes

- Double hinged lid opens and folds back to 180°
- Lock-access lid permanently fastened with anti-theft chain; secured with single pinned bolt



Standard Manholes

A0717 Square Manholes and Vaults

Size	Model No.	Style	Overall Height	Lid Weight	Total Weight
12"	*A0717-712VW	Locking Vault Water-resistant	11.6"	18 lbs.	38.1 lbs.
	A0717-712VWA	Locking Vault Water-resistant	24.6"	18 lbs.	38.1 lbs.
	A0717-712VWB	Locking Vault Water-resistant	18.6"	18 lbs.	42.5 lbs.
18"	A0717-718	Lay-in	9.6"	36 lbs.	56.3 lbs.
	*A0717-718ABW	Bolt-down Water-resistant	18.6"	36 lbs.	73.3 lbs.
	A0717-718BWA	Bolt-down Water-resistant	24.6"	36 lbs.	87.3 lbs.
	*A0717-718VW	Locking Vault Water-resistant	18.6"	36 lbs.	76.8 lbs.
	A0717-718VWA	Locking Vault Water-resistant	24.6"	36 lbs.	96.0 lbs.
	A0717-718VWL	Locking Vault Lift Assist Water-resistant	18.6"	36 lbs.	77.3 lbs.
24"	A0717-724	Lay-in	9.6"	65 lbs.	88.4 lbs.
	A0717-724A	Lay-in	24.6"	65 lbs.	112.0 lbs.
	A0717-724ABW	Bolt-down Water-resistant	24.6"	65 lbs.	119.8 lbs.
	A0717-724BBW	Bolt-down Water-resistant w/Handle	24.6"	65 lbs.	122.2 lbs.
	A0717-724BW	Bolt-down Water-resistant w/Handle	9.6"	65 lbs.	107.2 lbs.
	A0717-724E	Lay-in w/Handle	12.6"	65 lbs.	117.0 lbs.
	A0717-724V	Locking Vault	24.6"	65 lbs.	116.5 lbs.
	*A0717-724VW	Locking Vault Water-resistant	24.6"	65 lbs.	121.5 lbs.
	A0717-724VWB	Locking Vault Water-resistant	10.6"	65 lbs.	116.5 lbs.
	A0717-724VWC	Vault Bolt-down Water-resistant w/Handle	24.6"	65 lbs.	126.4 lbs.
	A0717-724VWE	Locking Vault Water-resistant	18.6"	65 lbs.	117.0 lbs.
	*A0717-724VWL	Locking Vault Lift Assist Water-resistant	24.6"	68 lbs.	120.9 lbs.
	A0717-724VWCL	Vault Lift Assist Bolt-down WR w/Handle	24.6"	68 lbs.	131.0 lbs.
30"	A0717-730VW	Locking Vault Water-resistant	24.6"	123 lbs.	200.0 lbs.
	A0717-730VWL	Locking Vault Lift Assist Water-resistant	24.6"	123 lbs.	200.0 lbs.
36"	A0717-736VW	Locking Vault Water-resistant	36.6"	165 lbs.	307.4 lbs.
	A0717-736VWA	Locking Vault Water-resistant 36x24x24	24.6"	165 lbs.	265.0 lbs.
	A0717-736VWAL	Locking Vault Lift Assist WR 36x24x24	24.6"	165 lbs.	270.0 lbs.
	A0717-736VWE	Locking Vault Water-resistant	24.6"	165 lbs.	285.0 lbs.
	A0717-736VWL	Locking Vault Lift Assist Water-resistant	36.6"	171 lbs.	287.0 lbs.
	A0717-736VWLA	Locking Vault Lift Assist Water-resistant	24.6"	171 lbs.	268.5 lbs.
48"	A0717-748VWL	Locking Vault Lift Assist Water-resistant	48.6"	165 lbs.	270.0 lbs.
	A0717-748VWLA	Locking Vault Lift Assist Water-resistant	24.6"	165 lbs.	270.0 lbs.
	A0717-748VWLF	Locking Vault Lift Assist WR 24x48x24	24.6"	171 lbs.	273.0 lbs.
72"	A0717-772VWLE	Locking Vault Lift Assist Bolt-down WR	24.6"		

*Most common variant

Custom sizes available upon request


V = Hinged; B = Bolt-down; W = Water-resistant; L = Lift Assist Lid

Monitoring Well Manholes

A072I Monitoring Well Manholes

All Emco Wheaton Monitoring Well Manholes incorporate cast-in identification triangles in accordance with API recommendations and meet AASHTO H20 wheel loading.

- Painted ductile iron lid and rim
- Optional galvanized steel or polyethylene skirt
- Bolt-down units have water-tight lids
- Custom skirt heights available
- Stainless steel bolts



Built-in side handle on 18" models - one hand opening and positioning



- Heavy-duty (16 gauge hot rolled carbon steel) skirts available. 100% welded skirt and seam.
To order, replace the first digit of the variant number with a 2.
- ID tag available on all models; large enough for all new regulatory requirements.
To order, add ID to the 8-digit part number

A0720 Locking Cap & Collar

The Emco Wheaton A0720 locking cap and collar is used to limit access and seal monitoring wells and can be threaded or solvent welded onto a 4" PVC monitoring well pipe. It displays the monitoring well designation and includes a padlock. The cap and collar are both made of durable ABS plastic.



Replacement Parts
564029 Lock/Key Set A0720

Model No.	Description	Pipe Size	Weight
A0720-001	Locking Cap and Collar	4"	1.3 lbs.

Monitoring Well Manholes

A072I Monitoring Well Manholes

Size	Model No.	Style	Skirt Type	Overall Height	Clearhole ID	Max. Dia.	Weight
5"	* A072I-105	Bolt-down	Steel	8.5"	3.8"	6.0"	5.7 lbs.
6"	* A072I-106	Bolt-down	Steel	7.5"	4.5"	6.7"	6.3 lbs.
	* A072I-106A	Bolt-down	Steel	9.5"	4.5"	6.7"	6.5 lbs.
7"	A072I-107	Bolt-down	Steel	13.2"	5.1"	8.9"	12.5 lbs.
8"	* A072I-008	Bolt-down	Poly	12.3"	6.0"	9.9"	11.7 lbs.
	A072I-008CE	BD, Large Bolts, White Lid	Poly	12.3"	6.0"	9.9"	11.1 lbs.
	A072I-008LA	Lay-in	Poly	12.3"	7.8"	9.9"	10.4 lbs.
	A072I-088	Bolt-down	Poly	8.0"	6.0"	9.9"	13.6 lbs.
	* A072I-108	Bolt-down	Steel	12.7"	6.0"	9.9"	13.7 lbs.
	* A072I-188	Bolt-down	Steel	9.2"	6.0"	9.9"	12.8 lbs.
	A072I-188A	Bolt-down	Steel	7.0"	6.0"	9.9"	12.7 lbs.
	* A072I-188L	Lay-in	Steel	8.9"	7.8"	9.9"	11.9 lbs.
	A072I-208	Bolt-down	HD Steel***	12.5"	6.0"	9.9"	12.7 lbs.
	A072I-308	BD, 3 Bolts, White Lid	Steel	8.8"	6.4"	9.4"	12.8 lbs.
	A072I-308A	BD, 3 Bolts, White Lid	Steel	12.8"	6.4"	9.4"	13.7 lbs.
	A0722-008**	Bolt-down	Poly	12.3"	6.0"	9.9"	12.4 lbs.
	* A072I-001	Bolt-down	Poly	12.0"	9.4"	15.1"	23.0 lbs.
	A072I-001CC	Bolt-down w/Rebar Tabs	Poly	12.0"	9.4"	15.1"	23.1 lbs.
	A072I-001L	Lay-in	Poly	12.0"	11.2"	13.8"	22.8 lbs.
12"	* A072I-101	Bolt-down	Steel	12.0"	9.4"	15.1"	28.8 lbs.
	A072I-101A	Bolt-down	Steel	18.0"	9.4"	15.1"	31.0 lbs.
	A072I-101L	Lay-in	Steel	12.0"	11.2"	13.8"	28.6 lbs.
	A072I-119	Bolt-down	Steel	19.0"	9.4"	15.1"	36.3 lbs.
	A072I-128	Bolt-down	Poly	8.1"	9.4"	15.1"	21.9 lbs.
	A072I-128A	Bolt-down	Steel	8.0"	9.4"	15.1"	23.6 lbs.
	A072I-201	Bolt-down	HD Steel***	12.0"	9.4"	15.1"	28.0 lbs.
	A0722-001**	Bolt-down	Poly	12.0"	9.4"	15.1"	24.3 lbs.
	* A072I-018	Bolt-down	Steel	12.3"	13.8"	18.4"	58.5 lbs.
	A072I-118	Bolt-down	Steel	18.0"	13.8"	18.4"	69.5 lbs.

*Most common variant

**Includes locking cap & collar

***Heavy duty

Lid Replacement Parts

Part No.	Lid	Description	Weight	Part No.	Lid	Description	Weight
494263	5"	Bolt 1/2" Hex, 3/8" Thd, 0.5 Lg		494261	8"	Bolt/Neoprene Washer 9/16" Hex, 3/8" Thd, 1.0 Lg	
569885	5"	Lid Gasket		566419	8"	O-ring for 9/16" Bolt	0.4 oz.
569883	5"	Lid Cast Bolt-down		566334	8"	O-ring for 5/8" Bolt	0.4 oz.
568692	6"	Lid Ductile Bolt-down	2.4 lbs.	567146	8"	Lid Gasket	0.1 lbs.
568662	6"	Bolt 1/2" Hex, 5/16" Thd, 0.75 Lg		563980	12"	Lid Ductile Bolt-down	11.0 lbs.
568820	6"	Lid Gasket	0.1 lbs.	569723	12"	Lid Ductile Lay-in	11.6 lbs.
571700	7"	Lid Ductile Bolt-down	3.3 lbs.	494262	12"	Bolt/O-ring 15/16" Hex, 5/8" Thd, 1.75 Lg	0.2 lbs.
494261	8"	Bolt/Neoprene Washer 9/16" Hex, 3/8" Thd, 1.0 Lg		566334	12"	O-ring for 5/8" Bolt	0.3 oz.
571702	7"	Lid Gasket	0.1 lbs.	563593	12"	Lid Gasket	0.1 lbs.
569106	8"	Lid Ductile Bolt-down	5.1 lbs.	567712	18"	Lid Ductile Bolt-down	28.8 lbs.
569285	8"	Lid Ductile Lay-in	6.0 lbs.	494262	18"	Bolt/O-ring 15/16" Hex, 5/8" Thd, 1.75 Lg	0.2 lbs.
567150	8"	Lid Ductile BD, White	6.0 lbs.	494375	18"	Bolt/O-ring 9/16" Hex, 3/8" Thd, 2.0 Lg	0.2 lbs.
494260	8"	Bolt/O-ring 15/16" Hex, 5/8" Thd, 1.0 Lg		566419	18"	O-ring for 9/16" Bolt	
				567995	18"	Lid Gasket	0.3 lbs.


Well Protectors

A0727 Well Protectors

- Raintight Cap - one piece die cast aluminum cap is powdered coated for corrosion resistance and painted with contrasting black triangle
- Riveted Construction - cap overlaps hinge pins, preventing vandalism
- Lockable
- Top Kit - complete cap assembly for bare tubing
- Optimized height - clears tallest well plug



Stainless Steel Hinges
Open 150°




Model No.	Description	Material	Weight
A0727-004A	4"x4"x5' Square Well Protector	Aluminum	12.0 lbs.
A0727-004S	4"x4"x5' Square Well Protector	Steel	23.0 lbs.
A0727-004K	Top Kit for Bare Tubing	Aluminum	1.6 lbs.

Custom lengths available upon request

A0728 Well Protectors

- Raintight Cap - welded steel construction cap overlaps pipe to prevent rain intrusion
- All Steel Construction
- Thick 14 gauge pipe
- Lockable
- Available in 4" & 6" diameters




Model No.	Description	Material	Weight
A0728-004	4"x5' Round Well Protector	Steel	30.0 lbs.
A0728-006	6"x5' Round Well Protector	Steel	39.9 lbs.

Custom lengths available upon request

Phase I Enhanced Vapor Recovery System

CARB Executive Order VR-105



1. **A0097 Fill Cap for Tank Probe**
(Refer to p. 7)



6. **A1004EVR Spill Containment**
(Refer to p. 69)



8. **A0099 Vapor Cap**
(Refer to p. 9)



2. **A0030-014 ATG Adapter**
A0030-014F ATG Adapter for INCON Tank Probe
(Refer to p. 5)



9. **A0076-124S Vapor Swivel Adapter**
(Refer to p. 8)



3. **A0097 Fill Cap**
(Refer to p. 7)



10. **A0079 Extractor Fitting**
(Refer to p. 18)



4. **A0030-124S Fill Swivel Adapter**
(Refer to p. 5)



7. **A1100EVR OPV Assembly**
(Refer to p. 71)



11. **A0075 Ball Float**
(Refer to p. 20)



5. **494096 Riser Seal**



Phase I Enhanced Vapor Recovery System

AI004EVR Spill Containment

Replaceable

Ductile Iron Lid


Heavy duty, snow plow resistant ductile iron rim

Triple Wiper Seal

HDPE bellows primary and secondary liners

Vapor tight drain assembly

4 inch NPT or BSPT thread



AI004EVR-316S

	Model No.	Description	Overall Dia. A	Screw-on Height B	Lid Dia.	Lid Weight	Total Weight	Drain Type
Single Wall	AI004EVR-210A	Single Wall, 5 gal	17.6"	12.3"	15.3"	20.0 lbs.	85.0 lbs.	Pull/Push
	AI004EVR-211A	Single Wall, 5 gal	17.6"	13.5"	15.3"	20.0 lbs.	81.0 lbs.	None
	AI004EVR-316A	SV, 16" center, 5 gal	16.0"	15.0"	13.2"	15.9 lbs.	66.0 lbs.	Pull/Push
	AI004EVR-317A	SV, 16" center, 5 gal	16.0"	15.0"	13.2"	15.9 lbs.	63.0 lbs.	None
	AI004EVR-215A	Single Wall, 15 gal	22.6"	18.0"	17.1"	29.5 lbs.	126.0 lbs.	Pull/Push
Double Wall	AI004EVR-210S	Double Wall, 5 gal	17.6"	18.0"	15.3"	20.0 lbs.	92.0 lbs.	Pull/Push
	AI004EVR-211S	Double Wall, 5 gal	17.6"	16.3"	15.3"	20.0 lbs.	81.0 lbs.	None
	AI004EVR-316S	DW, 16" center, 5 gal	16.0"	17.8"	13.2"	15.9 lbs.	84.0 lbs.	Pull/Push
	AI004EVR-317S	DW, 16" center, 5 gal	16.0"	18.9"	13.2"	15.9 lbs.	79.9 lbs.	None
	AI004EVR-215S	Double Wall, 15 gal	22.6"	19.0"	17.1"	29.5 lbs.	151.0 lbs.	Pull/Push

Replacement Kits & Parts

Model No.	Description	Weight
494360EVR	Primary Replacement Kit (-210A)	44.0 lbs.
494466EVR	Primary Replacement Kit (-211A)	44.0 lbs.
494350EVR	Primary Replacement Kit (-210S)	45.5 lbs.
494467EVR	Primary Replacement Kit (-211S)	47.7 lbs.
494550EVR	Primary & Secondary Kit (-215S)	90.2 lbs.
494660EVR	Primary & Secondary Kit (-216S)	88.0 lbs.



P/N 494118
Drain Valve
Kit w/Filter

Model No.	Description
AI004-210LID	Lid & Seal 5 gallon
567166K	Triple Wiper Seal
494554	Lid & Seal 15 gallon
569227	Triple Wiper Seal
494118	Drain Valve Kit w/Filter
493820	Drain Wrench
494367	Dipstick Assembly

Phase I Enhanced Vapor Recovery System

A1004EVR Spill Containment

Non-Replaceable

Heavy duty, snow plow resistant ductile iron rim


Triple Wiper Seal

HDPE Bellows Liner

Deep polyethylene gravel guard accommodates thick concrete pads

One piece fiberglass base with vapor tight drain assembly

4 inch NPT or BSPT thread



Model No.	Description	Lid Dia.	Lid Weight	Total Weight	Drain Type
A1004EVR-010	Slimline, 4", 5 gal	15.3"	20.0 lbs.	58.5 lbs.	Pull/Push
A1004EVR-011	Slimline, 4", 5 gal	15.3"	20.0 lbs.	57.9 lbs.	None

Part No.	Description
493806	Lid & Seal Slimline
567166K	Triple Wiper Seal
494118	Drain Valve Kit w/Filter
493820	Drain Wrench



P/N 494118
Drain Valve
Kit w/Filter



EVR Installation and Maintenance Tools

A0081-001C Adapter Wrench

Installation, torque tightening and removal of Emco Wheaton adapters




493820 Drain Wrench

Installation and removal of the Emco Wheaton A1004 Spill Containment Drain Valve



494120 Riser Seal Wrench

Installation and removal of the center insert of the Emco Wheaton Riser Seal



494240 Adapter Torque Wrench

Use to verify the static torque of the swivel adapter in accordance to CARB Test Procedure TP.201.1B



494241 Spill Containment Wrench

Installation and removal of the Emco Wheaton A1004 Spill Containment. A hex bolt is welded to the top of the wrench allowing use with a torque wrench



566675 Drill Fixture

Use to accurately drill the rivet holes on the top drop tube for the A1100 collar assembly




Phase I Enhanced Vapor Recovery System

AI100EVR Overfill Prevention Valve

Phase I CARB
EVR Certified

EMCO®
WHEATON RETAIL



Provides tank with automatic fuel shutoff at 95% capacity

- 1 Floats contained in protective sleeve** Insures damage-free installation & removal. No hinged legs or exposed floats to hang up.
- 2 Plug socket** Allows manual testing of flapper valve assembly in field.
- 3 Top tube-to-valve interface factory welded, sealed and tested** for vapor-tight performance
- 4 Secondary float bleed valve with Viton® seal** Allows fast hose drainage.
- 5 Diverter fins protect the flapper valve** Allows damage-free stick gauging at any fluid level.
- 6 Automatic valve resetting function** Positions flapper out of the flow stream. Allows immediate stick gauging after fill.
- 7 Base of overfill valve is threaded and factory welded to bottom tube incorporating Viton® seals** for vapor-tight performance

Straight through design gives highest flow rate

Compatible with all standard fuels

Material

Body: Aluminum

Floats: HDPE

Seals: Viton®

Viton® is a registered trademark of DuPont Dow Elastomers.



566675
Drilling Fixture

Model No.	Description	Upper Length A	Lower Length B	Overall Length C	Max. Burial Depth	Nominal Tank Dia.	Weight
AI100EVR-055	Dual Pt Screw-Together	73"	95"	168"	6.0'	8'	25.2 lbs.
AI100EVR-056	Dual Pt Screw-Together	85"	107"	192"	7.0'	10'	27.2 lbs.
AI100EVR-057	Dual Pt Screw-Together	85"	133"	218"	6.8'	12'	30.3 lbs.
AI100EVR-058	Dual Pt Screw-Together	127"	133"	260"	10.0'	12'	31.0 lbs.
493734E	Support Collar Kit	--	--	--	--	--	01.1 lbs.
566675	Drill Fixture	--	--	--	--	--	03.8 lbs.
569461	Drop Tube O-ring	--	--	--	--	--	00.1 lbs.

Custom lengths are available upon request

Phase I Enhanced Vapor Recovery System

A0020EVR Drop Tube

The A0020EVR Drop Tube fits directly into the tank riser pipe to permit tight fill submerged filling with reduced turbulence and minimal vapor loss. 4" diameter.

Model No.	Length	Weight
Rolled Edge Collar		
A0020EVR-004	12'	13.0 lbs.
A0020EVR-005	15'	16.1 lbs.
A0020EVR-007	17'	18.2 lbs.
A0020EVR-008	14'	14.0 lbs.
Heavy Duty Collar		
A0020EVRC-004	12'	13.7 lbs.
A0020EVRC-005	15'	16.8 lbs.
A0020EVRC-007	17'	18.9 lbs.
A0020EVRC-008	14'	14.7 lbs.

Replacement Parts

569461 Drop Tube O-ring

Material

Tube: Aluminum
Seals: Viton®

Viton® is a registered trademark of DuPont Dow Elastomers.



Standard Rolled
Edge



Heavy Duty
Collar

Extractor fittings and ball floats are not required components of the vapor recovery system, but may be installed without violating the Executive Order. Refer to pages 18 and 20 for product information on the A0075 Ball Float and A0079 Extractor Fitting.



Balance Phase II Enhanced Vapor Recovery

CARB Executive Orders

VR-203, VR-204, VR-207, VR-208, VR-501



**99.5%
Vapor Collection
Efficient**



Classified by UL to
UL 2586, Valves for
Flammable Fluids

CARB Approved Mix &
Match with VST

CARB Approved for UST
and AST Installations

Nozzle & Breakaway
Core Credit Program,
Refer to Page 78



**A4005EVR Balance Vapor
Recovery Nozzle**

**A4119EVR Coaxial
SafeBreak® Valve**

CARB EVR approved for use with:

Pressure Management Options



**Veeder-Root
Polisher Canister**



**Healy
Clean Air Separator**



**Hirt VCS-100
Oxidizer**

ISD System Options




**Franklin
Fueling
INCON**



**Veeder-Root
TLS-350**

Balance Phase II EVR Components

A4005EVR Balance Vapor Recovery Nozzle



The A4005EVR Nozzle is designed for use with Balance Phase II Vapor Recovery Systems. Complies with the California Air Resources Board CARB Enhanced Vapor Recovery Program EVR Certification Procedures CP-201.

- CARB EVR Executive Orders VR-203, VR-204, VR-207, VR-208, VR-501
- CARB Pre-EVR Mix & Match Approval Letter #09-10/ Advisory #408
- California State Fire Marshall GVRC 005:007:025
- California Division of Measurement Standards 3211(d)-09
- UL Listing MH1460 Classified to UL 2586




Material

Body & Spout: Aluminum
Lever & Guard: Thermoplastic
Seals: Nitrile & Viton®
Scuff Guard: Vinyl

Viton® is a registered trademark of DuPont Dow Elastomers.

Model No.	Description	Weight
A4005EVR-052	New Unleaded	4.5 lbs.

Refer to page 76 for Phase II EVR repair and replacement kits and tools.



Balance Phase II EVR Components

A4110EVR Coaxial Hose Swivel


The A4110EVR 45° hose swivel provides a full range of movement to minimizing kinking and twisting of the coaxial curb hose during routine vehicle refueling. Complies with CARB CP-201 Enhanced Vapor Recovery EVR Program.

Model	Description	Weight	List
A4110EVR-001	Coaxial Hose Swivel	1.3 lbs.	\$94.95

Repair Kits & Replacement Parts

Model	Description
494748EVR	Fuel Path O-ring Kit
494749EVR	Vapor Path O-ring Kit

Material
 Body: Cast Aluminum
 Snap ring: Plated Steel
 Swivel nut: Chrome Plated Brass



A4119EVR Coaxial SafeBreak® Valve


The A4119EVR Coaxial SafeBreak Valve is a shear pin style non-reconnectable component designed for use with Balance Phase II Vapor Recovery Systems. A dual poppet design seals off both the fuel and vapor paths upon separation due to customer related “drive-off” occurrences, eliminating fuel spillage, vapor emissions and minimizing damage to the dispenser unit. Complies with the California Air Resources Board CARB Enhanced Vapor Recovery Program EVR Certification Procedures CP-201.

Model No.	Description	Weight
A4119EVR-020	Coaxial Shear Pin	1.6 lbs.

Repair Kits & Replacement Parts

Model	Description
494748EVR	Fuel Path O-ring Kit


Material
 Body: Aluminum
 O-rings: Buna-N
 Protective Cover: Vinyl



A0063EVR Vapor Shear Valve

The A0063EVR vapor shear valve installs on the phase II vapor riser below the dispenser to eliminate the escape of vapors in the event of a collision to the dispenser. The double poppet valve incorporates a 1.5” female NPT connection to the underground piping and a 1” female NPT connection to dispenser piping. The valve incorporates a 3/8” test port. Mounting Kit is included. Approved for use with all CARB certified pre-EVR and EVR phase II vapor recovery systems.

Model No.	Description	Inlet	Outlet	Weight
A0063EVR-024	1 1/2” Double Poppet	Female	Female	9.0 lbs.



Material
 Body: Cast Iron
 Spring: Stainless Steel
 Seal: Viton®
 Viton® is a registered trademark of DuPont Dow Elastomers.

Balance Phase II EVR Components

Repair Kits & Replacement Parts



492775EVR
Bellows & Boot Face Kit



492834EVR
Spout Kit



492776EVR
Boot Face Kit



494150EVR
Latch Kit

A4005EVR Nozzle Repair Kits

Kit No.	Description	Weight
492775EVR	Bellows & Boot Face Kit	0.4 lbs.
492776EVR	Boot Face Kit	0.2 lbs.
492834EVR	Spout Kit	0.6 lbs.
494150EVR	Latch Kit	0.5 lbs.
494748EVR	Fuel Path O-ring Kit	
494750EVR	Bellows Band Clamp Kit	0.1 lbs.
A0557EVR-002	Scuff Guard, Black	0.4 lbs.

A4110EVR Hose Swivel Repair Kits

Kit No.	Description
494748EVR	Fuel Path O-ring Kit
494749EVR	Vapor Path O-ring Kit

A4119EVR SafeBreak® Repair Kits

Kit No.	Description
494748EVR	Fuel Path O-ring Kit

A4005EVR Nozzle Required Service Tools

- 494655EVR Balance Phase II EVR Service Kit**
Includes all Phase II installation and maintenance tools and sturdy, canvas tool bag
- 494635EVR Spout Plug**
Use to conduct CARB test procedure TP-201.6 or TP-201.6C Liquid Removal Test
- 494652EVR Bellows Band Clamp Crimp Tool**
Use to install and crimp the A4005EVR nozzle bellows band clamps
- 494653EVR Lever Guard Rivet Installation Tool**
Use to install the A4005EVR nozzle lever guard rivets
- 494654EVR Lever Guard Rivet Removal Tool**
Use to remove the A4005EVR nozzle lever guard rivets
- 494712EVR Bellows Retainer Plate Tool**
Use to secure the A4005EVR nozzle bellows during installation of the bellows band clamps
- 494761EVR Balance Nozzle Adapter**
Use to test and verify the accuracy of the ISD vapor flow meter
- 494771EVR Surrogate Spout Assembly**
Use to conduct a leak tightness integrity test on the ISD vapor flow meter test assembly




Balance Phase II Pre-EVR Components

A4005/A4015 Vapor Recovery Nozzle w/Vapor Valve



A4015 Short Spout



■ CARB Executive Orders G-70-17-AD, G-70-52-AM, G-70-199-AJ

UL Listed MHI460 Classified to UL 2586

Approved by the N.Y. Department of Environmental Conservation and the Oregon Department of Environmental Quality

The A4005/A4015 Vantage has proven itself as the balance vapor recovery nozzle of choice. Developed to be user friendly, the A4005/A4015 utilizes the most up-to-date vapor recovery technology available.

The A4005/A4015 offers the same lightweight and streamlined design advantages characteristic of the A4000 series product line. A low restriction vapor valve is built into the A4005/A4015 so it does not require an external vapor valve. This nozzle includes the no-seal, no-flow interlock mechanism and automatic shutoff for reliable, safe operation. It also has an internal pressure shutoff to detect vapor blockage.

Material


Body & Spout: Aluminum
 Lever: Thermoplastic
 Lever Guard: Aluminum
 Seals: Nitrile & Viton
 Scuff Guard: Vinyl

Viton® is a registered trademark of DuPont Dow Elastomers.

Model No.	Description	Weight
A4005-002	New Unleaded	4.6 lbs.
A4005-004	Rebuilt Unleaded	4.6 lbs.
A4005-002E	New Unleaded E85	4.6 lbs.
A4015-002	New Unleaded Short Spout	4.4 lbs.
A4015-004	Rebuilt Unleaded Short Spout	4.4 lbs.
A4015-002E	New Unleaded E85 Short Spout	4.4 lbs.

The above part numbers include the standard glossy black scuff guard.

Refer to page 78 for replacement items.



Balance System

A4005/A4015 Balance Nozzle

A4005 Replacement Parts

Kit No.	Description	Weight
493040	Spout Kit - Unleaded	2.0 lbs.
493042	Boot Face Kit	0.2 lbs.
493047	Clamp & Cover Kit	0.4 lbs.
493062	Latch Kit	0.1 lbs.
493780	Boot Only Kit	1.0 lbs.
493781	Boot & Face Kit	0.7 lbs.
493846	Front End Kit - Spout/Boot	1.5 lbs.
563834	Clamp 52.2 mm	0.2 oz.
566965	Clamp 66.0 mm	0.3 oz.

A4015 Replacement Parts

Kit No.	Description	Weight
493042	Boot Face Kit	0.2 lbs.
493047	Clamp & Cover Kit	0.4 lbs.
493062	Latch Kit	0.1 lbs.
493398	Spout Kit - Unleaded	0.6 lbs.
493400	Boot & Face Kit	0.5 lbs.
493584	Boot Only Kit	0.4 lbs.
493847	Front End Kit - Spout/Boot	0.9 lbs.
563834	Clamp 52.2 mm	0.2 oz.
566965	Clamp 66.0 mm	0.3 oz.

A4005/A4015 Scuff Guards

Nozzle Variant Numbers

Model No.	Description	Weight	A4005 New	A4005 Rebuilt	A4015 New	A4015 Rebuilt
565048	Black Emco Logo	0.4 lbs.	-002	-004	-002	-004
565148	Black No Logo	0.4 lbs.	-146	-150	-024	-032

Nozzle & Breakaway Core Credit Policy

Models Allowed For Core Credit	Core Credit Value	Return for Credit Against the Following
Nozzles		
A4005	\$45	Rebuilt A4005 or A4015
A4015	\$45	Rebuilt A4005 or A4015
A4005EVR	\$85	New A4005EVR
Competitor EVR Nozzle	\$85	New A4005EVR
Breakaways		
A4119EVR	\$25	New A4119EVR
Competitor EVR Breakaway	\$25	New A4119EVR

Credits: All nozzle and breakaway cores must be returned within 90 days of invoice to be eligible for credit.

Cores with cracked bodies, stripped threads or damaged in any way that limits their ability to be rebuilt will not be accepted for credit.

Nozzle cores returned without a front end assembly (spout, bellows and boot face) or any other part will be subject to a 50% core credit reduction.

Breakaway cores returned with only one half will be subject to a 50% core credit reduction.


Invoicing: Nozzle and breakaway models allowed for core credit will be invoiced at list price less your distributor discount. Acceptable cores will be credited against those invoices.

Freight: Inbound freight charges for nozzle and breakaway cores returned for credit must be prepaid by the distributor.

Core Bank: Nozzle and breakaway cores may be sent to Emco in anticipation of future purchases. Emco will store all cores in the distributor's account for a maximum time period of 18-months from date received. All cores stored longer than 18 months will be discarded and no credit given.

Automatic Nozzles

A6000 Roughneck® Truck Stop Nozzle




The A6000 Roughneck® is a full-flow automatic nozzle for up to 60 GPM, designed for the unique durability requirements of truck stops. The A6000 has a modern, human engineered shape that's lighter, more comfortable to handle and much easier to use. Its rugged unibody construction, thick walled spout and stamped steel lever are built for durability, long lasting reliability, and maximum flow rates. The A6000 features a hold-open latch and vinyl scuff guard. Spout Kits and a variety of scuff guard colors are available. Every A6000 Roughneck® nozzle features the standard Emco Wheaton 12 month warranty. Spout ID is 1"; OD is 1 3/16".

For retaining ring on spout, specify B suffix after part number.

Material

Body & Spout: Aluminum
Lever: Steel
Lever Guard: Aluminum
Seals: Nitrile
Scuff Guard: Vinyl



Model No.	Scuff Color	Inlet Size	Weight
A6000-001	Black	1"	4.7 lbs.
A6000-001B	Black	1"	4.8 lbs.
A6000-002	Black	1" BSPT	4.7 lbs.
A6000-007*	Black	1" BSPT	4.7 lbs.
A6000-010	Yellow	1"	4.7 lbs.
A6000-012	Green	1"	4.7 lbs.
A6000-012B	Green	1"	4.8 lbs.

*Attitude Device

B versions include spout retaining ring

A6000 Replacement Parts


Kit No.	Description	Weight
492958	Latch Kit	
492769	Spout Kit	1.0 lbs.
562587	Black Scuff	0.8 lbs.
565912	Yellow Scuff	0.8 lbs.
566176	Green Scuff	0.8 lbs.

Conventional Nozzle Replacement Parts

A0500 Splash Guard

The A0500 Splash Guard is constructed of TPR and is for use on all conventional nozzles.

Model No.	Color	Weight
A0500-002	Black	0.1 lbs.
A0500-062	Green	0.1 lbs.
A0500-064	Yellow	0.1 lbs.



Additional colors are available upon request; please contact our Customer Service Department at 800-234-4394.

470002 Reducer Bushing

The 470002 Reducer Bushing is used on a conventional nozzle to convert a 1" inlet to a 3/4" inlet.

Kit No.	Description	Weight
470002	Reducer Bushing	0.1 lbs.



DISPENSER ACCESSORIES


3/4" Standard

A2119 Shear Pin SafeBreak®


A2219 Reconnectable SafeBreak®



Shear Pin



Reconnectable



Material

Body: Aluminum

O-rings & Seals: Buna-N & Viton®

Protective Cover: Plastic

Viton® is a registered trademark of DuPont Dow Elastomers

■ UL Listed MH17833

ATEX (A2119-002) FTZU07ATEX0240

ATEX (A2119-003) SIRA03ATEX9396U

ATEX (A2219-004) SIRA03ATEX9395U

ETL 536786

The Emco Wheaton A2119 Standard SafeBreak® has an economical shear pin design with 3/4" connection for standard hose applications. The double poppets seal both hoses upon separation.

The Emco Wheaton A2219 Standard SafeBreak® allows for immediate return to service after a drive-away, with no repair kit required. This is made possible by a unique, reconnectable design. The double poppets seal both hoses upon separation.

Model No.	Description	Weight
A2119-002	3/4" Shear Pin NPT	0.4 lbs.
A2119-003	3/4" Shear Pin BSPP	0.4 lbs.
A2219-002	3/4" Reconnectable NPT	0.8 lbs.
A2219-004	3/4" Reconnectable BSPP	0.8 lbs.

SafeBreak®

I" Standard

A3019 Shear Pin SafeBreak®

A3219 Reconnectable SafeBreak®




Material

Body: Aluminum


O-rings & Seals: Buna-N & Viton®

Protective Cover: Plastic

Viton® is a registered trademark of DuPont Dow Elastomers



Shear Pin



Reconnectable

■ UL Listed MH17833
ATEX (A3019-003) SIRA03ATEX9396U


The Emco Wheaton A3019 Standard SafeBreak® has an economical shear pin design with 1" connection for standard hose applications. The double poppets seal both hoses upon separation.

The Emco Wheaton A3219 Standard SafeBreak® with a 1" hose connection, allows for immediate return to service after a drive-away, with no repair kit required. This is made possible by a unique, reconnectable design. The double poppets seal both hoses upon separation.

Model No.	Description	Weight
A3019-001	1" Shear Pin NPT	1.0 lbs.
A3019-003	1" Shear Pin BSPP	1.0 lbs.
A3219-001	1" Reconnectable NPT	1.0 lbs.
A3219-003	1" Reconnectable BSPP	1.0 lbs.

Vapor Recovery Balance

A4I I9EVR Shear Pin SafeBreak®



Material
Body: Aluminum
O-rings: Buna-N
Protective Cover: Vinyl

- CARB Approval 95-3
- UL Listed MH17833
- ULC Listed MH27243
- Approved under Phase II EVR
- Executive Orders VR-207 & VR-208, VR-203-I & VR-204-I



The Emco Wheaton A4I I9EVR Coaxial SafeBreak® is made with a cost-effective shear pin design for use with coaxial, balance type hoses. A dual poppet design seals off both the fuel and vapor paths upon separation due to customer related “drive-off” occurrences, eliminating fuel spillage, vapor emissions and minimizing damage to the dispenser unit.

Model No.	Description	Weight
A4I I9EVR-020	Coaxial Shear Pin	1.6 lbs.
A4I I9-020E	Coaxial Shear Pin E85	1.6 lbs.
494748EVR	Fuel Path O-ring Kit	

Swivels


A0360 Hose Swivel

Material

Body: Aluminum or stainless steel

Seal: Viton® & Fluorosilicone

Viton® is a registered trademark of DuPont Dow Elastomers.



The Emco Wheaton A0360 Hose Swivel is available with an aluminum or stainless steel body. Both options incorporate stainless steel male fittings. Viton® o-rings provide positive sealing and compatibility with all fuels. Fluorosilicone o-rings provide excellent low temperature performance. The outlet swivel rotates 360° at the nozzle inlet to keep the nozzle in a comfortable, upright position, and prevents hose kinking and wear. The A0360 is designed for non-vapor recovery applications and is available with .75" or 1.0" NPT or BSPP or BSPT threads.

■ UL Listed MH6036

**Available in
Stainless Steel**

Model No.	Stainless Steel Model No.	Hose Connection Size	Nozzle Connection Size	A	B	Weight	SST Weight
A0360-075	A0360-075S	3/4" Female	3/4" Male	4.0"	2.2"	0.6 lbs.	1.2 lbs.
A0360-076	A0360-076S	3/4" Female BSPT	3/4" Male BSPT	4.0"	2.2"	0.6 lbs.	1.2 lbs.
A0360-077		3/4" Female BSPP	3/4" Male BSPP	4.0"	2.2"	0.6 lbs.	
A0360-100	A0360-100S	1" Female	1" Male	4.4"	2.6"	0.8 lbs.	1.9 lbs.
A0360-101		1" Female BSPT	1" Male BSPT	4.4"	2.6"	0.8 lbs.	


A4110EVR-001 Coaxial Hose Swivel

Material

Body: Cast Aluminum

Snap ring: Plated Steel

Swivel nut: Chrome Plated Brass



The Emco Wheaton A4110EVR Coaxial Hose Swivel is designed for use with balanced vapor recovery nozzles. The 45° hose swivel provides a full range of movement to minimizing kinking and twisting of the coaxial curb hose during routine vehicle refueling.

■ CARB Approval 92-14
UL Listed MH6036
Approved under Phase II EVR
Executive Orders VR-207 & VR-208

Model	Description	Weight
A4110EVR-001	Coaxial Swivel	1.3 lbs.
A4110-001E	Coaxial Swivel E85	1.3 lbs.
494748EVR	Fuel Path O-ring Kit	
494749EVR	Vapor Path O-ring Kit	




A4043 Splitter

Material

Body: Aluminum

O-rings: Buna



■ CARB Approval 94-26
UL Listed MH10206
ULC Listed MH27243

The Emco Wheaton A4043 Splitter is for use on coaxial balance Stage II Vapor Recovery Systems. The cast aluminum body is lightweight and strong. The A4043 includes two buna o-rings for a reliable hose seal.


Model No.	Application	Material	Port Size	Weight
A4043-001	High Hose Mount	Aluminum	1 7/8"	2.0 lbs.

A4041 Splitter

Material

Body: Aluminum

O-rings: Buna



■ CARB E.O. G-70-52-AL
UL Listed MH10206
ULC Listed MH27243

The Emco Wheaton A4041 Splitter is designed for converting a side mount dispenser which is not vapor ready into a coaxial vapor recovery system. For vertical island plumbing of the vapor line, order the A4041-001. For plumbing the vapor line through the dispenser wall, order the A4041-002.


Model	Application	Material	Weight	Port Sizes	
A4041-001	Island Mount	Aluminum	2.1 lbs.	Fuel Inlet	3/4"
A4041-002	Dispenser Mount	Aluminum	1.6 lbs.	Vapor Outlet	3/4"
A4041-003	Island Mount	Nickel Plated	2.5 lbs.	Coaxial	1 7/8"

Adapters/Flow Regulators

563639 Adapter

The Emco Wheaton 563639 Adapter allows you to retrofit a balance dispenser to use 3/4" NPT conventional hanging hardware.


Material		Model No.	Weight
Body:	Aluminum	563639	4.0 oz.
O-rings:	Buna		



563639AST Adapter

The Emco Wheaton 563639AST Adapter allows you to retrofit a vacuum assist dispenser to use 3/4" NPT conventional hanging hardware. The adapter is a one-piece assembly.


Material		Model No.	Weight
Body:	Aluminum	563639AST	3.2 oz.
O-rings:	Buna		



A0010 Flow Regulator

The Emco Wheaton A0010 is an in-line liquid flow regulating device calibrated to limit flow to 10 gpm, in accordance with Federal EPA requirements. The A0010 is manufactured from zinc-plated steel or aluminum with 3/4" ports.

■ CARB E.O. G-70-118-AB
UL/ULC Listed MH10206



Model	Material	Inlet	Outlet	Installation	A	B	Weight
A0010-003	Steel	Male	Female	Dispenser Outlet	1.44"	2.7"	1.0 lbs.
A0010-010	Aluminum	Female	Male	Nozzle Inlet	1.13"	2.5"	0.3 lbs.
A0010-011	Aluminum	Male	Female	Dispenser Outlet	1.13"	2.5"	0.3 lbs.

Hose Assemblies

A002I Standard Hose Assemblies

3/4"

Model No.	Description	Weight	Model No.	Description	Weight
A002I-140	6" Whip Hose	0.56 lbs.	A002I-149	9" Whip Hose	0.66 lbs.
A002I-145	8" Whip Hose	0.62 lbs.	A002I-150	10" Whip Hose	0.69 lbs.
A002I-148	9" Whip, Swivel One End	0.70 lbs.	A002I-155	12" Whip Hose	0.75 lbs.

Model No.	Description	Weight
A002I-300	8.0' Curb Pump Hose	3.51 lbs.
A002I-301	8.0' Curb Pump Hose, Swivel One End	3.55 lbs.
A002I-303	8.5' Curb Pump Hose	3.71 lbs.
A002I-304	8.5' Curb Pump Hose, Swivel One End	3.75 lbs.
A002I-305	9.0' Curb Pump Hose	3.90 lbs.
A002I-306	9.0' Curb Pump Hose, Swivel One End	3.95 lbs.
A002I-307	9.0' Curb Pump Hose, Swivel Both Ends	3.99 lbs.
A002I-308	9.5' Curb Pump Hose	4.10 lbs.
A002I-309	9.5' Curb Pump Hose, Swivel One End	4.14 lbs.
A002I-310	10.0' Curb Pump Hose	4.30 lbs.
A002I-311	10.0' Curb Pump Hose, Swivel One End	4.34 lbs.
A002I-313	10.5' Curb Pump Hose	4.49 lbs.
A002I-314	10.5' Curb Pump Hose, Swivel One End	4.54 lbs.
A002I-315	11.0' Curb Pump Hose	4.69 lbs.
A002I-316	11.0' Curb Pump Hose, Swivel One End	4.73 lbs.
A002I-320	12.0' Curb Pump Hose	5.08 lbs.
A002I-321	12.0' Curb Pump Hose, Swivel One End	5.13 lbs.
A002I-325	13.0' Curb Pump Hose	5.48 lbs.
A002I-326	13.0' Curb Pump Hose, Swivel One End	5.52 lbs.
A002I-330	14.0' Curb Pump Hose	5.87 lbs.
A002I-331	14.0' Curb Pump Hose, Swivel One End	5.91 lbs.
A002I-335	15.0' Curb Pump Hose	6.27 lbs.
A002I-336	15.0' Curb Pump Hose, Swivel One End	6.31 lbs.
A002I-345	17.0' Curb Pump Hose	7.05 lbs.
A002I-346	17.0' Curb Pump Hose, Swivel One End	7.10 lbs.
A002I-350	18.0' Curb Pump Hose	7.45 lbs.
A002I-351	18.0' Curb Pump Hose, Swivel One End	7.49 lbs.
A002I-355	19.0' Curb Pump Hose	7.84 lbs.
A002I-356	19.0' Curb Pump Hose, Swivel One End	7.88 lbs.
A002I-360	20.0' Curb Pump Hose	8.23 lbs.
A002I-361	20.0' Curb Pump Hose, Swivel One End	8.28 lbs.
A002I-905	5.0' Curb Pump Hose	2.33 lbs.
A002I-925	30.0' Curb Pump Hose	12.17 lbs.
A002I-934	4.0' Curb Pump Hose	1.94 lbs.



- Couplings are available as internally expanded brass fittings  or brass inserts with crimped aluminum ferrules 
- Single-wire braid construction provides static conductivity and increases hose strength 
- Compatible with up to E15 ethanol blend gasoline and B20 biodiesel blends
- UL 330 listed
- Softwall hose assemblies also available
- Custom lengths are available

1"

Model No.	Description	Weight	Model No.	Description	Weight
A002I-170	6" Whip Hose	0.8 lbs.	A002I-400	8' Curb Pump Hose	6.5 lbs.
A002I-175	8" Whip Hose	1.3 lbs.	A002I-405	9' Curb Pump Hose	7.1 lbs.
A002I-177	9" Whip Hose	1.7 lbs.	A002I-410	10' Curb Pump Hose	7.7 lbs.
A002I-180	10" Whip Hose	2.1 lbs.	A002I-420	12' Curb Pump Hose	8.9 lbs.
A002I-185	12" Whip Hose	2.9 lbs.	A002I-445	17' Curb Pump Hose	12.0 lbs.
A002I-188	13.5" Whip Hose	3.5 lbs.	A002I-460	20' Curb Pump Hose	13.9 lbs.
			A002I-927	6' Curb Pump Hose	5.3 lbs.

Dispenser Conversion Frames

A0069 Dispenser Conversion Frame


The Emco Wheaton A0069 Dispenser Conversion Frame is designed for use when converting old dispensers to new dispensers. The A0069 is constructed of stainless steel, and comes complete with mounting hardware. The conversion frames are available in both raised platform and flush mount applications. Custom applications are also available.

Material

Frame: 304 Stainless Steel
Installation Hardware: Stainless Steel
Adhesive: Powers AC100+ Gold®



Stainless Steel
at Powder Coated
Pricing



Flush Mount



Model No.	Frame Style	Old Dispenser	New Dispenser
A0069-001	Raised Platform	<u>Gilbarco Advantage</u>	<u>Gilbarco Encore</u> NA0, NA1, NA2, NA3, NG0, NG1, NG4, NJ0, NJ2, NJ4, NL0-3, NN0-3, NP3, NP4, NC0, NC1, NC2, NC3, NG2, NG3, NG5, NJ1, NJ3, NL4-7, NN5-7
A0069-003	Raised Platform	<u>Tokheim</u> H311B, H312B, H322B, H324B, H411B, H413B, H422B, H426B	<u>Gilbarco Encore</u>
A0069-007	Raised Platform	<u>Wayne Vista</u> 3/V390D, 3/V390D/U, 3/V390P, 3/V390P/U, 3/V394D, 3/V399D, 3/V399P, 3/V490D, 3/V490D/U, 3/V590D, 3/V590D/U, 3/V590P/U, 3/V591D, 3/V591P, 3/V595D, 3/V595D/U, 3/V595P, 3V595P/U	<u>Wayne Ovation</u> B12, B23, R22
A0069-017	Raised Platform	<u>Gilbarco Encore</u>	<u>Wayne Ovation</u>
A0069-101	Flush Mount	<u>Gilbarco MPD</u>	<u>Gilbarco Encore</u>

Dispenser Sumps

A0718 Above Ground Dispenser Sumps


The Emco Wheaton A0718 Above Ground Dispenser Sump is designed for use in marina and aboveground applications to mount dispensers that are plumbed to above ground tanks. The A0718 is constructed of Type 304 stainless steel. Includes hardware for the shear valve stabilizer bar and to mount the frame to the sump. The sumps are available with flush mount or raised anchor legs. Piping penetration is done on site.

The upper dispenser frame is interchangeable. When upgrading dispensers, it is only necessary to change out the frame; the sump remains in place.

Material

Frame and Sump: 304 Stainless Steel

Hardware: Stainless Steel



Model No.	Description	Bolt Pattern			Rain Lip	
		A	Mid	B	C	D
A0718-729CMDR-1	Commander; 1 bracket/1 mounting plate/1 stabilizer bar	19.75"	--	14.88"	13.5"	22.10"
A0718-729CMDR-2	Commander; 2 brackets/2 mounting plates/2 stabilizer bars	19.75"	--	14.88"	13.5"	22.10"
A0718-729ATLS-1	Gasboy Atlas; 1 bracket/1 mounting plate/1 stabilizer bar	12.60"	6.3"	14.04"	12.5"	24.75"
A0718-729ATLS-2	Gasboy Atlas; 2 brackets/2 mounting plates/2 stabilizer bars	12.60"	6.3"	14.04"	12.5"	24.75"

Fuel Stop Switch Pedestal


A0729 E-Stop Switch Pedestal

The Emco Wheaton A0729-048 E-Stop Switch Pedestal is designed for emergency shut-off switches. A hole in the base provides wiring access. Welded aluminum construction. Tiger series 38 super durable powder coating in anodized silver, meets AAMA 2604 compliance providing corrosion and weather resistance in marine and other harsh environments. UV resistant for five years in Florida exposure. E-stop and sign not included.

Material

Pedestal: Powder coated aluminum

Base: Powder coated aluminum



Model No.	Height	Weight
A0729-048	48"	11.5 lbs.

Custom sizes available

CROSS REFERENCE

Competitor Cross Reference

Emco	Description	OPW	Franklin	Universal	Morrison Bros.
Caps and Adapters					
A0030-024	FILL ADAPTER BRASS 4X4	633T-8076	778-301-02	724-4040	305L-0200A
A0030-024A	FILL ADAPTER ALUMINUM 4X4	633T-8075			
A0030-124S	FILL SWIVEL ADAPTER BRASS 4X4	61SALP-1020EVR	SWF-100-B		305SA-0200AA
A0076-002	VAPOR ADAPTER AL 4"CAMX3" RISER	1611AV-1605	300-300-01	0611V-3030	323-0100-AA
A0076-005	VAPOR ADAPTER AL 4"CAMX4" RISER	1611AV-1620	300-210-01	0611V-3040	323-0200-AA
A0076-124S	VAPOR SWIVEL ADAPTER BRASS 4X4	61VSA-1020EVR	SWV-101-B		323SA-0200-AA
A0089-001	TIGHT FILL ADAPTER COAX A0088	633TCP-3803		724CA-4040	605AL-0100-AA
A0096-001	TIGHT FILL ADAPTER COAX A0070	633TC-8090	306-300-01	724CA-4040	605AL-0100-AA
A0097-004LP	TIGHT FILL CAP 4" LOW PROFILE	634LPC-0400		731-40	
A0097-005	TIGHT FILL CAP 4"	634TT-7085EVR	777-201-01	733-40	305C-0100-ACEVR
A0097-010	TIGHT FILL CAP 4" FOR TANK PROBE	62M-0500		418TM-40	
A0099-002	VAPOR CAP 4"	1711T-7085 EVR	304-200-01	0614VC-30	323C-0100-ACEVR
A0099-004LP	VAPOR CAP 4" LOW PROFILE	1711LPC-0300		0613VC-30	

Emergency Shear Valves

A0060-002	SHEAR VALVE 1 POP MALE	10BM-5825	662-410-03	521RMS-15	636M 0000 AVU
A0060-003	SHEAR VALVE 1 POP FEMALE	10BF-5725	662-410-02	521RFS-15	636F 0000 AVU
A0060-022	SHEAR VALVE 2 POP MALE	10BHMP-5830	662-440-03	521DP-RM-15	
A0060-023	SHEAR VALVE 2 POP FEMALE	10BFP-5726	662-440-02	521DP-RF-15	
A0063EVR-024	VAPOR SHEAR VALVE 2 POP FEMALE	60VSP-1001			
492938	TOP KIT A0060 1 POP MALE	10RMT-5850	662-118-03		
492939	TOP KIT A0060 1 POP FEMALE	10RFT-5750	662-118-02		
493887	TOP KIT A0060 2 POP MALE	10RMTP-5851	662-240-01		
493888	TOP KIT A0060 2 POP FEMALE	10FTP-5701	662-242-01		

Overfill Prevention Valves

AI100-010	GUARDIAN VALVE ONLY 4"	61SO-4BYT	708-494-04	39-04	
AI100-055S	DUAL POINT SCREW TOGETHER 4"X13'	71SO-400C	708-491-01		
AI100-056S	DUAL POINT SCREW TOGETHER 4"X15'	71SO-410C	708-491-02		
AI100-057S	DUAL POINT SCREW TOGETHER 4"X18'		708-492-01		
AI100-058S	DUAL POINT SCREW TOGETHER 4"X21'		708-492-02		
AI100-065S	COAX SCREW TOGETHER 4"X13'	61SOC-4001	708-493-03		
AI100-066S	COAX SCREW TOGETHER 4"X15'		708-493-04		
AI100-067S	COAX SCREW TOGETHER 4"X18'	61SOC-4011			
AI100-085S	COAX SCREW TGTHR POPPET 4"X13'	61SOP-4002			
AI100-087S	COAX SCREW TGTHR POPPET 4"X18'	61SOP-4012			
AI100EVR-055	DP SCREW TOGETHER EVR 4"X13'	71SO-400C	708-491-11		
AI100EVR-056	DP SCREW TOGETHER EVR 4"X15'	71SO-410C	708-491-12		
AI100EVR-057	DP SCREW TOGETHER EVR 4"X18'		708-492-11		
AI100EVR-057E	DP SCREW TOGETHER EVR 4"X18' E85	61SOM-412C-EVR	708-492-31		
AI100EVR-058	DP SCREW TOGETHER EVR 4"X21'	71SO-420C	708-492-12		

Drop Tubes

A0020-004	DROP TUBE ALUMINUM 4" X 12'	61T-7268		723-4012-2	419-0400-1T
A0020-005	DROP TUBE ALUMINUM 4" X 15'	61T-7368		723-4015	419-0500-1T
A0020-007	DROP TUBE ALUMINUM 4" X 17'	61T-7468			
A0020EVR-004	DROP TUBE ALUMINUM 4" X 12' EVR	61T-7268	782-204-12-2		
A0020EVR-005	DROP TUBE ALUMINUM 4" X 15' EVR	61T-7368	782-204-15-2		
A0020EVR-007	DROP TUBE ALUMINUM 4" X 15' EVR	61T-7468			
A0088-101	DROP TUBE COAXIAL VR 4" X 12'	61TCP-3800			

Competitor Cross Reference

Emco	Description	OPW	Franklin	Universal	Morrison Bros.
Ball Floats & Extractor Fittings					
A0075-001	BALL FLOAT 2X5" 1/8 BH	53VL-0050		37-206018	317-0600AV
A0075-006	BALL FLOAT 2X6.87" 1/16 BH	53VL-0060		37-206016	
A0075-010	BALL FLOAT 2X18" 1/8 BH				317-1700-AV
A0075-013	BALL FLOAT 2X13.75" 1/8 BH			37-201218	
A0075-015	BALL FLOAT 2X15.75" 1/8 BH			37-201618	317-1500AV
A0075-017	BALL FLOAT 2X17.75" 1/8 BH				317-1700AV
A0078-009A	BALL FLOAT/CAGE 2X9" 1/16 BH	53VML-2090			
A0078-015	BALL FLOAT/CAGE 2X15.75" 1/16 BH	53VML-0160	308-020-116		
A0078-018A	BALL FLOAT/CAGE 2X18" 1/16 BH	53VML-0180			
A0078-021A	BALL FLOAT/CAGE 2X21" 1/16 BH	53VML-0210			
A0078-308	BALL FLOAT/CAGE 3X8" 1/16 BH	53VML-3080	308-300-08		
A0078-312	BALL FLOAT/CAGE 3X12" 1/16 BH	53VML-3120	308-300-12		
A0078-318	BALL FLOAT/CAGE 3X18" 1/16 BH	53VML-3180	308-300-18		
A0079-019	EXTRACTOR FTG & 2" CAGE 4X4X3X2			V421-3020	562-0100-AE
A0079-020	EXTRACTOR FTG & 2" CAGE 4X4X2X2			V421-2020	560-0100-AE
A0079-025	EXTRACTOR FTG & 2" CAGE 4X4X3X3			V421-3030	
A0079-050	EXTRACTOR FTG 4X4X2X2	233-4422		V420-2020	560-0101-MBE
A0079-051	EXTRACTOR FTG 4X4X3X2	233-4432	330-400-11	V420-3020	562-0101-MBE
A0079-052	EXTRACTOR FTG 4X4X3X3	233-4433	331-400-01	V420-3030	
A0079-119	EXTRACTOR FTG & 2" CAGE 4X4X3			V421-0030	563-0100AE
A0079-120	EXTRACTOR FTG & 2" CAGE 4X4X2			V421-0020	561-0100AE
A0079-150	EXTRACTOR FTG 4X4X2	233-4420		V420-0020	561-0101MBE
A0079-152	EXTRACTOR FTG 4X4X3	233-4430		V420-0030	563-0101MBE
A0179-002	EXTRACTOR CAGE 2"	H11930		V423	
A0279-001	EXTRACTOR CAGE TEST PLUG	233VMP-6047	391-201-01	V425	
A0560-003	WRENCH FOR BAR-STYLE CAGE 1 1/2"	89-0044	321-100-01	410W	
A0585-003	EXTRACTOR PIPE CAP BAR STYLE	116-7085		412-40	578-0100AC

Valves

A0066-020	CHECK VALVE PRES RELIEF 15-35PSI		622-200-01	212BPR-20-1535	
A0750-200	BALL VALVE	21BV-0200		213FP-20	

Suction System Components

A0732-001	UNION CHECK VALVE 1.5"		650-108-02	200A-15	331-0100AV
A0732-002	UNION CHECK VALVE & SCREEN 1.5"		650-104-02	200AS-15	331S-0100AV

Vents

		OPW	Franklin	Universal	Morrison Bros.
A0084-038	VENT P-V 3" PRES 8" VAC 2" F EPA	623V-2203			749CRB0600AV
A0084-103	VENT P-V 3" PRES 8" VAC 2" SLIP ON EPA				749CRBS600AV
A0084-204	VENT P-V 8 OZ. PRES .5 VAC 2"	523V-1100	802-303-01	46-2080	749-0100AV
A0084-215	VENT P-V 13.86" PRES 3" VAC 2" SLIP ON	523V-2253			
A4103-002	VENT UPWARD "V" 1.5" & 2"	23-0033, -0044		45-15 / 45-20	

Competitor Cross Reference

Emco	Description	OPW	Franklin	Universal	Fairfield
Spill Containment					
A1004-010	SPILL CONT 5GAL SLIM PP DRAIN	IC-2100D	705-479-01-CI	71CD-1212	
A1004-316A	SW 16" CENTER 5 GAL PP DRAIN	IC-3101D	705545001CI		
A1004-316S	DW 16" CENTER 5 GAL PP DRAIN	IC-3112D	705555101CI	71CD-0512-DW	SCM-5DWT
A1004-316S-CM	DW 16" CENTER 5 GAL SENSOR DRAIN		705555201CI		
A1004-317A	SW 16" CENTER 5 GAL NO DRAIN	IC-3101P	705545002CI		
A1004-317S	DW 16" CENTER 5 GAL NO DRAIN	IC-3112P	705555102CI		
A1004-317S-CM	DW 16" CENTER 5 GAL SENSOR NO DRN		705555202CI		
A1004EVR-210A	SINGLE WALL 5 GAL PP DRAIN EVR	IC-3101D	705545001CI		
A1004EVR-210S	DOUBLE WALL 5 GAL PP DRAIN EVR	IC-3112D	705555101CI		
A1004EVR-211A	SINGLE WALL 5 GAL PP NO DRAIN EVR	IC-3101P	705545002CI		
A1004EVR-211S	DOUBLE WALL 5 GAL PP NO DRAIN EVR	IC-3112P	705555102CI		
A1004EVR-316A	SW 16" CENTER 5 GAL PP DRAIN EVR	IC-3101D	705545001CI		
A1004EVR-316S	DW 16" CENTER 5 GAL PP DRAIN EVR	IC-3112D	705555101CI		
A1004EVR-317A	SW 16" CENTER 5 GAL PP NO DRAIN EVR	IC-3101P	705545002CI		
A1004EVR-317S	DW 16" CENTER 5 GAL PP NO DRAIN EVR	IC-3112P	705555102CI		
A1004EVR-215A	SINGLE WALL 15 GAL PP DRAIN EVR	6511A-0025SCI51			
A1004EVR-215S	DOUBLE WALL 15 GAL PP DRAIN EVR	IC-31512D			
A0031-175	RISER EXTENSION 4 X 4 X 1.75			1002S-40	
A0031-250	RISER EXTENSION 4 X 4 X 2.5			1002L-40	57IS-0100AE

Composite Manholes		OPW	Franklin	Flexing	Morrison Bros.
A0716-039	COMPOSITE LAY-IN 39X10	39CD-PL10	781-433-13	14U-3810	318L 3800AM
A0716-039B	COMPOSITE BOLT-DOWN 39X10	39CD-WT10	781-433-12	14URT-3810	418L 3800AM
A0716-039C	COMPOSITE CAM-LOCK 39X10	39CD-RL10		14URT-3810CL	418LC3800AM
A0716-039CL	COMPOSITE CAM-LOCK LID ONLY 39"	E00714			
A0716-039LID	COMPOSITE LAY-IN LID ONLY 39"	E00618	781-448-06	14U-3810C	
A0716-042	COMPOSITE LAY-IN 42X10			14U-4210	
A0716-042LID	COMPOSITE LAY-IN LID ONLY 42"			14U-4210C	
A0716-044	COMPOSITE LAY-IN 44X10	44CD-PL10	781-443-13		318L 4400AM
A0716-044B	COMPOSITE BOLT-DOWN 44X10	44CD-WT10	781-443-12		418L 4400AM
A0716-044C	COMPOSITE CAM-LOCK 44X10	44CD-RL10			418LC4400AM
A0716-044CL	COMPOSITE CAM-LOCK LID ONLY 44"	E00712			
A0716-044LID	COMPOSITE LAY-IN LID ONLY 44"	E00626	781-445-06		

Standard Manholes		OPW	Franklin	Pemco	Fairfield
A0717-018	MANHOLE CI LID 18"X12" STEEL	104A-1800	781-418-12-STL	10618x10	180-12
A0717-018A	MANHOLE CI LID 18"X18" STEEL		781-418-18-STL		180-18
A0717-024	MANHOLE 3/8" STEEL LID 24"X10" STEEL	6110-2410	SR2409HD	10624X10	240 HD
A0717-030	MANHOLE 3/8" STEEL LID 30"X10" STEEL	6110-3010	SR3009HD	10630X10	300 HD-B
A0717-030B	MH 3/8" STEEL LID 30"X10" STEEL BD		SR3009WT	10730X10	300 WT
A0717-036	MANHOLE 1/2" STEEL LID 36"X10" STEEL		SR3609HD		
A0717-036B	MH 1/2" STEEL LID 36"X10" STEEL BD	6110-37WT	SR3609WT		
A0717-038	MANHOLE 1/2" STEEL LID 38"X10" STEEL		SR3809HD		
A0717-038B	MH 1/2" STEEL LID 38"X10" STEEL BD	6110-37WT	SR3809WT		
A0717-038C	MANHOLE 3/8" STEEL LID 38"X10" STEEL	6110-3710		10638X10	380HD
A0717-042A	MANHOLE 1/2" STEEL LID 42"X10" STEEL	6110-4200	SR4209HD		420HD
A0717-042D	MANHOLE 3/8" STEEL LID 42"X10" STEEL			10642X10	
A0717-048	MANHOLE 1/2" STEEL LID 48"X10" STEEL		SR4809HD	10748X10	480HD
A0717-108	MANHOLE CI LID 8"X12" STEEL			100C8X12	80-12
A0717-122	MANHOLE CI LID 12"X12" STEEL	104A-1200	781-212-12-CI	100C12X12	120-12
A0717-122BW	MANHOLE STL LID 12"X12" STEEL BD			10212X12	120WT
A0717-122FG	MANHOLE CI LID 12"X12" STEEL FINGER	104FG-1200			

Competitor Cross Reference

Emco	Description	OPW	Franklin	Pemco	Fairfield
Standard Manholes, continued					
A0717-124	MANHOLE STEEL LID 24"X10" STEEL BD	6110-24WT		I0724X10	240WT
A0717-128	MANHOLE CI LID 12"X8" STEEL			I00C12X8	120 8
A0717-136	MANHOLE 3/8" STEEL LID 36"X10" STEEL	6110-3710		I0636x10	360 HD
A0717-136B	MH 3/8" STEEL LID 36"X10" STEEL BD			I0736X10	360 WT
A0717-148	MANHOLE 3/8" STEEL LID 48"X10" STEEL		SR4809WT	I0648X10	
A0717-188	MANHOLE CI LID 8"X9" STEEL		78120808	I00C8X75	80 8

Square Manholes and Vaults

A0717-718	MANHOLE STEEL LID SQUARE 18"X9"				18S
A0717-724	MANHOLE STEEL LID SQUARE 24"X9"		SSQ2409	I0524X24	24S
A0717-724A	MANHOLE STEEL LID SQUARE 24"X24"			I0524X24X24	
A0717-724ABW	MANHOLE STEEL LID SQ 24"X24" BD WR			I0524X24WT	
A0717-724V	MANHOLE LOCKING VAULT 24"X24"			I04242424	
A0717-724VW	MANHOLE LOCKING VAULT 24"X24" WR			I04242424WT	

Monitoring Well Manholes

		Universal	Morrison Bros.	Pemco	Fairfield
A0720-001	MONITOR WELL CAP, COLLAR & LOCK	1300-40	305XA-0100 AC		
A0721-018	MONITOR WELL 18"X12" STEEL		418XAP-1200 AM	I06MW18X12	I08-TMW-12
A0721-101	MONITOR WELL 12"X12" STEEL	65-1212-WC	418XAP-0400 AM	I0312X12	I20-MW-12
A0721-106	MONITOR WELL 6"X8" STEEL			I035X6	
A0721-106A	MONITOR WELL 6"X10" STEEL			I035X12	
A0721-108	MONITOR WELL 8"X12" STEEL	65-8012-WC	418XAP-0900 AM	I038X12	80-MW-12
A0721-118	MONITOR WELL 18"X18" STEEL		418XAP-1300 AM		I80-TMW-18
A0721-119	MONITOR WELL 12"X19" STEEL			I0312X18	
A0721-188	MONITOR WELL 8"X9" STEEL	65-8075-WC	418XAP-0850 AM	I038X75	80-MW-8
A0721-188L	MONITOR WELL 8"X9" STEEL LAY-IN	60MW-8075		I00MW8X75	
A0721-208	MONITOR WELL 8"X12" HD STEEL		418XAW-0700 AM		

Vapor Recovery Balanced Nozzles

		OPW	Husky	VST
A4005-NUL	N-NOZZLE-BAL-UL	I1VF-XX27	005210-04	
A4005-RUL	R-NOZZLE-BAL-UL	I1VF-XX87	005450-04	
A4015-NUL	N-NOZZLE-BAL-UL		005010-04	
A4015-RUL	R-NOZZLE-BAL-UL		005410-04	
A4005EVR-052	N-NOZZLE-BAL-UL EVR			VST-EVR-NB

Truck Nozzle

A6000-N	N-STD-NOZZLE-TRUCK	7H	VIII-173310	
---------	--------------------	----	-------------	--

Competitor Cross Reference

Emco	Description	OPW	Franklin	Husky	VST
Safebreaks					
A2119-002	SAFEBREAK 3/4" SHEAR PIN	66V-0300		2273	
A2219-002	SAFEBREAK 3/4" RECONNECTABLE	66REC-1000	697-137-01	3360	
A3019-001	SAFEBREAK 1" SHEAR PIN	66V-1300			
A3219-001	SAFEBREAK 1" RECONNECTABLE	66RB-2000	797-225-01	2276	
A4119EVR-020	SAFEBREAK COAXIAL SHEAR PIN EVR				VSTA-EVR-SBK

Swivels

A0360-075	SWIVEL 3/4"M X 3/4"F NPT	205-7575	3DC3/4	0350	
A0360-100	SWIVEL 1"M X 1"F NPT	205-1010	3DC1X1	0087	

Splitters

A4041-001	COAX SPLITTER ISLAND MOUNT	38CS-0380	3030101		
A4043-001	COAX SPLITTER HIGH HOSE				

Hose Assemblies

		IRPCO	Goodyear	Thermoid
A0021-145	HOSE WHIP 3/4" X 8" STANDARD	124021	532-327-124-20969	
A0021-149	HOSE WHIP 3/4" X 9" STANDARD	124041		
A0021-155	HOSE WHIP 3/4" X 12" STANDARD		532-327-124-21269	
A0021-180	HOSE WHIP 1" X 10" STANDARD	123041		
A0021-185	HOSE WHIP 1" X 12" STANDARD	123061		
A0021-305	HOSE CURB PUMP 3/4" X 9' STANDARD		532-327-124	1481-211
A0021-310	HOSE CURB PUMP 3/4" X 10' STANDARD	124341	532-327-124	1481-101
A0021-320	HOSE CURB PUMP 3/4" X 12' STANDARD	124421	532-327-124	1481-121
A0021-330	HOSE CURB PUMP 3/4" X 14' STANDARD	124481	532-327-124	1481-141
A0021-335	HOSE CURB PUMP 3/4" X 15' STANDARD	124501		1481-151
A0021-400	HOSE CURB PUMP 1" X 8' STANDARD	123201	532-327-13200869	
A0021-410	HOSE CURB PUMP 1" X 10' STANDARD	123241	532-327-13221069	1641-101
A0021-420	HOSE CURB PUMP 1" X 12' STANDARD	123301	532-327-132	1641-121
A0021-445	HOSE CURB PUMP 1" X 17' STANDARD	123461	537-327-13201769	1641-171
A0021-460	HOSE CURB PUMP 1" X 20' STANDARD	123521	537-327-13202069	1641-201

Numerical Index

Model Number	Product Description	Page Number	Model Number	Product Description	Page Number
409628	Gasket Kit A0030-014, 024, 114	5	494263	Bolt 3/8" w/O-ring 5" A0721 Lid	65
470002	Reducer Bushing A2000/A2500	80	494301	O-ring Kit, Swivel Adapters	5,8
492769	Spout Kit A6000	79	494329	Internal Repair Kit, A1004 Fatboy	55
492775EVR	Bellows & Boot Face Kit A4005EVR	76	494335	Lid for OPW 1-2100 Series Spill Cont.	53
492776EVR	Boot Face Kit A4005EVR	76	494343	Test Adapter A1004-210TEST	50
492834EVR	Spout Kit A4005EVR	76	494350	Primary Replacement Kit A1004-210S	55
492938	Top Kit Male A0060-002	10	494350-CM	Primary Replacement Kit A1004-210S-CM	55
492939	Top Kit Female A0060-003	10	494350EVR	Primary Rplcmnt Kit A1004EVR-210S	55,69
492958	Latch Kit A6000	79	494360	Primary Replacement Kit A1004-210A	55
492963K	Fusible Link Kit A0060	10	494360EVR	Primary Rplcmnt Kit A1004EVR-210A	55,69
493040	Spout Kit UL A4005	78	494367	Dipstick Assembly A1004EVR	54,69
493042	Boot Face Kit A4005/A4015	78	494375	Bolt 9/16" w/O-ring 18" A0721 Lid	65
493047	Clamp & Cover Kit A4005/A4015	78	494466EVR	Primary Rplcmnt Kit A1004EVR-211A	55,69
493062	Latch Kit A4005/A4015	78	494467G	Primary Replacement Kit A1004-211G	55
493123	Lid & O-Ring Aluminum A1003	52	494467EVR	Primary Rplcmnt Kit A1004EVR-211S	55,69
493192	A1100 Kit, Assembly Valve to Tube	14	494550EVR	Pri.&Sec. Rplcmnt Kit A1004EVR-215S	55,69
493195	Coax Collar Kit A0070 (Not Self-Sealing)	17	494551	Drain Kit A1004-210,-316	54
493197	Self-Sealing Coax Collar Kit A0088	17	494554	Lid & Seal Kit A1004-215	52
493391	Riser Collar Kit A0020	16	494635EVR	Spout Plug A4005EVR Service Tool	76
493398	Spout Kit UL A4015	78	494641	Dipstick Assembly A1004-210,-316	54
493400	Boot & Face Kit A4015	78	494652EVR	Bellows Band ClampCrimpTool A4005EVR	76
493436	Remote Fill Cage Kit	14	494653EVR	Lever Guard Rivet Install Tool A4005EVR	76
493508K	Pull/Push Drain Assembly A1004	54	494654EVR	Lever Guard Rivet RemovalTool A4005EVR	76
493584	Boot Only Kit A4015	78	494655EVR	Balance Phase II EVR Service Kit	76
493734E	Support Collar A1100EVR	71	494660EVR	Pri.&Sec. Rplcmnt Kit A1004EVR-216S	55,69
493734S	Support Collar A1100 Dual Point	14	494697	Drain Plug Kit for 494551 Drain	54
493780	Boot Only Kit A4005	78	494712EVR	Bellows Retainer Plate Tool A4005EVR	76
493781	Boot & Face Kit A4005	78	494748EVR	Fuel Path O-Ring Kit A4005,4110,4119EVR	75,76
493785S	Replacement Collar Kit Self-Sealing Coax	15	494749EVR	Vapor Path O-Ring Kit A4110EVR	75,76
493806	Lid & Seal A1004,A1005	52	494750EVR	Bellows Band Clamp Kit A4005EVR	76
493820	Wrench Drain 494118, 493508K	54,70	494761EVR	Balance Nozzle Adapter A4005EVR	76
493846	Front End Kit Spout/Boot A4005	78	494771EVR	Surrogate Spout Assembly A4005EVR	76
493847	Front End Kit Spout/Boot A4015	78	494794	Primary Replacement Kit A1004-316S	55
493855	Bellows Assembly A1005-001	55	494794EVR	Primary Rplcmnt Kit A1004EVR-316S	55,69
493885	Top Kit Female BSP A0060-016	10	494794-CM	Primary Replacement Kit A1004-316S-CM	55
493886	Top Kit Male BSP A0060-015	10	494795	Primary Replacement Kit A1004-317S	55
493887	Top Kit Male A0060-022	10	494795EVR	Primary Rplcmnt Kit A1004EVR-317S	55,69
493888	Top Kit Female A0060-023	10	494795-CM	Primary Replacement Kit A1004-317S-CM	55
493889	Top Kit Male BSP A0060-025	10	494797	Primary Replacement Kit A1004-316A	55
493890	Top Kit Female BSP A0060-026	10	494797EVR	Primary Rplcmnt Kit A1004EVR-316A	55,69
494096	Riser Seal Assembly	68	494798	Primary Replacement Kit A1004-317A	55
494118	Drain Valve Kit w/Filter	54,69	494798EVR	Primary Rplcmnt Kit A1004EVR-317A	55,69
494120	Riser Seal Wrench	70	494833	Test Cover A1005-505C Series	47
494150EVR	Latch Kit A4005EVR	76	494836	Primary Rim Kit A1004-316	55
494240	Swivel Adapter Torque Wrench	70	494845	Flange Seal A1005-517 Series	55
494241	Spill Containment Wrench	70	494854	Test Cover A1005-505CP	47
494247	Internal Repair Kit, A1004 Slimline	55	494875	Adapter Kit 494551 Drain	54
494260	Bolt 5/8" w/O-ring 8" A0721 Lid	65	494888	Handle Kit A1004-316LID	55
494261	Bolt 9/16" w/O-ring 8" A0721 Lid	65	494890	Sensor Test Port Cap	54
494262	Bolt 5/8" w/O-ring 12", 18" A0721 Lid	65	494897	Flange Seal A1005-517GS	55

Numerical Index

Model Number	Product Description	Page Number	Model Number	Product Description	Page Number
494952	Adapter Kit for 494118 Drain	54	A0030	Tight Fill Adapter	5
495202	Drain Plug Kit, 493508K, 494118 Drains	54	A0030-014	Automatic Tank Gauge Adapter	5,68
562587	Scuff Black A6000 Truck	79	A0030-124S	Tight Fill Swivel Adapter Brass 4"x4"	5,68
562803	Gasket for A0076-005	8	A0031	Riser Extension	48
563593	Gasket 12" Lid A0721	65	A0032-001	Adapter Clamp	6
563639	Adapter Coax to NPT	86	A0033-004	Debris Collector	6
563639AST	Adapter Vac Assist to Conventional	86	A0060	Shear Valve	10
563834	Clamp 52.2 mm A4005/A4015	78	A0063	Vapor Shear Valve	11,75
563939	Replacement Gasket A0097, A0099	7,9	A0065	Mounting Kit for A0060	11
563980	Lid Ductile 12" A0721	65	A0066	Multi-Purpose Check Valve	21
564029	Lock/Key Set A0720	64	A0069	Dispenser Conversion Frame	88
565048	Scuff Black A4005/A4015	78	A0070	Drop Tube Coaxial	17
565148	Scuff Black No Logo A4005/A4015	78	A0075	Ball Float	20
565271	Rim, Ductile, A1004 Fatboy	55	A0076	Vapor Adapter	8
565912	Scuff Yellow A6000 Truck	78	A0076-124S	Vapor Swivel Adapter Brass	8,68
566176	Scuff Green A6000 Truck	78	A0078	Ball Float with Cage	20
566332	Lid A1004 Fatboy	52	A0079	Extractor Fitting	18
566675	Drill Fixture A1100	14,70	A0079-444	Extractor Tee	13,18,37
566949	Rim Ductile A1004 Slimline	55	A0081-001	Wrench, Adapter	51
566965	Clamp 66.0 mm A4005/A4015	78	A0081-001C	Wrench, Adapter Compact	51,70
567146	Gasket 8" Lid A0721	65	A0081-001H	Wrench, Primary Repair Kit	51
567150	Lid Ductile 8" A0721 White	65	A0081-001R	Retrofit Lid Wrench	42,51
567166K	Triple Wiper Seal A1004-210LID, 493806	53	A0081-003	Pipe Nipple Extractor	51
567177	Lid Ductile 12" A0717 Round	61	A0081-006JP	Remote Fill Piping Test Assembly	13,37
567712	Lid Ductile 18" A0721	65	A0084	Vent P-V	23,24
567995	Gasket 18" Lid A0721	65	A0085	Vent Adapter	24
568662	Bolt 6" Lid A0721	65	A0088	Drop Tube Coaxial Self-Sealing	17
568692	Lid Ductile 6" A0721	65	A0089	Tight Fill Adapter Coax A0088	6
568820	Gasket 6" Lid A0721	65	A0096	Tight Fill Adapter Coax A0070	6
568961	Seal 494335, A1005-505C Lids	53	A0097	Tight Fill Cap	7,68
569106	Lid Ductile 8" A0721	65	A0097-004LP	Tight Fill Cap Low Profile	7
569143	Test Cap Assembly, A1004-210TEST	50	A0097-010	Fill Cap for Tank Probe	7,68
569227	Triple Wiper Seal 494554 Lid	53	A0099	Vapor Cap	9,68
569285	Lid Ductile 8" Lay-in A0721	65	A0099-004LP	Vapor Cap Low Profile	9
569427	Euro Lift Handle A0716	58	A0099-001TEST	Vapor Test Cap	9,50
569461	O-Ring Drop Tube A1100EVR	71	A0179	Extractor Cage	19
569723	Lid Ductile 12" Lay-in A0721	65	A0279	Extractor Cage Test Plug	19
569883	Lid Cast 5" A0721	65	A0333	Hand Pump Spill Container	50
569885	Gasket 5" Lid A0721	65	A0360	Hose Swivel	84
569924	Gasket Kit, A0030-124S, A0076-124S	5,8	A0379	Remote Fill Cage Adjustable	13,37
569989	Rim Gasket, Bellows A1004-316	55	A0479-001	Dip Stick Port	13,37
570012	Triple Wiper Seal A1004-316LID	53	A0500	Splash Guard A2500/A2501	80
571700	Lid Cast 7" A0721	65	A0557EVR	Scuff Guard A4005EVR	76
571702	Gasket 7" Lid A0721	65	A0560	Wrench For Buckeye Cage	19
571814	Drill Fixture for Remote Fill	14	A0585-003	Extractor Pipe Cap Bar Style	19
A0010	Flow Regulator	86	A0716	Composite Manhole	58-59
A0020	Drop Tube	16	A0717	Standard Manhole, Round	60-61
A0020EVR	Drop Tube EVR	16,72	A0717	Standard Manhole, Square	62-63
A0021	Standard Hose	87	A0717	Vault	62-63
A0028	Riser Lock	50	A0718-729	Dispenser Sump	89

Numerical Index

Model Number	Product Description	Page Number
A0720	Monitoring Well Cap & Collar	64
A0721/A0722	Monitoring Well Manhole	64,65
A0727	Well Protector Square	66
A0728	Well Protector Round	66
A0729-048	E-Stop Switch Pedestal	90
A0732	Union Check Valve 1 1/2"	21
A0750	Ball Valve	21
A0785	Vent Downward 1.5" / 2" Female	25
A0997	Tank ID Tag	24
A0998	In-Ground ID Marker	24
A1004	Spill Cont Non-Replacable Poly 5gal	34
A1004-001GAGE	EZ-Gage	54
A1004-001SEN	Sensor Kit	54
A1004-014	Multi-purpose Access Manhole	35
A1004-210A	Spill Cont Repl SW Poly, See -316A	30
A1004-210LID	Lid A1004-210 Series	52
A1004-210S	Spill Cont Repl DW Poly, See -316S	32
A1004-210TEST	Vacuum Apparatus w/Test Adptr	47,50
A1004-316A	Spill Cont Repl SW Poly 16" 5 gal	30
A1004-316LID	Lid A1004-316, A1005-517 Series	52
A1004-316R	SC Retrofit Poly OPW 500&700	42
A1004-316G	Spill Cont Repl DW Poly 16" 5 gal	32
A1004EVR	Spill Cont Non-repl SW Poly, EVR	70
A1004EVR-210A	Spill Cont Repl SW Poly, EVR 5 gal	69
A1004EVR-210S	Spill Cont Repl DW Poly, EVR 5 gal	69
A1004EVR-215A	Spill Cnt Rpl SW Poly, EVR 15 gal	30,69
A1004EVR-215S	Spill Cnt Rpl DW Poly, EVR 15 gal	32,69
A1004EVR-316A	Spill Cnt Rpl SW Poly, EVR 5 gal	30,69
A1004EVR-316S	Spill Cnt Rpl DW Poly, EVR 5 gal	32,69
A1005-010TM	Spill Cnt SST Tank Monitor 2" Riser	35
A1005-015TM	Spill Cnt SST Tank Monitor 4" Riser	35
A1005-501	Spill Cont Non-repl Slip-On 5 gal	34
A1005-505C	SC Retrofit OPW Stnls Stl Insert	40-41
A1005-505CE, CFI	SC Retrofit Franklin Stnls Stl Insert	39
A1005-505CU	SC Retrofit Universal Stnls Stl Insert	43
A1005-505CP	SC Retrofit Pomeco Stnls Stl Insert	44
A1005-505CF5	SC Retrofit Fairfield Stnls Stl Insert	44
A1005-505CPEM	SC Retrofit Pemco Stnls Stl Insert	44
A1005-505CEW	SC Retrofit Emco Stnls Stl Insert	45-46
A1005-505CL	Lids Retrofit Stainless Steel	52
A1005-505DP	Drain Plug Kit A1005-505C	40,41
A1005-505DPE	Drain Plug Kit A1005-505C Epoxy	40,41
A1005-505DPEB	Drain Plug Kit A1005-505CE	39
A1005-505DPU	Drain Plug Kit A1005-505CU	43
A1005-517A	SC Repl SW Slip-On Stnls Steel	31
A1005-517ADEF	SC Repl SW Slip-On SST DEF	31
A1005-517AF	SC Repl SW Remote Fill	36-37
A1005-517G	SC Repl DW Slip-On Stnls Steel	33
A1005-517GDEF	SC Repl DW Slip-On SST DEF	33
A1005-517SF	SC Repl DW Remote Fill	36-37

Model Number	Product Description	Page Number
A1005-518A	SC Repl SW Thread-On Stnls Stl	31
A1005-518G	SC Repl DW Thread-On Stnls Stl	33
A1005-518ADRDEF	SC Repl SW Thread-On DEF Drn	31
A1005-518R	SC Retrofit Stnls Stl OPW 500&700	42
A1005-905	SC Repl Below Grade 5 gal	31
A1005-915	SC Repl Below Grade 15 gal	31
A1100-010	Overfill Prevention Valve	12-15
A1100-05XS	Overfill Prevention Valve Dual Point	14
A1100-05XSFR	OPV Dual Point Remote Fill	14
A1100-06XS	Overfill Prevention Valve Coaxial	15
A1100-08XS	OPV Coaxial Self-Sealing	15
A1100EVR	Overfill Prevention Assembly EVR	71
A2119	SafeBreak 3/4"x3/4" Shearpin	81
A2219	SafeBreak 3/4" Reconnectable	81
A3019	SafeBreak 1" Shear Pin	82
A3219	SafeBreak 1" Reconnectable	82
A4005	Balance Nozzle	77
A4005EVR	Balance Nozzle EVR	74
A4015	Balance Nozzle Short Spout	77
A4041	Splitter Coax	85
A4043	Splitter Not Vapor Ready to Coax	85
A4103	Vent Upward "V" Alum 2"	23
A4110EVR	Swivel Coaxial 45 Degree	75,84
A4119EVR	SafeBreak Coaxial Shear Pin	75,83
A6000	Truck Stop Nozzle	79
A7900-004H	Male Pipe Plug NPSM	13,37
A7901	Pipe Nipple	49
A7901-3xxK	Adptr Kit A1005-505CEW1,CEW2	47
A7904-004	Merchant Steel Coupling	49
A7904-500	Short Pipe Coupling	49
Z0838	Anti-Seize Joint Seal	25
Z0839	Urethane Super Duty Sealant	25

Warranty Policy

Emco Wheaton Retail Corporation service station products are warranted to be free from defects in material and workmanship under normal use and service. Non-EVR Vapor recovery nozzles are warranted for a period of twelve (12) months from date of shipment from Emco Wheaton Retail Corporation or from installation date as specified by the returned warranty card, not to exceed fourteen (14) months from the date of shipment from Emco Wheaton Retail Corporation. This warranty excludes the spout and/or front end components of balance vapor recovery nozzles unless damage is obvious when the nozzle is removed from the shipping carton and the defective nozzle is returned to Emco Wheaton Retail Corporation prior to use and within two (2) months from the date of invoice. EVR vapor recovery hanging hardware components are subject to other specific warranty conditions as stated in a separate warranty policy. Other service station products are warranted for a period of twelve (12) months from the date of manufacture.

Emco Wheaton Retail Corporation shall, at its option, repair or replace that part which proves to be defective. Repaired or replacement nozzles are warranted for the balance of the original warranty period. This warranty is void unless the original purchaser returns the claimed defective item to Emco Wheaton Retail Corporation for inspection to determine whether the claimed defect is covered by this warranty.

The exclusive and sole remedy under this warranty is repair or replacement of the defective part. Emco is not responsible for claims for damage caused by improper installation or maintenance; corrosive fluids; misuse of the product or use the product for other than its intended purpose; or accident, acts of God, or natural phenomena. Emco will not pay for labor or related expenses, nor shall Emco be liable for any incidental, consequential or exemplary damages. This warranty is void if the Emco Wheaton Retail Corporation product has been previously repaired with parts not approved by Emco Wheaton Retail Corporation, or if a nozzle bears the mark or imprint of a company other than Emco Wheaton Retail Corporation, indicating the nozzle has been rebuilt or repaired by a company other than Emco Wheaton Retail Corporation.

EMCO WHEATON RETAIL CORPORATION MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, (WHETHER WRITTEN OR ORAL), INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE.

In the event a nozzle is returned to Emco Wheaton Retail Corporation within the warranty period described above, and when tested is found to be functional and without defect, Emco Wheaton Retail Corporation reserves the right to return the nozzle to the customer or apply a Core Credit (see Nozzle Core Return Program), at Emco Wheaton Retail Corporation's discretion.

In the event of failure within the warranty period, call the Customer Service Department at (800) 234-4394. Describe the problem and provide the product date stamp information to the customer service representative. In the case of a nozzle, provide the serial number. The customer service representative will provide a product complaint number, if applicable. Ship the defective equipment PREPAID, to Emco Wheaton Retail Corporation for repair or replacement.

Emco Wheaton Retail Corporation products should be used in compliance with applicable federal, state and local laws and regulations. Product selection should be based on physical specifications and limitations and compatibility with the environment and material to be handled. All illustrations and specifications are based on the latest product information available at the time of publication. Emco Wheaton Retail Corporation reserves the right to make changes at any time in prices, materials, specifications and models and to discontinue models without notice or obligation.



2300 Industrial Park Drive • Wilson, NC 27893
252-243-0150 • 252-243-4603 (Fax) • www.emcoretail.com

09/2015