




FINISH THOMPSON

PUMPS FOR CHEMICAL PROCESSING APPLICATIONS

DB & SP Series


Coverage Chart

3450 (2900) rpm, 60 (50) Hz



Flows to 253 gpm (51 m³/h)

Heads to 201 feet (61.3 m)



- Sealless magnetic drive
- Polypropylene or PVDF construction for strong corrosion resistance
- Utilizes powerful neodymium boron iron magnets
- Available with NEMA or IEC motors
- Offered with NPT or BSP threaded, union or ANSI/DIN/JIS flanged connections
- Carries a 5-year warranty
- Runs dry for hours (with a carbon bushing)
- Best efficiency in the world
- ATEX & CE certified

Self-priming models:

- Can lift fluids from as deep as 25 feet (7.6 meters) below the pump
- Lifts 18 feet (5.5 meters) in less than 90 seconds

Drum/Barrel Pumps

Flows to 40 gpm (9 m³/h)

Heads to 300 feet (91.4 m)

- Constructed of polypropylene, PVDF, 316 SS, CPVC to handle aggressive, corrosive or hazardous fluids
- Universal 115V and 230V motors
- Variable speed motors available
- Viscosities to 100,000 cP
- Tube lengths to 72 inches (183 cm)
- CE certified
- FDA-compliant materials available
- Explosion proof, ATEX certified, electric or air motors
- Try the convenient on-line drum pump selector at www.finishthompson.com




AP Series

Flows to 321 gpm (80 m³/h)

Heads to 263 feet (80.2 m)

- Sealed centrifugal pumps
- 316 SS construction
- Horizontal or vertical configurations available
- Carbon, Ceramic, FKM, EPDM, SiC, Buna, or Kalrez® seal materials (Horizontal models)
- Temperatures to 300° F (149° C)
- Available with NEMA or IEC motors
- FDA-compliant materials available
- ATEX & CE certified



*Kalrez® is a registered trademark of DuPont Performance Elastomers

ULTRACHem UC Series

Flows to 1450 gpm (329 m³/h)

Heads to 314 feet (95.7 m)


- Sealless magnetic drive
- ANSI dimensional
- Rugged ductile iron housing lined with DuPont Tefzel® ETFE)
- ANSI/ISO/DIN/PN flanges
- Utilizes powerful neodymium boron iron magnets
- Runs dry with carbon bushing and SiC Dri-Coat®
- Modified concentric volute, partial splitter, or conventional volute for industry lowest radial loads
- Available with NEMA or IEC motors
- ATEX certified

*Tefzel® Fluoropolymer Resin is a registered trademark of DuPont




Coverage Chart

3450 (2900) rpm, 60 (50) Hz



1750 (1450) rpm, 60 (50) Hz



MADE IN THE USA



finishthompson.com

FINISH THOMPSON INC. - HEADQUARTERS

921 Greengarden Road | Erie, PA 16501
800.934.9384 | ph 814.455.4478 | fx 814.455.8518
email fti@finishthompson.com

FINISH THOMPSON INC. - EUROPE CENTER

Otto-Hahn-Strasse 16 | Maintal, D-63477 Germany
49 (0)6181-90878-0 | fx 49 (0)6181-90878-18
email fti@finishthompson.com