



# Model 515 Series AST Remote Spill Container

SPECIFICATION SHEET

## Application

Remote fill containers provide containment for small spills that may occur at the fill point during remote filling operations.

## Features and Details

- Single connections in 2", 3" or 4" female threads
- Dual connections in 2" or 3" (may be combined)
- 15 gallon capacity
- Gas spring cylinder holds the lid in the up position when fueling
- Lockable with a padlock
- Weather-tight enclosure
- Vent cover
- 2 Inch female threaded return pump connection
- 1" NPT drain with locking ball valve
- Base to centerline connection height 30" to 48" pedestal model
- Base to centerline connection height 31" to 47" Four leg stand model
- Container 22-1/2" wide x 24" deep x 24-1/4" height
- Four leg stand ships knocked down and requires minimal assembly

## Materials of Construction

- Container and lid... 12 gauge steel, powder coated white
- Pipe connection... powder coated steel
- Pedestal mount... Schedule 40 steel pipe, powder coated steel white
- Adjustable four-leg stand... 10 gauge stainless steel or powder coated steel white
- Ball valve... brass
- Gasket... Teflon

## Code Compliance

CAN-ULC-S663-11; Florida DEP EQ 535

Item numbers and drawings on next page.



515  
(pedestal mount)



515  
(4 leg stand)





Item Number	A	B	C	D	E	F	G	H
515---0200 AC	P	1	2"	B	Y	23"	24"	136.50
515---0300 AC	P	1	3"	B	Y	23"	24"	138.0
515---0400 AC	P	1	4"	B	Y	23"	24"	140.0
515---2200 AC	P	2	2" & 2"	B	Y	23"	24"	147.0
515---2300 AC	P	2	3" & 3"	B	Y	23"	24"	150.0
515---3200 AC	P	2	2" & 3"	B	Y	23"	24"	148.50
515-ST0200 AC	S	1	2"	B	Y	23"	24"	136.50
515-ST0300 AC	S	1	3"	B	Y	23"	24"	138.0
515-ST0400 AC	S	1	4"	B	Y	23"	24"	140.0
515-ST2200 AC	S	2	2" & 2"	B	Y	23"	24"	147.0
515-ST2300 AC	S	2	3" & 3"	B	Y	23"	24"	150.0
515-ST3200 AC	S	2	2" & 3"	B	Y	23"	24"	148.50
515OEM0200 AC	T	1	2"	T	Y	23"	24"	103.0
515OEM0300 AC	T	1	3"	T	Y	23"	24"	101.0
515OEM2200 AC	T	2	2" & 2"	T	Y	23"	24"	107.0
515OEM2300 AC	T	2	3" & 3"	T	Y	23"	24"	103.0
515ST-0100 AS	Four leg adjustable stand, powder coated							
515STS0100 AS	Four leg adjustable stand, stainless steel							

**SPECIFICATION OPTIONS:**

- A**—Mounting connection: Pedestal mount female thread (P), four leg stand (S), or back mount 4 tabs (T)
- B**—Number of ports
- C**—Port sizes, Female NPT
- D**—Port location, Back (B), Top (T)
- E**—ULC Listed (Y), Not Listed (N)
- F**—Width (inches) (+/- 1/2")
- G**—Height (inches) (+/- 1/2")
- H**—Shipping weight (lbs)

