



# Model 515SD Series AST Remote Spill Container

SPECIFICATION SHEET

## Application

Remote fill containers provide containment for small spills that may occur at the fill point during remote filling operations.

## Features and Details

- Single connections in 2", 3" or 4" female threads
- Dual connections in 2" or 3" (may be combined)
- 15-gallon capacity
- Gas spring cylinder holds the lid in the up position when fueling
- Lockable with a padlock
- Weather-tight enclosure
- Vented cover
- 2" female threaded return pump connection
- Integrated sump drain with 1/2" with locking ball valve
- Container 22 1/2" wide x 24" deep x 24 1/4" height
- Four-leg stand ships knocked down and requires minimal assembly

## Materials of Construction

- Container and lid... 12 gauge stainless steel
- Pipe connection... stainless steel
- Pedestal mount... schedule 40 stainless steel pipe
- Adjustable four-leg stand... 10 gauge stainless steel
- Ball valve... stainless
- Flange connection gasket... Teflon®

## Code Compliance

CAN-ULC-S663-11\*; Florida DEP EQ 535

*\*Low profile stand excluded from listing.*



515SD



515SDST



515SD shown on  
515STSL0100 AS

Item numbers and drawings on next page...



MORRISON BROS. CO.



Item Number	A	B	C	D	E	F	G
515SD-0200 AC	P	1	2"	Yes	23"	24"	155.0
515SD-0300 AC	P	1	3"	Yes	23"	24"	156.0
515SD-0400 AC	P	1	4"	Yes	23"	24"	157.0
515SD-2200 AC	P	2	2" & 2"	Yes	23"	24"	159.0
515SD-2300 AC	P	2	3" & 3"	Yes	23"	24"	160.0
515SD-3200 AC	P	2	2" & 3"	Yes	23"	24"	160.0
515SD-0200 ACO	N	1	2"	Yes	23"	24"	155.0
515SD-0300 ACO	N	1	3"	Yes	23"	24"	156.0
515SD-0400 ACO	N	1	4"	Yes	23"	24"	157.0
515SD-2200 ACO	N	2	2" & 2"	Yes	23"	24"	159.0
515SD-2300 ACO	N	2	3" & 3"	Yes	23"	24"	160.0
515SDST0200 AC	S	1	2"	Yes	23"	24"	
515SDST0300 AC	S	1	3"	Yes	23"	24"	
515SDST0400 AC	S	1	4"	Yes	23"	24"	
515SDST2200 AC	S	2	2" & 2"	Yes	23"	24"	
515SDST2300 AC	S	2	3" & 3"	Yes	23"	24"	
515ST-0100 AS	Four-leg adjustable stand, powder coated						
515STS0100 AS	Four-leg adjustable stand, stainless steel						
515STSL0100 AS	Four-leg, low profile stand, stainless steel						

**SPECIFICATION OPTIONS:**

- A**—Mounting connection: Pedestal mount (P), four-leg stand (S), NO post or stand (N)
- B**—Number of ports
- C**—Size: Female NPT threads
- D**—Drain: Yes (Y), No (N)
- E**—Width (inches) (+/- 1/2")
- F**—Depth (inches) (+/- 1/2")
- G**—Shipping weight (lbs)

\*Order low profile stand and fill box separately.

