FUELMASTER 2500 Series



Your Fixed Site Fuel Management Solution

The FuelMaster 2500 series is engineered to provide a turnkey fuel management solution for capturing fuel transactions in any location. Each unit is built to custom specifications to meet the precise needs of the fueling site. With fuel access 24/7, organizations can be confident that transactions are being accurately tracked providing increased accountability & physical security at the fueling site as well as eliminating unauthorized use of fuel.

Durable

Built to military specs with aircraft-quality aluminum and tested in conditions ranging from -40F to +140F

Customizable

No matter how large or small your fueling operations may be, we have tailored solutions to fit your needs

Compatible

Interfaces with mechanical and electrical dispensers in the retail or commercial markets

Tank Interface

Integrates with a variety of automatic tank gauge manufacturers

Fleet Integration

Transactional data can be exported to most fleet maintenance or accounting programs



FUELMASTER 2500 Series



MODEL NUMBERS

FMU2500 Prokee FMU2540 Smartcard

FMU2550 Prokee, Credit Card FMU2560 Smartcard, Credit Card

FMU2580 Prokee, Smartcard

All available with either 50A Pump relay or Dual Control relay. All can control up to 8 hoses.

TECHNICAL SPECIFICATIONS

Hardware

- Mechanical Dispensers
- Electronic Dispensers
- Tank Monitor Units
- Manual Firmware Updates
- Optional Advanced Surge Protection

Compliance

- Weights and Measures Compliant
- PADSS Compliant

Communication:

- Dial Up (POTS) Connection
- Integrated Wired Ethernet
- Wi-Fi with 3rd Party Bridge
- Cellular with 3rd Party Cellular Modem

Fuel Security & Authorization

- Product / Quantity Limits
- Odometer Reasonability
- Lube Bay Operations

User Access Devices

- Prokee / Prox / Magstripe (Local Auth)
- Prepaid Card
- Smartcard
- Bank / Fleet Card

Credit/Fleet Card Authorization

- Multiple Credit Card Hosts
- Discounts by Specific Credit Card
- Multiple Fleet Card Networks
- Local Authorization

Mobile Fueling

- Non-Automated Mobile Fueling
- Automated Mobile Fueling

Software Platform

• FMPlus (client based)

System Features

- Preventative Maintenance Alerts
- Invoicing
- Exports
- Reports
- Manual Software Updates
- Inventory Management
- User Accountability

Operating Temperatures

• -40F to 140F

Dimensions

• Enclosure: 19"W x 13"H x 10"D

• Pedestal: 12"W x 48"H x 6"D

Certifications

- UL-1238 Ed. 6
- CSA C22.2 No. 22 (R2014)
- CSA C22.2 No. 142 (R2013)
- EN 61010-1:2010
- FCC Certified

